



(19) **United States**

(12) **Patent Application Publication**

Tsai et al.

(10) **Pub. No.: US 2011/0090611 A1**

(43) **Pub. Date: Apr. 21, 2011**

(54) **PARTICLE CHARGER WITH SHEATH AIR FLOW FOR ENHANCING CHARGING EFFICIENCY**

Publication Classification

(51) **Int. Cl.**
H05F 3/00 (2006.01)
(52) **U.S. Cl.** 361/225

(75) Inventors: **Chuen-Jinn Tsai**, Hsinchu County (TW); **Lin Guan-Yu**, Taipei County (TW); **Chen Hui-Lin**, Keelung City (TW)

(57) **ABSTRACT**

A particle charger with sheath air flow for enhancing charging efficiency includes a housing and a discharge wire. The housing has a charging chamber for accommodating the discharge wire, a particle inlet, a sheath air inlet, an outlet and an accelerating channel. A clean sheath air is guided through the sheath air inlet into the charging chamber to surround charged particles, reducing deposition of charged particles on the inside wall of the housing. A relatively small annular gap of accelerating channel accelerates the charged particles to exit the particle charger, and therefore minimized the particle electrostatic loss due to depositing on the inner surface of the housing. Additionally, uncharged particles approach the discharge wire axially, and charged particles move away radially. It is helpful for the charged particles to diffuse rapidly and uniformly, thereby enhancing the charging efficiency.


(73) Assignee: **NATIONAL CHIAO TUNG UNIVERSITY**, Hsinchu City (TW)

(21) Appl. No.: **12/654,667**

(22) Filed: **Dec. 29, 2009**

(30) **Foreign Application Priority Data**

Oct. 15, 2009 (TW) 98134998






FIG. 1




FIG. 2




FIG. 3

PARTICLE CHARGER WITH SHEATH AIR FLOW FOR ENHANCING CHARGING EFFICIENCY

BACKGROUND OF THE INVENTION

[0001] 1. Field of the Invention

[0002] The present invention relates to air pollution control technology or measuring technology, and more particularly to a particle charger with sheath air flow for enhancing charging efficiency.

[0003] 2. Description of the Related Art

[0004] Particle charging technology has been widely applied to air pollution control and particle concentration measurement. Particle charging efficiency directly affects the performance of the related air pollution control equipment and the sensitivity and accuracy of the particle concentration measuring instrument. Therefore it is important to improve the charging efficiency of a particle charging equipment.

[0005] U.S. Pat. No. 5,973,904 discloses a particle charging apparatus, which includes a housing having a longitudinal axis extending between an inlet and an outlet of the housing with a stream of aerosol particles flowing parallel to the longitudinal axis. An electric field is created within the housing for directing a stream of unipolar ions toward the outlet for charging the stream of aerosol particles. Additionally, a clean sheath air is created between the stream of aerosol particles and the housing to reduce charged particle loss within the housing. But the sheath air velocity is not properly controlled and is not high enough to prevent loss of charged particles on the wall.

[0006] In addition, the aforesaid particle charging apparatus needs radioactive isotope to achieve discharging, a metal screen to create a clean sheath and a complicated design to create an axial electric field. These technical features complicate the structure of the particle charging apparatus, resulting in the increase of cost and causing the apparatus unable to be miniaturized for use in a portable particle measuring instrument.

SUMMARY OF THE INVENTION

[0007] The main object of the present invention is to provide a particle charger with high velocity sheath air flow near the inner wall of the charger for enhancing charging efficiency, which has a simple structure and can be optimized for smaller size.

[0008] To achieve this and other objectives of the present invention, a particle charger with high speed sheath air flow for enhancing charging efficiency comprises a housing and a discharge wire. The housing is made of electrically conductive material, comprising a charging chamber, a particle inlet, an outlet and a first accelerating channel. The particle inlet is disposed in communication with the charging chamber. The first accelerating channel with a small annular gap is connected between the charging chamber and the outlet. The discharge wire is arranged in the charging chamber of the housing. The charging chamber and the particle inlet of the housing both have a circular cross section. The charging chamber, the particle inlet and the discharge wire extend along the same longitudinal axis. The particle charger further comprises an insulative cover, a first flow guide sleeve, a second flow guide sleeve, an insulative cover, a conductive rod and an electrode holder. The first flow guide sleeve is mounted inside the housing. The gap of the first accelerating

channel is defined between the first flow guide sleeve and the inside wall of the housing. Further, the first flow guide sleeve comprises an outside annular groove extending around the periphery thereof at a location corresponding to the outlet of the housing. The housing further comprises a sheath air inlet. The second accelerating channel is connected between said charging chamber and said sheath air inlet, and included a gap defined between said second flow guide sleeve and an inside wall of said housing. The second flow guide sleeve comprises an outside annular groove extending around the periphery thereof at a location corresponding the sheath air inlet, and an axial hole disposed in communication with the charging chamber and the particle inlet of the housing. The insulative cover is attached to the housing, having a center hole for the passing of the conducting rod. The electrode holder is mounted inside the housing, comprising an insulative holder body and a metal conductor. The insulative holder body is connected to the bottom end of the conducting rod. The metal conductor is mounted in the insulative holder body and electrically connected with the conducting rod and the discharge wire. Further, the first flow guide sleeve has a center hole for the passing of the conducting rod.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] FIG. 1 is the block diagram of the particle charger with sheath air flow for enhancing charging efficiency in accordance with the present invention.

[0010] FIG. 2 is an exploded view of the particle charger with sheath air flow for enhancing charging efficiency in accordance with the present invention.

[0011] FIG. 3 is a sectional view of the particle charger with sheath air flow for enhancing charging efficiency in accordance with the present invention.

DETAILED DESCRIPTION OF THE INVENTION

[0012] Referring to FIGS. 1~3, a particle charger 10 in accordance with the present invention is shown comprising a housing 20, a first flow guide sleeve 30, a second flow guide sleeve 40, an insulative cover 50, a conducting rod 60, an electrode holder 70 and a discharge wire 80.

[0013] The cylindrical housing 20 is made from an electrically conducting material, defining a longitudinal axis A. The inside of the housing 20 has a charging chamber 21, a particle inlet 22, a sheath air inlet 23, an outlet 24, a first accelerating channel 25 and a second accelerating channel 26. The particle inlet 22 is in communication with the charging chamber 21. The first accelerating channel 25 is connected between the charging chamber 21 and the outlet 24. The first accelerating channel 25 has a small annular gap 25 formed between the first flow guide sleeve 30 and an inside wall of the cylindrical housing 20. The second accelerating channel 26 is connected between the charging chamber 21 and the sheath air inlet 23. The second accelerating channel 26 has small annular gap 26 formed between the second flow guide sleeve 40 and an inside wall of the cylindrical housing 20.

[0014] The first flow guide sleeve 30 and the second flow guide sleeve 40 are cylindrical and mounted inside the housing 20. The first flow guide sleeve 30 and the second flow guide sleeve 40 each have an annular groove 32 or 42 extending around the periphery. The two annular grooves 32 and 42 are disposed corresponding to the sheath air inlet 23 and the outlet 24 respectively. The first flow guide sleeve 30 has a center hole 34, and a bottom conical surface 36. The second

flow guide sleeve **40** has an axial hole **44** in communication between the charging chamber **21** and the particle inlet **22**.

[0015] The insulative cover **50** is a single-piece member prepared from an electrically insulative material, having a cylindrical large diameter portion **54** and a cylindrical small diameter portion **56** axially connected together. The cylindrical large diameter portion **54** is disposed at the top side of the cylindrical small diameter portion **56**. The cylindrical small diameter portion **56** is inserted into the center hole **34** of the first flow guide sleeve **30**. Further, the insulative cover **50** has a center hole **52** and an inner thread (not shown) extending around the inside wall of the center hole **52**.

[0016] The conducting rod **60** is a metal member mounted in the center hole **52** of the insulative cover **50**. The conducting rod **60** has an outer thread (not shown) meshed with the inner thread (not shown) in the center hole **52** of the insulative cover **50**.

[0017] The electrode holder **70** is mounted inside the housing **20**, comprising an electrically insulative holder body **72** and a metal conductor **74**. The electrically insulative holder body **72** is threaded onto the bottom end of the conducting rod **60**. The metal conductor **74** is inserted into the inside of the electrically insulative holder body **72** and electrically connected to the conducting rod **60**. The cylindrical small diameter portion **56** of the insulative cover **50**, the conducting rod **60** and the electrode holder **70** are inserted into the center hole **34** of the first flow guide sleeve **30**.

[0018] The discharge wire **80** is arranged inside the charging chamber **21** of the housing **20** and electrically connected to the conducting rod **60** through the metal conductor **74** of the electrode holder **70**. The discharge wire **80** extends along the longitudinal axis A of the housing **20**.

[0019] The conducting rod **60** is connected with a high-voltage DC power source (not shown), whereas the housing **20** is grounded, thus electric field can be formed between the discharge wire **80** and the housing **20**. When a stream of particles is guided through the particle inlet **22** into the charging chamber **21**, they are charged by the discharge wire **80** due to diffusion and field charging mechanisms. Thereafter, charged particles go through the first accelerating channel **25** and the outlet **24** to the outside of the particle charger **10** for further application. A high speed clean sheath air is guided through the sheath air inlet **23** and the second accelerating channel **26** into the charging chamber **21** to prevent deposition of charged particles on the inside wall of the housing **20**.

[0020] In addition, the first accelerating channel **25** has a relatively small annular gap which helps accelerating the flow and guiding charged particles to exit the particle charger **10** rapidly, and therefore the particle electrostatic loss due to depositing on the inner surface of the housing **20** is minimized. Further, the charging chamber **21**, the particle inlet **22** and the discharge wire **80** extend along the same longitudinal axis A so that particles that approach the discharge wire **80** axially are charged in the charging chamber **21**. The smooth and unobstructed route is helpful for the charged particles to diffuse rapidly and uniformly, thereby enhancing the charging efficiency.

[0021] Although a particular embodiment of the invention has been described in detail for purposes of illustration, various modifications and enhancements may be made without

departing from the spirit and scope of the invention. Accordingly, the invention is not to be limited except as by the appended claims.

What is claimed is:

1. A particles charger, comprising:

a housing made from an electrically conductive material, said housing comprising a charging chamber, a particle inlet, an outlet and a first accelerating channel, said particle inlet being disposed in communication with said charging chamber, said first accelerating channel being connected between said charging chamber and said outlet and including a gap; and

a discharge wire arranged in said charging chamber of said housing.

2. The particle charger as claimed in claim 1, wherein said charging chamber and said particle inlet of said housing each have a circular cross section; said charging chamber, said particle inlet and said discharge wire extend along one same longitudinal axis.

3. The particle charger as claimed in claim 1, further comprising a first flow guide sleeve mounted inside said housing; said gap of said first accelerating channel is defined between said first flow guide sleeve and an inside wall of said housing.

4. The particle charger as claimed in claim 3, wherein said first flow guide sleeve comprises an outside annular groove extending around the periphery thereof at a location corresponding to said outlet of said housing.

5. The particle charger as claimed in claim 1, further comprising a second flow guide sleeve mounted inside said housing, said housing further comprising a sheath air inlet and a second accelerating channel being connected between said charging chamber and said sheath air inlet, said second accelerating channel including a gap defined between said second flow guide sleeve and an inside wall of said housing.

6. The particle charger as claimed in claim 5, wherein said second flow guide sleeve comprises an outside annular groove extending around the periphery thereof at a location corresponding said sheath air inlet.

7. The particle charger as claimed in claim 5, wherein said second flow guide sleeve comprises an axle hole disposed in communication with said charging chamber and said particle inlet of said housing.

8. The particle charger as claimed in claim 1, further comprising an insulative cover, a conducting rod and an electrode holder, said insulative cover being attached to said housing and having a center hole for the passing of said conducting rod, said electrode holder being mounted inside said housing and comprising an insulative holder body and a metal conductor, said insulative holder body being connected to a bottom end of said conducting rod, said metal conductor being mounted in said insulative holder body and electrically connected with said conducting rod and said discharge wire.

9. The particle charger as claimed in claim 8, further comprising a first flow guide sleeve mounted inside said housing, said first flow guide sleeve having a center hole for the passing of said conducting rod.

* * * * *