

Reference

Chapter 2

- [1] T.D. Moustakas, D.A. Anderson, W. Paul, Solid State Commun. 23. (1977) 155.
- [2] M. Kitigawa, K. Setsune, Y. Marabe, T. Hirao, Jpn. J. Appl. Phys. 27 (1988) 2026.
- [3] G.N. Parsons, C. Wang, M.J. Williams, G. Lucovsky, Appl. Phys. Lett. 56. (1990) 1895.
- [4] Y. Hishikawa, S. Tsuge, N. Nakamura, S. Tsuda, S. Nakano, Y. Kuwano, J. Appl. Phys. 69 (1991) 508.
- [5] J.P. Conde, K.K. Chan, J.M. Blum, J.J. Cuomo, J. Appl. Phys. 71. (1992) 3981.
- [6] A. Suzuki, G. Ganguly, A. Matsuda, Appl. Phys. Lett. 63 (1993) 2806.
- [7] J.P. Conde, K.K. Chan, J.M. Blum, M. Arienzo, P.A. Monteiro, J.A. Ferreira, V. Chu, N. Wyrsh, J. Appl. Phys. 73 (1993) 1826.
- [8] T. Kamei, G. Ganguly, N. Hata, A. Matsuda, J. Non-Cryst. Solids. 164-166 (1993) 43.
- [9] M.K. Cheung, M.A. Petrich, J. Appl. Phys. 73 (1993) 3237.
- [10] G. Ganguly, A. Matsuda, Phys. Rev. B 47 (1993) 3661.
- [11] P. Roca i Cabarrocas, Appl. Phys. Lett. 65 (1994) 1674.
- [12] M. Goto, H. Toyoda, M. Kitagawa, T. Hirao, H. Sugai, Jpn. J. Appl. Phys. Part 2-Lett. 35 (1996) L1009.
- [13] E. Srinivasan, D.A. Lloyd, G.N. Parsons, J. Vacuum Sci. Technol. A 15

(1997) 77.

[14] M.B. Schubert, Thin Solid Films 337 (1999) 240.

[15] O.S. Panwar, C. Mukherjee, R. Bhattacharyya, Solar Energy Mater. Solar Cells 57 (1993) 373.

[16] S.He,H. Nishiki, J. Hartzell, and Y.Nakata SID 00 DIGEST, pp.278-281 (2000).

[17] H.Gleskova, S. Wagner, Z.suo, J. Non-Cryst. Solids 266-269, pp.1320-1324(2000).

[18] S. Po;ach, D. Horst, G. Maier, T. Kallfass, and E. Lueder, SPIE, vol. 3649, pp. 31-39, 1999.



Chapter 3

[1]A. Sazonov, A. Nathan, and D. Striakhilev, “ Materials optimization for thin film transistors fabricated at low temperature on plastic substrate,” Journal of Non-Crys-talline Solids, vol. 266-269, pp. 1329-1334, 2000.

[2]G. N. parsons, J. Non-cryst. Solids, “Surface reactions in a very-low-temperature hydrogenated amorphous silicon deposition, and application to thin film transistor,” vol. 266-269, pp. 23-32, 2000.

[3]S. M. Gates, “Prospects for active matrix displays on plastic,” Mat. Res. Soc. Symp. Proc., vol. 467, pp. 843-849, 1997.



Chapter 4

- [1].C. P. Jarrett, R. H. Friend, A. R. Brown, and D. M. de Leeuw, *J. Appl. Phys.* **77**, 6829 (1995).
- [2].G. C. R. Lloyd, N. Sedghi, M. Raja, R. Di Lucrezia, S. J. Higgins, and W. Eccleston, *Mater. Res. Soc. Symp. Proc.* **708**, BB10.57 (2002)
- [3]. Y.-Y. Lin, D. J. Gundlach, S. F. Nelson, T. N. Jackson, *IEEE Trans. Electron Dev.*, **44**(8), 1325 (1997).
- [4].H. Sirringhaus, P. J. Brown, R. H. Friend, M. M. Nielsen, K. Bechgaard, B. M. W. Langeveld-Voss, A. J. H. Spiering, R. A. J. Janssen, E. W. Meijer, P. T. Herwig, D. M. de Leeuw, *Nature*, **401**, 685 (1999).
- [5]. C. D. Sheraw, L. Zhou, J. R. Huang, D. J. Gundlach, T. N. Jackson, M. G. Kane, I. G. Hill, M. S. Hammond, J. Campi, B. K. Greening, J. Franc J. West, *Appl. Phys. Let.*, **80**(2), 1088 (2002).
- [6]. A. Salleo, M. L. Chabinyc, M. S. Yang, R. A. Street, *Appl. Phys. Let.*, **81**(23), 4383 (2002).
- [7].C. K. Song, K. D. Kilm, Y. X. Xu, M. W. Lee, K. H. Kim, **SID 03 DIGEST**, 228 (2003).