

LIST OF TABLES

Table 2.1	Parameters of DMT modulation in VDSL standard.....	8
Table 4.1	Control signals at each stage in Figure 4.9	32
Table 4.2	Comparison hardware of different pipelined FFT processor	38
Table 4.3	Comparison utilization of different pipelined FFT processor.....	38
Table 4.4	Comparison hardware of different memory based FFT processor.....	38
Table 5.1	Select addition control signal with radix 2, 4, 8.....	50
Table 5.2	Select addition control signal with radix 4, 8.....	52
Table 5.3	Select addition control signal with radix 8.....	52
Table 5.4	Interval regions of twiddle factor design	56
Table 5.5	Description of twiddle factor parameters.....	57
Table 5.6	Some various coefficient values with different regions of 64-point FFT ..	60
Table 5.7	Description of SRAM parameters.....	65
Table 5.8	Function of eight types of commutator with the help of 64-point FFT	68
Table 5.9	Mode control of FFT with variable length.....	72
Table 5.10	Representation of data address generation scheme at different stages of fixed radix-8 for 512-point FFT.....	74
Table 5.11	Representation of data address generation scheme at different stages of mixed radix-8+2 for 1024-point FFT.....	75
Table 5.12	Representation of data address generation scheme at different stages of mixed radix-8+4 for 2048-point FFT.....	76
Table 5.13	Description of coefficient address generation parameters in Figure5.30...	78
Table 5.14	Address (m) generation in W^m at different stages for 512-point FFT	79
Table 5.15	Address (m) generation in W^m at different stages for 1024-point FFT ...	80
Table 5.16	Address (m) generation in W^m at different stages for 2048-point FFT	81
Table 5.17	Address (m) generation in W^m at different stages for 4096-point FFT ...	82
Table 5.18	Memory assignment for a 512-point FFT	84
Table 5.19	Memory assignment for a 1024-point FFT	85
Table 5.20	Memory assignment for a 2048-point FFT	86

Table 5.21	Performance comparisons	93
Table 6.1	FFT pin configuration	107
Table 6.2	Features of our FFT chip design	110



LIST OF FIGURES

Figure 2.1 The VDSL network.....	5
Figure 2.2 Wire pair coupling causing Near End Crosstalk and Far End Crosstalk.....	6
Figure 2.3 Schematic diagram of subcarrier in frequency domain of DMT system.....	8
Figure 2.4 Block diagrams of DMT system.....	9
Figure 3.1 Separation procedure for radix-2 algorithm	12
Figure 3.2 Butterfly structure of radix-2 DIF FFT	13
Figure 3.3 Signal flow graph of complete decomposition of a 16 point radix-2 DIF FFT	14
Figure 3.4 Butterfly structure for radix-4 algorithm.....	15
Figure 3.5 Signal flow graph of complete decomposition of a 16 point radix-4 DIF FFT	16
Figure 3.6 Butterfly structure of radix-8 algorithm	18
Figure 3.7 Signal flow graph of a 8-point radix-8 DIF FFT	19
Figure 3.8 Butterfly structure of split radix-2/4 algorithm	20
Figure 3.9 Computation of a 16-point split radix-2/4 algorithm	21
Figure 3.10 Butterfly structure of radix-2/8 algorithm	22
Figure 3.11 A 16-point split radix-2/8 algorithm	23
Figure 4.1 Pipeline architecture	26
Figure 4.2 A 16- point radix-2 single path delay feedback architecture	27
Figure 4.3 Routing of data diagram for R2SDF (N=16).....	27
Figure 4.4 A 16- point radix-4 single path delay feedback architecture	28
Figure 4.5 Timing diagram for R4SDF (N=16).....	28
Figure 4.6 A 16-point radix-4 multiple path delay commutator architecture	29
Figure 4.7 Timing diagram for R4MDC (N=16)	30
Figure 4.8 A 16- point radix-4 single path delay commutator architecture	31
Figure 4.9 Delay commutator for R4SDC at each stage.....	32
Figure 4.10 Action of switch in Figure 4.9 for 16-point FFT	32
Figure 4.11 Timing diagram for 16-point R4SDC	33

Figure 4.12 Schematic diagram of memory architecture.....	34
Figure 4.13 Single memory-based architecture block diagram	34
Figure 4.14 Dual memory-based architecture block diagram.....	35
Figure 4.15 Cache memory-based architecture block diagram	35
Figure 4.16 Radix-2 memory-based FFT processor	37
Figure 4.17 Radix-4 memory-based FFT processor	37
Figure 5.1 Schematic block diagrams of internal architecture for proposed architecture.....	41
Figure 5.2 Simulation of FFT Processor control signal.....	42
Figure 5.3 Block diagram of serial to parallel design.....	43
Figure 5.4 Signal flow of the radix-8 butterfly operation.....	44
Figure 5.5 Block diagrams of implementation hardware with butterfly operation.....	45
Figure 5.6 Schematic data path of the pipelined butterfly radix-8 processing element..	46
Figure 5.7 Schematic data path of the pipelined butterfly radix-4 processing element..	47
Figure 5.8. Schematic data path of the pipelined butterfly radix-2 processing element.	47
Figure 5.9 Sharing addition hardware with radix- 2, 4, 8.....	49
Figure 5.10 Sharing addition hardware with radix- 4, 8.....	51
Figure 5.11 (a) Multiplication with constant twiddle factor W_8^1 (b) Multiplication with constant twiddle factor W_8^3	54
Figure 5.12 Implementation hardware of $\frac{\sqrt{2}}{2}$ in Figure 5.11	54
Figure 5.13 Complex multiplier with four real multiplications and two real additions .	55
Figure 5.14 Complex multiplier with three real multiplications and five real additions	55
Figure 5.15 Twiddle factor boundary diagram.....	57
Figure 5.16 Block diagram of a twiddle factor circuit design for fixed FFT length.....	61
Figure 5.17 Twiddle factor mapping diagram for fixed FFT length.....	61
Figure 5.18 Block diagram of a twiddle factor circuit design for variable FFT length..	63
Figure 5.19 Concept of twiddle factor interchanging for variable FFT length.....	63
Figure 5.20 Sketch block diagram of our SRAM model	64
Figure 5.21 Basic block diagram of dual port SRAM	65
Figure 5.22 Detailed block diagram of our SRAM design	66
Figure 5.23 Function of commutator with the help of 64-point data index.....	68

Figure 5.24 Eight types of read/write commutators.....	69
Figure 5.25 Schematic diagram of data address generator for variable length.....	70
Figure 5.26 Address generation scheme with different stages of 512-point FFT	72
Figure 5.27 Address generation scheme with different stages of 4096-point FFT	72
Figure 5.28 Address generation scheme with different stages of 1024-point FFT	73
Figure 5.29 Address generation scheme with different stages of 2048-point FFT	73
Figure 5.30 Block diagram of twiddle factor coefficient address generation.....	78
Figure 5.31 Rotation bit number scheme for <i>romaddr_mul</i> (<i>n</i>) with different stages	78
Figure 5.32 Workflow of the implementation hardware rules for address control	87
Figure 5.33 Address mapping for mixed radix-8+2 case.....	88
Figure 5.34 Address mapping for mixed radix-8+4 case.....	88
Figure 5.35 Eight types of address commutator	89
Figure 5.36 Read and write data mapping for mixed radix8+2 algorithm	90
Figure 5.37 Read and write data mapping for mixed radix8+4 algorithm	91
Figure 5.38 Data reorder design.....	93
Figure 6.1 Fixed and mixed radix-8 FFT algorithm flowchart.....	96
Figure 6.2 Comparison of input and output data for 512 –point FFT simulation with radix-8 algorithm	97
Figure 6.3 Processing flow chart of simulation with twiddle factor and databus wordlength	99
Figure 6.4 Simulation of the optimal wordlength for data bus and twiddle factor.....	100
Figure 6.5 Flow chart of FFT chip design	101
Figure 6.6 Simulation waveform of 512-point with read/ write address generation	102
Figure 6.7 Simulation of 2048-point with input/output data and butterfly operation...	102
Figure 6.8 Verification for FFT IC system block.....	103
Figure 6.9 Verification for FFT IC flowchart	104
Figure 6.10 Compare coding and decoding data to verify FFT IC design	105
Figure 6.11 A sketch of FFT chip floorplan.....	106
Figure 6.12 FFT package definition.....	106
Figure 6.13 Layout view of our variable length FFT chip.....	110