


TABEL OF CONTENTS

ABSTRACT (Chinese)	i
ABSTRACT (English)	ii
ACKNOWLEDGEMENTS	iii
TABLE OF CONTENTS	iv
LIST OF TABLES	vi
LIST OF FIGURES	vii
CHAPTER 1 Motivation of this research	1
CHAPTER 2 A Planar Shaped-Beam Antenna with metal grating.....	5
2.1 Structure Configuration.....	5
2.2 Method of Analysis	7
2.3 Numerical and Experimental Results.....	11
2.3.1 Measurement results of antenna.....	11
2.3.2 Effect of the dielectric slab thickness on the radiation pattern	33
2.3.3 Effect of the relative dielectric constant on the radiation pattern	35
2.3.4 Effect of the number of metal strips on the radiation pattern	36
2.3.5 Effect of the line source position on the radiation pattern	37
2.3.6 Frequency range of operation	39
2.3.7 Shaped-bean antenna for wireless LAN band operation.....	40
CHAPTER 3 A Planar Shaped-Beam Antenna with dielectric grating.....	44
3.1 Structure Configuration.....	44
3.2 Method of Analysis	46
3.3 Numerical Results	52
3.3.1 Effect of the relative dielectric constant on the radiation pattern	52

3.3.2	Effect of the aspect ratio of the grating layer on the radiation pattern	55
3.3.3	Effect of the dielectric grating thickness on the radiation pattern	58
3.3.4	Effect of the line source position on the radiation pattern	60
3.3.5	Frequency range of operation	62
CHAPTER 4	Concluding Remarks.....	64
REFERENCES	65
APPENDIX I	Input-Output relation for a metal grating : Mode-matching analysis.....	68
APPENDIX II	Mode function in the dielectric grating layer.....	71
APPENDIX III	Far-field Calculation	76
PERSONAL INFORMATION	78	
(CHINESE)		
PUBLICATION LIST	79



LIST OF FIGURES

1. Figure 1(a). The planar shaped-beam antenna; structure configuration and parameters assignment	5
2. Figure 1(b) The planar shaped-beam antenna; front view	6
3. Figure 1(c) The planar shaped-beam antenna; side view	6
4. Figure 2(a) Measured, computed and target patterns of the shaped-beam antenna ($\epsilon_r=2.59$, $a=5\text{mm}$, $b=15\text{mm}$, $t_m=0.05\text{mm}$, $t_d=1.86\text{mm}$, $d_1=12.52\text{mm}$, $d_2=3.0\text{ mm}$, 16 metal strips); 10.9GHz.	13
5. Figure 2(b) Measured, computed and target patterns of the shaped-beam antenna ($\epsilon_r=2.59$, $a=5\text{mm}$, $b=15\text{mm}$, $t_m=0.05\text{mm}$, $t_d=1.86\text{mm}$, $d_1=12.52\text{mm}$, $d_2=3.0\text{ mm}$, 16 metal strips); 11.35GHz.	14
6. Figure 2(c) Measured, computed and target patterns of the shaped-beam antenna ($\epsilon_r=2.59$, $a=5\text{mm}$, $b=15\text{mm}$, $t_m=0.05\text{mm}$, $t_d=1.86\text{mm}$, $d_1=12.52\text{mm}$, $d_2=3.0\text{ mm}$, 16 metal strips); 11.37GHz.	15
7. Figure 2(d) Measured, computed and target patterns of the shaped-beam antenna ($\epsilon_r=2.59$, $a=5\text{mm}$, $b=15\text{mm}$, $t_m=0.05\text{mm}$, $t_d=1.86\text{mm}$, $d_1=12.52\text{mm}$, $d_2=3.0\text{ mm}$, 16 metal strips); 11.41GHz.	16
8. Figure 2(e) Measured, computed and target patterns of the shaped-beam antenna ($\epsilon_r=2.59$, $a=5\text{mm}$, $b=15\text{mm}$, $t_m=0.05\text{mm}$, $t_d=1.86\text{mm}$, $d_1=12.52\text{mm}$, $d_2=3.0\text{ mm}$, 16 metal strips); 11.43GHz.	17
9. Figure 2(f) Measured, computed and target patterns of the shaped-beam antenna ($\epsilon_r=2.59$, $a=5\text{mm}$, $b=15\text{mm}$, $t_m=0.05\text{mm}$, $t_d=1.86\text{mm}$, $d_1=12.52\text{mm}$, $d_2=3.0\text{ mm}$, 16 metal strips); 11.45GHz.	18
10. Figure 2(g) Measured, computed and target patterns of the shaped-beam antenna ($\epsilon_r=2.59$, $a=5\text{mm}$, $b=15\text{mm}$, $t_m=0.05\text{mm}$, $t_d=1.86\text{mm}$, $d_1=12.52\text{mm}$, $d_2=3.0\text{ mm}$, 16 metal strips); 11.47GHz.	19
11. Figure 2(h) Measured, computed and target patterns of the shaped-beam antenna ($\epsilon_r=2.59$, $a=5\text{mm}$, $b=15\text{mm}$, $t_m=0.05\text{mm}$, $t_d=1.86\text{mm}$, $d_1=12.52\text{mm}$, $d_2=3.0\text{ mm}$, 16 metal strips); 11.51GHz.	20
12. Figure 2(i) Measured, computed and target patterns of the shaped-beam antenna ($\epsilon_r=2.59$, $a=5\text{mm}$, $b=15\text{mm}$, $t_m=0.05\text{mm}$, $t_d=1.86\text{mm}$, $d_1=12.52\text{mm}$, $d_2=3.0\text{ mm}$, 16 metal strips); 11.53GHz.	21
13. Figure 2(j) Measured, computed and target patterns of the shaped-beam antenna ($\epsilon_r=2.59$, $a=5\text{mm}$, $b=15\text{mm}$, $t_m=0.05\text{mm}$, $t_d=1.86\text{mm}$, $d_1=12.52\text{mm}$, $d_2=3.0\text{ mm}$, 16 metal strips); 11.57GHz.	22

14. Figure 2(k) Measured, computed and target patterns of the shaped-beam antenna ($\epsilon_r=2.59$, $a=5\text{mm}$, $b=15\text{mm}$, $t_m=0.05\text{mm}$, $t_d=1.86\text{mm}$, $d_1=12.52\text{mm}$, $d_2=3.0\text{ mm}$, 16 metal strips); 11.90GHz.	23
15. Figure 3(a) Measurement setup in chamber	25
16. Figure 3(b) The probe is at the position $(x, y, z) = (0, 0, 52)$	25
17. Figure 3(c) The probe is at the position $(x, y, z) = (0, 90, 52)$	26
18. Figure 3(d) The probe	26
19. Figure 4 Measured reflection coefficient for the probe	27
20. Figure 5(a) Measured contour map of the y-direction electric field strength on a rectangular plane; 10.9GHz	27
21. Figure 5(b) Measured contour map of the y-direction electric field strength on a rectangular plane; 11.37GHz	28
22. Figure 5(c) Measured contour map of the y-direction electric field strength on a rectangular plane; 11.43GHz	28
23. Figure 5(d) Measured contour map of the y-direction electric field strength on a rectangular plane; 11.45GHz	29
24. Figure 5(e) Measured contour map of the y-direction electric field strength on a rectangular plane; 11.47GHz	29
25. Figure 5(f) Measured contour map of the y-direction electric field strength on a rectangular plane; 11.53GHz	30
26. Figure 5(g) Measured contour map of the y-direction electric field strength on a rectangular plane; 11.90GHz	30
27. Figure 6 Measured and calculated reflection coefficient for the shaped-beam antenna	31
28. Figure 7 Radiation pattern for different dielectric layer thicknesses at 11.43GHz ($\epsilon_r=2.59$, $a=5\text{mm}$, $b=15\text{mm}$, $t_m=0.05\text{mm}$, $d_1=12.52\text{mm}$, $d_2=3.0\text{mm}$)	34
29. Figure 8 Radiation pattern for different dielectric constants at 11.43GHz ($a=5\text{mm}$, $b=15\text{mm}$, $t_m=0.05\text{mm}$, $t_d=1.86\text{mm}$, $d_1=12.52\text{mm}$, $d_2=3\text{mm}$)	36
30. Figure 9 Radiation pattern for different number of metal-strip array at 11.43GHz ($\epsilon_r=2.59$, $a=5\text{mm}$, $b=15\text{mm}$, $t_m=0.05\text{mm}$, $t_d=1.86\text{mm}$, $d_1=12.52\text{mm}$, $d_2=3\text{mm}$)	37
31. Figure 10 Radiation pattern for different distances from the line source to metal ground plane ($\epsilon_r=2.59$, $a=5\text{mm}$, $b=15\text{mm}$, $t_m=0.05\text{mm}$, $t_d=1.86\text{mm}$, $d_1=12.52\text{mm}$, 11.43GHz)	38
32. Figure 11 Radiation pattern for various frequencies ($\epsilon_r=2.59$, $a=5\text{mm}$, $b=15\text{mm}$, $t_m=0.05\text{mm}$, $t_d=1.86\text{mm}$, $d_1=12.52\text{mm}$, $d_2=3\text{mm}$)	40

33. Figure 12(a) Radiation pattern for 2.4GHz; (a) 4 metal strips.....	42
34. Figure 12(b) Radiation pattern for 2.4GHz; (b) 6 metal strips	42
35. Figure 13(a) Radiation pattern for 5.2GHz; (a) 8 metal strips.....	43
36. Figure 13(b) Radiation pattern for 5.2GHz; (b) 12 metal strips	43
37. Figure 14 The structure configuration and parameters assignment of the shaped-beam antenna	45
38. Figure 15 Radiation pattern for different dielectric constant at 5.4GHz	53
39. Figure 16 Electric field magnitude on the antenna aperture for different relative dielectric constant of dielectric rods at 5.4GHz.....	54
40. Figure 17 Radiation pattern for different aspect ratio at 5.4GHz	56
41. Figure 18 Electric field magnitude on the antenna aperture for different aspect ratio at 5.4GHz.....	57
42. Figure 19 Radiation pattern for different dielectric grating layer thickness at 5.4GHz ($a=0.5, b=1.0, d_a=5, d_1=1.05, d_2=0.68$)	58
43. Figure 20 Electric field magnitude on the antenna aperture for different dielectric grating layer thickness at 5.4GHz	59
44. Figure 21 Radiation pattern for different distances from line source to metal ground plane at 5.4GHz	61
45. Figure 22 Radiation pattern for different operation frequency	63
46. Figure 23 Multiplayer planar structure and its equivalent network Representation.....	71
47. Figure 24(a) Transverse field distribution of first six modes with effective dielectric constant; (a) 2.584.....	71
48. Figure 24(b) Transverse field distribution of first six modes with effective dielectric constant; (b) 2.335.....	71
49. Figure 24(c) Transverse field distribution of first six modes with effective dielectric constant; (c) 1.927.....	72
50. Figure 24(d) Transverse field distribution of first six modes with effective dielectric constant; (d) 1.384.....	72
51. Figure 24(e) Transverse field distribution of first six modes with effective dielectric constant; (e) 0.846.....	71
52. Figure 24(f) Transverse field distribution of first six modes with effective dielectric constant; (f) 0.669.	71