

Acknowledgement

- This research is funded by MOEA (Ministry of Economic Affairs, ROC) and supported by ITRI (Industrial Technology Research Institute) / ERSO (Electronics Research & Service Organization)
- UV curable adhesive is provided by Henkel, Taiwan, Ltd. with technical assistance by Joseph Han



Reference

- [1] Tai-Ran Hsu, "Packaging Design of Microsystems and Meso-Scale Devices", IEEE Transactions on Advantaged Packaging, VOL. 23, NO. 4, Nov 2000
- [2] Anders Hanneborg, "Silicon Wafer Bonding Techniques for Assembly of Micromechanical Elements", IEEE MEMS, Nara Japan, 1991 (Tech. Digest)
- [3] C.Lin, R.Ghodssi, A.A. Ayon, D.Chen, S.Jacobson, K.Breuer, AH Epstein and MA Schmidt, "Fabrication and Characterization of a Micro Turbine/Bearing Rig," IEEE International MEMS'99, pp. 529-531
- [4] Gregory T.A. Kovacc, Micromachined Transducers Sourcebook, Mc Graw-Hill, 1998
- [5] A.C.Gracias, A.N.Rios, I.A.Maia, J.R.Senna, "Experiments on Silicon-to-Silicon Direct Bonding", 13th Meeting of the Brazilian Vacuum Society, Campinas, Brazil, July, 1998
- [6] P.W. Barth, "Silicon Fusion Bonding for Fabrication of Sensors, Actuators, and Microstructures", *Sensors and Actuators*, A21-23, 1990, pp. 919-926.
- [7] G. Wallis, D.I. Pomerantz, J. Appl. Phys. 40 (1969) 3946.
- [8] R.F. Wolffenbuttel, K.D. Wise, "Low-Temperature Silicon Wafer-to-Wafer Bonding using Gold at Eutectic Temperature", *Sensors and Actuators A*, 43 (1994)
- [9] Martin A. Schmidt, "Wafer-to-Wafer Bonding for Microstructure Formation", *Proceedings of the IEEE*, Vol. 86, No.8, August 1998
- [10] LOCTITE®Product 3492 datasheet, May, 1999
- [11] Yu-Ting Cheng, Liwei Lin, and Khalil Najafi, *Fellow, IEEE*, "A Hermetic Glass-Silicon Package Formed Using Localized Aluminum/Silicon-Glass Bonding", *JOURNAL OF MICROELECTROMECHANICAL SYSTEMS*, VOL. 10, NO. 3, SEPTEMBER 2001

- [12] Thierry Cormany, Peter Enoksson and Goran Stemme, “Deep wet etching of borosilicate glass using an anodically bonded silicon substrate as mask”, J. Micromech. Microeng. 8 (1998) 84–87.
- [13] Shuichi Shoji, Hiroto Kikuchi and Hirotaka Torigoe, “Anodic Bonding Below 180°C for Packaging and Assembling of MEMS Using Lithium Alminosilicate- β -Quartz Glass-Ceramic”, IEEE, 1997
- [14] D.C. Bien, P.V. Rainey, S.J.N. Mitchell and H.S. Gamble, “Characterization of Masking Materials for Deep Glass Micromachining”, Journal of Micromechanics and Microengineering, 2003, 34-40
- [15] Yu-T. Cheng, Wan-Tai Hsu, Member, IEEE, Khalil Najafi, Fellow, IEEE, Clark T.-C. Nguyen, Student Member, IEEE and Liwei Lin, “Vacuum Packaging Technology Using Localized Aluminum/Silicon-to-Glass Bonding”, Journal of Microelectromechanical Systems, VOL 11, NO.5, October 2002

