## **Figure Captions**

| Chapter 1 | 1 |
|-----------|---|
|-----------|---|

| Fig.1.1 Fuel cell stack application on several electronic productions            |
|--|
| Fig.1.2 The schematic images of fuel cell stack                                  |
| Fig.1.3 Atomic structure of carbon: (a) fullerence (b) nanotubes (c) graphite,   |
| (d)diamond7  |
| Fig.1.4 Carbon nanotubes (a) SEM image of as-grown MWNTs (b) TEM image of an     |
| individual MWNT8   |
| Fig.1.5 The SEMmicrographs of platinum nanoparticles on GCNFs/graphite electrode |
| and graphite electrode. (a) GCNFs/graphite electrode (low magnification)         |
| (b) GCNFs/graphite electrode (high magnification)9                               |
| Fig.1.6 (a) Carbon nanocoils grown among the carbon microcoils under an applied  |
| magnetic field in the reaction zone. Catalyst: Ni fine powder                    |
| (b) Carbon nanocoils. Catalyst: Au sputtered films                               |
| Fig.1.7 SEM images of the carbon nanoflake films deposited at the substrate      |
| temperature of (a)400,(b) 500,(c) 600 (d) and 700 °C11                           |
| Chapter 2.   |
| Fig.2.1 The schematic of a unit cell of conventional PEMFC14                     |
| Fig.2.2 MEA structure  |
| Fig.2.3 The chemical formula and physical structure of the membrane Nafion15     |
| Fig.2.4 Schematic diagram of vapor-solid (VS) growth model23                     |
| Fig.2.5 Schematic diagram of VLS growth mechanism for nanotubes23                |
| Fig 2.6 Schematic of SLS growth mechanism 23                                     |

## Chapter 3.

| Fig.3.1 Flow chart of experimental procedures   | 26  |
|---|-----|
| Fig.3.2 Schematic diagram of the bias assisted microwave plasma chemical vapor        |     |
| deposition system   | .27 |
| Fig.3.3 Experimental detail of chemical solution reaction of Pt/ Ru particle          | .29 |
| Fig 3.4 Schematic diagram of a Scanning Electron Microscopy                           | .30 |
| Fig.3.5 Raman shift of (a) diamond, (b) diamond film, (c) amorphous carbon,           | (d) |
| graphite  | .32 |
| Fig.3.6 Schematic diagram of micro-Raman equipment                                    | .32 |
| Fig.3.7 Schematic diagram of BET equipment and analysis data                          | .33 |
| Fig.3.8 Schematic diagram of four-point-probe working mechanism                       | .33 |
| Fig.3.9 The basic shape of the current response for a cyclic voltammetry experimen    | ıt. |
| Chapter 4.  Fig.4.1 SEM images of changes negative bias voltage for synthesizing carb |     |
| nanotubes on silicon  |     |
| Fig.4.2 HRTEM images of an individual CNT   | .40 |
| Fig.4.3 Raman spectrum of CNT   | .40 |
| Fig.4.4 SEM images of changes from -100V to +100V in the symmetric period ti          | me  |
| for synthesizing carbon flakes on silicon   | .42 |
| Fig 4.5 HRTEM of individual petal of CNF  | .43 |
| Fig.4.6 Raman spectrum of carbon nanoflake under (-100, +100) V for 10mins            | .43 |
| Fig.4.7 SEM images of fixed -100V for10mins and switch to +100V in the differ         | ent |
| period time for synthesizing carbon flakes on silicon                                 | .46 |
| Fig.4.8. Enlarged SEM image of Fig 4.7  | .46 |

| Fig.4.9 Raman spectrum and components ratio of fixed -100V for 10mins, changed    |
|---|
| +100V for 5~20mins  |
| Fig.4.10 SEM images of fixed -100V for10mins and changed positive bias voltage    |
| from +50V~+200V, each for 10mins for synthesizing CNFs on silicon48               |
| Fig.4.11 Enlarged SEM images of Fig.4.1048  |
| Fig.4.12 Raman spectrum and components ratio of fixed -100V for 10mins, changed   |
| +50~200V,each for 10mis   |
| Fig.4.13 SEM images of changed +50~200V, each for 10mins in front of fixed -100V  |
| for 10 mins: (a) +50V (b) +100V (c) +150V (d) +200V51                             |
| Fig.4.14 SEM images of compared two orders of positive bias applying:             |
| (a)+100V,-100V (b)-100V,+100, each for 10 mins51                                  |
| Fig.4.15 SEM images of improvement of CNT to CNF:(a)-(b) two types of CNT,        |
| (c)-(d) CNF grown on CNT separately of (a)-(b), (e)-(f) enlarged image of         |
| (c)-(d)   |
| Fig.4.16 SEM images of CNFs' collection   |
| Fig.4.17 HRTEM of CNF grown on CNT: (a) CNT stem with petals                      |
| (b)stem has branch shows graphitic layers54                                       |
| Fig.4.18 Growth model suspension of CNF55   |
| Fig.4.19 SEM images of plain carbon cloth textured by carbon fiber with different |
| magnitude57   |
| Fig.4.20 SEM images of plain carbon cloth deposited of CNFs and CNTs:             |
| (a) CNFs (b) CNTs (c)-(d) enlarged image of (a)-(b) separately58                  |
| Fig.4.21 TEM images of Pt on CNF and CNT by sputtering60                          |
| Fig.4.22. TEM images of Pt on CNF by sputtering and poyol: (a) sputtering         |
| (b)poyol61  |

| Fig.4.23 HRTEM images of deposited Pt particle:(a) Pt on CNF (b) diffraction                                |
|---|
| pattern of Pt62   |
| Fig.4.24 EDX of Pt on CNF62   |
| Fig.4.25 Electroanalytical measurement setup63  |
| Fig.4.26 The CVs of carbon cloth, Pt/carbon nanoflakes/carbon cloth, and Pt /carbon nanotubes/carbon cloth. |
| Fig.4.27 CVs of Pt/carbon nanotubes/carbon cloth by different concentatrtion of Pt/Ru                       |
| solution65  |
| Fig.4.28 CVs of Pt/carbon nanoflakes/carbon cloth by different concentatrtion of                            |
| Pt/Ru solution65  |
| Fig.4.29 CVs of Pt/carbon nanotubes/carbon cloth by different time of sputtering66                          |
| Fig.4.30 CVs of Pt/carbon nanotubes/carbon cloth by different applied current of sputtering                 |
| 1896  |