

## 參考文獻

1. 林正章、劉志遠，「路線貨運業貨物整體運輸網路設計之研究」，**運輸計劃季刊**，第二十八卷第四期，民國 88 年 12 月，頁 535-564。
2. 王小娥、許凱翔，「汽車貨物運輸業成本結構與相關彈性之分析」，**運輸計劃季刊**，第三十卷第三期，民國 90 年 9 月，頁 603-634。
3. 陳高村、許志誠，「道路交通事故損害賠償成本推估之研究」，**運輸計劃季刊**，第三十二卷第二期，民國 92 年 6 月，頁 365-390。
4. 馮正民、黃新薰，「城際複合物流運輸鐵路轉運中心最適區為模式」(**運輸計劃季刊已接受**，預定刊登第三十四卷第四期)。
5. 倪佩貞、白仁德、朱佩芸、劉國棟，都會區機動車輛之空氣污染排放與燃油效率係數之推估及污染排放總量之計算，交通部運輸研究所交通事故與交通違規之社會成本推估研討會，民國 89 年。
6. 蕭代基、錢玉蘭，交通運輸與交通事故管理策略減輕空氣污染之健康效益評估，交通部運輸研究所交通事故與交通違規之社會成本推估研討會，民國 89 年。
7. 中華民國運輸學會，交通部台灣鐵路管理局貨運服務總所營運改善策略，民國 90 年。
8. 詹鴻漳，台鐵發展快遞業務可行性之研究，交通大學交通運輸研究所碩士論文，民國 90 年。
9. 交通部運輸研究所，運輸部門節約能源及減少溫室氣體排放之規劃研究，民國 90 年。
10. 林正章，「貨物運輸網路研究之回顧與展望」，**運輸網路分析**，五南圖書公司，民國 90 年。
11. 交通部運輸研究所，第三期台灣地區整體運輸規劃，民國 88 年 11 月。
12. 交通部運輸研究所，「公路行駛時間調查(90年)」，民國 91 年 2 月。
13. 交通部，交通政策白皮書，民國 91 年。
14. 交通部運輸研究所，國家貨運發展政策白皮書，民國 93 年。
15. 張清溪、許嘉棟、劉鶯釗、吳聰敏，經濟學，雙葉書廊有限公司，民國 84 年。
16. 許志義，多目標決策，五南圖書公司，民國 84 年。
17. 經濟部商業司，物流經營管理實務，民國 85 年。
18. Aikens, C. H. (1985), "Facility location models for distribution planning," **European Journal of Operational Research** **22**, 263-279.
19. Aykin, T. (1990), "A quadratic integer program for the location of interacting hub facilities," **European Journal of Operational Research** **46**, 409-411.
20. Aykin, T. (1995), "Networking policies for hub-and-spoke systems with

- application to the air transportation system,” **Transportation Science**, Vol. **29**, No. **3**, 201-221.
21. Barcelo, J. and Casanovas, J. (1984), “A heuristic Lagrangian algorithm for the capacitated plant location problem,” **European Journal of Operational Research** **15**, 212-226.
  22. Brandeau, M. L. and Chiu, S. S. (1989), “An overview of representative problems in location research”, **Management Science** **35**, 645-674.
  23. Beasley, J. E. (1993), “Lagrangian heuristic for location problems,” **European Journal of Operational Research** **65**, 383-399.
  24. Boyer, D. Kenneth (1998), Principles of Transportation Economics, USA.
  25. Bickel, P., Schmid, S., Krewitt, W. and Friedrich, R. (1998), “Transport externalities due to airborne pollutants in Germany-application of the extern approach,” **TERA 98**, October Milan, Italy.
  26. Beuthe, M., degrandsart, F., Geerts, J-F. and Jourquin, B. (2002), “External costs of the Belgian interurban freight traffic: a network analysis of their internalisation,” **Transportation Research Part D**, Vol. **7**, 285-301.
  27. Carson, R. (1962), Silent Spring, Houghton Mifflin Company.
  28. Cline, W. R. (1992), The Economics of Global Warming, Institute for International Economics, Washington.
  29. Campbell, J. F. (1994a), “A survey of network hub location,” **Studies in Locational Analysis** **6**, 31-49.
  30. Campbell, J. F. (1994b), “Integer programming formulations of discrete hub location problems,” **European Journal of Operational Research** **72**, 387-405.
  31. Commission of the European Communities (1995), Green Paper Towards Fair and Efficient Pricing in Transport, COM (95), 691 final Brussels.
  32. Elson, D. G. (1972), “Site location via mixed-integer programming,” **Operational Research Quarterly** **23**, 31-43.
  33. EEA(1996), User’s Manual for Mobile-Taiwan Version2, CTCI Corporation.
  34. EPA(1996), State of the Environment in Ireland. Dublin: EPA.
  35. ExternE Project (1997), ExternE Costs of Transport in ExternE, Final Report, European Commission DG12, Non Nuclear Energy Programme Joule 3.
  36. Frankhauser, S. (1995), Valuing Climate Change. The Economics of the Greenhouse, Earthscan, London.
  37. Fokenbrock, D. J. (1999), ”External costs of intercity truck freight transportation,” **Transportation Research Part A**, Vol. **33**, 505-526.

38. Fokenbrock, D. J. (2001), "Comparison of external costs of rail and freight transportation," **Transportation Research Part A**, Vol. 35, 321-337.
39. Favrel, V. and Hecq, W. (2001), "External costs of air pollution generated by road traffic in the Brussels urban area," **International Journal of Vehicle Design**, Vol.27, Nos. 1-4, 129-139.
40. Feng, C. M. and Huang, H. H. (2003), "Modelling the intermodal logistics between intercity rail and city truck," **Journal of the Eastern Asia Society for Transportation Studies**, Vol. 5, 2313-2326.
41. Geoffrion, A. M. and Graves, G. W. (1974), "Multicommodity distribution system design by Benders decomposition," **Management Science**, Vol. 20, No. 5, 822-844.
42. Grünert, T. and Sebastian, H-J. (2000), "Planning models for long-haul operations of postal and express shipment companies," **European Journal of Operational Research** 122, 289-309.
43. Gibbons, E. and O'Mahony, M. (2002), "External cost internalization of urban transport: a case study of Dublin," **Journal of Environmental Management** 64, 401-410.
44. Hall, R. W. (1989), "Configuration of an overnight package air network," **Transportation Research A** 23, 139-149.
45. Holmberg, K., Rönnqvist, M. and Yuan D. (1999), "An exact algorithm for the capacitated facility location problems with single sourcing", **European Journal of Operational Research** 113, 544-559.
46. Hinojosa, Y., Puerto, J. and Fernández, F. R. (2000), "A multiperiod two-echelon multicommodity capacitated plant location problem," **European Journal of Operational Research** 123, 271-291.
47. IPCC/OECD (1996), Revised 1996 IPCC Guidelines for Greenhouse Gas Inventories, IPCC WGI Technical Support Unit.
48. Jones-Lee, M. W. (1990), "The value of transport safety," **Oxford Review of Economics and Policy** 6, 31-43.
49. Jansson, J. O. (1994), "Accident externality charges," **Journal of Transport Economics and Policy**, 31-43.
50. Jaillet, P., Song, G. and Yu, G. (1996), "Airline network design and hub location problems," **Location Science**, Vol. 4, No. 3, 195-212.
51. Klincewicz, J. G. and Luss, H. (1986), "A Lagrangian relaxation heuristic for capacitated facility location with single-source constraints," **Journal of the Operational Research Society** 37, 495-500.
52. Klincewicz, J. G. (1991), "Heuristics for the p-hub location problem," **European Journal of Operational Research** 53, 25-37.

53. Kuby, M. and Gray, R. G. (1993), "The hub network design problem with stopovers and feeders: The case of Federal Express," **Transportation Research A**, Vol. 27A, No. 1, 1-12.
54. Kim, D., Barnhart, C., Ware, K. and Reinhard, T. G. (1999), "Multimodal express package delivery: A service network design application," **Transportation Science**, Vol. 33, No. 4, 391-407.
55. Klose, A. (2000), "A Lagrangian relax-and-cut approach for the two-stage capacitated facility location problem," **European Journal of Operational Research** 126, 408-421.
56. Klose, A. and Drexl A. (2005), "Facility location models for distribution system design," **European Journal of Operational Research** 162, 4-29.
57. Lin, C. C. (2001), "The freight routing problem of time-definite freight delivery common carrier", **Transportation Research Part B**, Vol. 35, No. 6, 525-547.
58. Lindberg, G. (2001), "Traffic insurance and accident externality charges," **Journal of Transport Economics and Policy**, Vol. 35, Part 3, 399-416.
59. Marglin, S. (1967), *Investment Criteria*, MIT Press, Cambridge, Massachusetts.
60. Major, D. C. (1969), "Benefit-cost ratios for projects in multiple objective investment program," **Water Resource Research**, Vol. 5, No. 6, 1174-1178.
61. Mishan, E. (1971), "Evaluation of life and limb: a theoretical approach," **Journal of Political Economy**," Vol. 74.
62. Miller, T., Viner, J., Rossman, S., Pindus, N., Gellert, W., Douglass, J., Dillingham, A. and Blomquist, G. (1991), *The Cost of Highway Crashes*, Urban Institute, FHWA.
63. Mayeres, I., Ochelen, S. and Proost, S. (1996), "The marginal external cost of transport," **Transportation Research Part D**, Vol. 1, No. 2, 111-130.
64. Mazzola, J. B. and Neebe, A. W. (1999), "Lagrangian-relaxation-based solution for a multiproduct capacitated facility location problem with choice of facility type," **European Journal of Operational Research** 115, 285-299.
65. Newbery, T. (1988), "Road user charges in Britain," **Economy Journal**, 98, 161-176.
66. National Research Council (1991), *Rethinking the Ozone Problem in Urban and Regional Air Pollution*, Washington, National Academy Express.
67. Nilsson, S. (1991), "European Forest Decline: The Effects of Air Pollution and Suggested Remedial Policy," IIASA, Laxenburg.

68. O'Kelly, M. E. (1986), "Activity levels at hub facilities in interacting networks," **Geographical Analysis** **18**, 343-356.
69. O'Kelly, M. E. (1987), "A quadratic integer program for the location of interacting hub facilities," **European Journal of Operational Research** **32**, 393-404.
70. O'Kelly, M. E. and Lao, Y. (1991), "Mode choice in a hub-and-spoke network: A zero-one linear programming approach," **Geographical Analysis** **23**, 283-297.
71. O'Kelly, M. E. (1992), "Hub facility location with fixed costs," Papers in Regional Science: **The Journal of the RSAI** **71**, 293-306.
72. O'Kelly, M. E. and Miller, H. J. (1994), "The hub network design problem: a review and synthesis," **Journal of Transport Geography** **2**, 31-40.
73. O'Kelly, M. E., Bryan, D., Skorin-kapov, D., Skorin-kapov, J. (1996), "Hub network design with single and multiple allocation: a computational study," **Location Science**, Vol. 4, No. 3, 125-138.
74. Pirkul, H. (1987), "Efficient algorithm for the capacitated concentrator location problem," **Computers and Operations Research** **14**, 197-208.
75. Persson, U. and Ödegaard, K. (1995), "External cost estimates of road traffic accidents-an international comparison," **Journal of Transport Economics and Policy**, 291-304.
76. Pirkul, H. and Jayaraman V. (1996), "Production, transportation, and distribution planning in a multi-commodity tri-echelon system", **Transportation Science** Vol. 30, No. 4, 291-302.
77. Pirkul, H. and Jayaraman V. (1998), "A multi-commodity, multi-plant, capacitated facility location problem: Formulation and efficient heuristic solution," **Computers and Operations Research** Vol. 25, No. 10, 869-878.
78. Quinet, E. (1993), "The social costs of transport: evaluation and links with international policies," Joint OECD/ECMT Seminar on Internalising the Social Costs of Transport, 30 September-1 October. Paris: Organisation for Co-operation and Development.
79. Rutten, B. C. M (1998) The design of a terminal network for intermodal transport, **Transport Logistics**, Vol. 1, No. 4, 279-298.
80. Rönnqvist, M., Tragantalerngsak, S. and Holt, J. (1999), "A repeated matching heuristic for the single-source capacitated facility location problem," **European Journal of Operational Research** **166**, 51-68.
81. Sridharan, R. (1993), "Lagrangian heuristic for the capacitated plant location problem with single-source constraints," **European Journal of Operational Research** **66**, 305-312.



82. Sridharan, R. (1995), "The capacitated plant location problem," **European Journal of Operational Research** **87**, 203-213.
83. Small, K. A. and Kazimi, C., (1995), "On the costs of air pollution from motor vehicles," **Journal of Transport Economics and Policy**, **29(1)**, 7-32.
84. TRB (1996), *Paying Our Way: Estimating Marginal Social Costs of Freight Transportation*, Special Report 246.
85. Taniguchi, E., Noritake, M., Yamada, T. and Izumitani, T. (1999), "Optimal size and location planning of public logistics terminals," **Transportation Research Part E** **35**, 207-222.
86. Tragantalerngsak, S., Holt, J. and Rönnqvist, M. (2000), "An exact method for the two-echelon, single-source, capacitated facility location problem," **European Journal of Operational Research** **123**, 473-489.
87. US Environmental Protection Agency (EPA) (1982), "Air quality criteria for particulate matter and sulfur," Oxides, vol. 3, Research. Triangle Park, North Carolina: EPA.
88. Vickery, W. (1968), "Automobile accident, tort law, externalities, and insurance," **Law and Contemporary Problem**, Summer.
89. Varian, H. R. (1984), *Microeconomics Analysis*, 2<sup>nd</sup> ed., W. W. Norton, New York.
90. Woodburn, A. G. (2001), "The changing nature of rail freight in Great Britain: the start of a renaissance ?" **Transport Reviews**, **Vol. 21, No. 1**, 1-13.
91. Zadeh, L. A. (1963), "Optimality and nonscalar-valued performance criteria," **IEEE Transactions on Automatic Control**, **Vol. AC-8, No. 1**, 59-60.