

References

- [01] J. F. Scott, “Ferroelectric Memories”, Springer Series, 2000.
- [02] Y. M. Chang, “Physical ceramics”, John Wiley & Sons, 1997.
- [03] H. S. Nalwa, “Handbook of Thin Film Materials, Vol. 3, Ferroelectric and Dielectric Thin Films”, Academic Press, 2002.
- [04] K. Uchino, “Ferroelectric Devices”, Marcel Dekker, 2000.
- [05] C. Kittel, “Introduction to solid state physics”, 7th edition, John Wiley & Sons, 1996.
- [06] D. Bolten, U. Bottger, A. Li, and R. Waser, “ Reversible and irreversible polarization processes in ferroelectric ceramics and thin films” *J. Appl. Phys.* **93**, 1735, 2003.
- [07] A. Sheikholeslami and P. G. Gilak, “A Survey of Circuit Innovations in Ferroelectric Random-Access Memories”, *Proc. IEEE*, **88**, 667, 2000.
- [08] D. Takashima, “Overview and trend of chain FeRAM architecture”, *IEICE Trans. On Electron.*, **E84-C**, 747, 2001.
- [09] D. Takashima and I. Kunishima, “High-density chain ferroelectric random access memory (Chain FRAM)”, *IEEE Journal of Solid State Circuits*, **33**, 787, 1998.
- [10] D. Takashima, S Shuto, I. Kunishima , H. Takenaka, Y. Oowaki, and S. Tanaka, “A sub-40-ns chain FRAM architecture with 7-ns cell-plate-line Drive”, *IEEE Journal of Solid State Circuits*, **34**, 1557,1999.
- [11] S. Y. Wu, “A new ferroelectric memory device, metal ferroelctric semiconductor transistor”, *IEEE Trans. Electron Devices*, **ED-21**. 449 (1974).
- [12] K. Sakamaki, T. Hirai, T. Uesugi, H. Kishi, and Y. Tarui, “Characteristics of a Metal/Ferroelectric/Insulator/Semiconductor Structure Using an Ultrathin Nitrided Oxide Film as the Buffer Layer”, *Jpn. J. Appl. Phys.*, **38**, L451,1999.
- [13] D. S. Shin, H. N. Lee, Y. T. Kim, I. H. Choi, and B. H. Kim, “Electrical Properties of Pt/SrBi₂Ta₂O₉/CeO₂/SiO₂/Si Structure for Nondestructive Readout Memory”, *Jpn. J. Appl. Phys.*, **37**, 4373,1998.
- [14] H. S. Choi, Y. T. Kim, S. I. Kim, and I. H. Choi, “Electrical Characteristics of Pt/SrBi₂Ta₂O₉/Ta₂O₅/Si Using Ta₂O₅ as the Buffer Layer”, *Jpn. J. Appl. Phys.*, **40**, 2940, 2001.
- [15] J.-D. Park, J.-H. Choi, and T.-S. Oh, “Electrical Characteristics of the

- Pt/SrBi_{2.4}Ta₂O₉/ZrO₂/Si Structure for Metal-Ferroelectric-Insulator-Semiconductor Field-Effect-Transistor Application”, Jpn. J. Appl. Phys., **41**, 5645, 2002.
- [16] B.-E. Park, and H. Ishiwara, “Electrical properties of LaAlO₃/Si and Sr_{0.8}Bi_{2.2}Ta₂O₉/LaAlO₃/Si structures”, Appl. Phys. Lett., **79**, 806, 2001.
- [17] W.-J. Lee, C.-H. Shin, C.-R. Cho, J.-S. Lyu, B.-W. Kim, B.-G. Yu, and K.-I. Cho, “Electrical Properties of SrBi₂Ta₂O₉/Insulator/Si Structures with Various Insulators”, Jpn. J. Appl. Phys., **38**, 2039, 1999.
- [18] C.-H. Chien, D.-Y. Wang, M.-J. Yang, P. Lehn, C.-C. Leu, S.-H. Chuang, T.-Y. Huang, and C.-Y. Chang, “High-performance Pt/SrBi₂Ta₂O₉/HfO₂/Si structure for nondestructive readout memory”, IEEE Electron Device Lett., **24**, 553, 2003.
- [19] M. Noda, K. Kodama, S. Kitai, M. Takahashi, T. Kanashima, and M. Okuyama, “Basic characteristics of metal-ferroelectric-insulator-semiconductor structure using a high- k PrO_x insulator layer”, J. Appl. Phys., **93**, 4137, 2003.
- [20] M. Takahashi, H. Sugiyama, T. Nakaiso, K. Kodama, M. Noda, and M. Okuyama, “Analysis and Improvement of Retention Time of Memorized State of Metal-Ferroelectric-Insulator-Semiconductor Structure for Ferroelectric Gate FET Memory”, Jpn. J. Appl. Phys., **40**, 2923, 2001.
- [21] K. Kodama, M. Takahashi, D. Ricinschi, A. I. Lerescu, M. Noda, and M. Okuyama, “Improved Retention Characteristics of Metal-Ferroelectric-Insulator-Semiconductor Structure Using a Post-Oxygen-Annealing Treatment”, Jpn. J. Appl. Phys., **41**, 2639, 2002.
- [22] M. Noda, K. Kodama, I. Ikeuchi, M. Takahashi, and M. Okuyama, “A Significant Improvement in Memory Retention of Metal-Ferroelectric-Insulator-Semiconductor Structure for One Transistor-Type Ferroelectric Memory by Rapid Thermal Annealing”, Jpn. J. Appl. Phys., **42**, 2055, 2003.
- [23] D. Ito, N. Fujimura, T. Yoshimura, and T. Ito, “Influence of Schottky and Poole-Frenkel emission on the retention property of YMnO₃-based metal/ferroelectric/insulator/semiconductor capacitors”, J. Appl. Phys., **94**, 4036, 2003.
- [24] C.B. Sawyer and C. H. Tower, “Rochelle Salt as a Dielectric”, Phys. Rev., **35**, 269, 1930.
- [25] A. M Glazer, P. Groves, and D. T. Smith, “Automatic sampling circuit for ferroelectric hysteresis loops”, J. Phys., E **17**, 95, 1984.
- [26] L. F. Schloss and P. C. McIntyre, “Polarization recovery of fatigued Pb(Zr,Ti)O₃ thin films: Switching current studies”, J. Appl. Phys. **93**, 1743, 2003.

- [27] J. F. Scott, C. A. Araujo, H. B. Meadows, L. D. McMillan, and A. Shawabkeh, “Radiation effects on ferroelectric thin-film memories: Retention failure mechanisms”, *J. Appl. Phys.* **66**, 1444, 1989.
- [28] J. A. Giacometti, C. Wisniewski, W. A. Moura, and P. A. Ribeiro, “Constant current: A method for obtaining hysteresis loops in ferroelectric materials”, *Rev. Sci. Instrum.* **70**, 2699, 1999.
- [29] J. A. Giacometti, C. Wisniewski, P. A. Ribeiro, and W. A. Moura, “Electric measurements with constant current: A practical method for characterizing dielectric films”, *Rev. Sci. Instrum.* **72**, 4223, 2001.
- [30] Y. Igarashi, K. Tani, M. Kasai, K. Ashikaga, and T. Ito, “Submicron Ferroelectric Capacitors Fabricated by Chemical Mechanical Polishing Process for High-Density Ferroelectric Memories”, *Jpn. J. Appl. Phys.*, **39**, 2083, 2000.
- [31] S. Tiedke, T. Schmitz, K. Prume, A. Roelofs, T. Schneller, U. Kall, R. Waser, C. S. Ganpule, V. Nagarajan, A. Stanishevsky, and R. Ramesh, “Direct hysteresis measurements of single nanosized ferroelectric capacitors contacted with an atomic force microscope”, *Appl. Phys. Lett.*, **79**, 3678, 2001.
- [32] R. Bouregba, B. Vilquin, G. Le Rhun, G. Poullain, and B. Domenges, ”Sawyer–Tower hysteresis measurements on micron sized $\text{Pb}(\text{Zr},\text{Ti})\text{O}_3$ capacitors”, *Rev. Sci. Instrum.*, **74**, 4429, 2003.
- [33] N. Inoue, T. Takeuchi, and Y. Hayashi, “Sputtering process design of PZT capacitors for stable FeRAM operation”, *Int. Electron Device Meet. Tech. Dig.*, 819, 1998.
- [34] S.-H. Kim , J. Ha , C.S. Hwang, and A.I. Kingon, “Ca- and Sr-doped $(\text{Pb}_{1-x}\text{La}_x)(\text{Zr}_y\text{Ti}_{1-y})_{1-x/4}\text{O}_3$ thin films for low-voltage operation”, *Thin Solid Films.*, **394**, 130, 2001.
- [35] M. Aratani, T. Ozeki, and H. Funakubo, “Low Temperature Deposition of $\text{Pb}(\text{Zr},\text{Ti})\text{O}_3$ Film by Source Gas Pulse-Introduced Metalorganic Chemical Vapor Deposition”, *Jpn. J. Appl. Phys.*, **40**, L343, 2001.
- [36] Y. Fujimori, T. Nakamura, and H. Takasu, “Low-Temperature Crystallization of Sol-Gel-Derived $\text{Pb}(\text{Zr}, \text{Ti})\text{O}_3$ Thin Films”, *Jpn. J. Appl. Phys.*, **38**, 5346, 1999.
- [37] L. A. Bursill and K. G. Brooks, “Crystallization of sol-gel derived lead-zirconate-titanate thin films in argon and oxygen atmospheres”, *J. Appl. Phys.*, **75**, 4501, 1994.
- [38] N. Inoue, T. Nakura, and Y. Hayashi, “Low thermal-budget fabrication of sputtered-

- PZT capacitor on multilevel interconnects for embedded FeRAM”, Int. Electron Device Meet. Tech. Dig., 797, 2000.
- [39] N. Soyama, K. Maki, S. Mori, and K. Ogi, “Preparation and Evaluation of Pb(Zr, Ti)O₃ Thin Films for Low Voltage Operation”, Jpn. J. Appl. Phys., **39**, 5434, 2000.
- [40] Y. S. Yang, S. J. Lee, S.H. Kim, B.G. Chae, and M.S. Jang, “Schottky barrier effects in the electronic conduction of sol–gel derived lead zirconate titanate thin film capacitors”, J. Appl. Phys. **84**, 5005, 1998.
- [41] D. Wu, A. Li, and N. Ming, “Structure and electrical properties of Bi_{3.15}Nd_{0.85}Ti₃O₁₂ ferroelectric thin films”, J. Appl. Phys. **95**, 4275, 2004.
- [42] C. S. Ganpule, A. Stanishevsky, Q. Su, S. Aggarwal, J. Melngailis, E. Williams, and R. Ramesh, “Scaling of ferroelectric properties in thin films”, Appl. Phys. Lett., **75**, 409, 1999.
- [43] C. S. Ganpule, A. Stanishevsky, S. Aggarwal, J. Melngailis, E. Williams, R. Ramesh, V. Joshi, and C. P. de Araujo, “Scaling of ferroelectric and piezoelectric properties in Pt/SrBi₂Ta₂O₉/Pt thin films”, Appl. Phys. Lett., **75**, 3874, 1999.
- [44] F. Nüesch, Y. Li, and L. J. Rothberg, “Patterning and switching of nanosize ferroelectric memory cells”, Appl. Phys. Lett., **75**, 1793, 1999.
- [45] S. Bühlmann, B. Dwir, J. Baborowski, and P. Muralt, “Size effect in mesoscopic epitaxial ferroelectric structures: Increase of piezoelectric response with decreasing feature size”, Appl. Phys. Lett., **80**, 3195, 2002.
- [46] I. Chung, D. Jang, J. Heo, J. Lee, M. Yastake, and I. Yi, Jpn. “Application of Scanning Probe Microscope for Novel Characterization of Ferroelectric Capacitor”, J. Appl. Phys., **41**, 6743, 2002.
- [47] A. L. Kholkin, K. G. Brooks, and N. Setter, “Electromechanical properties of SrBi₂Ta₂O₉ thin films”, Appl. Phys. Lett., **71**, 2044, 1997.
- [48] B. Dickens, E. Balizer, A. S. DeReggi, and S. C. Roth, “Hysteresis measurements of remanent polarization and coercive field in polymers”, J. Appl. Phys., **72**, 4258 ,1992.
- [49] T. Yoshimura and N. Fujimura, “Polarization Hysteresis Loops of Ferroelectric Gate Capacitors Measured by Sawyer-Tower Circuit”, Jpn. J. Appl. Phys., **42**, 6011, 2004.
- [50] S.-M. Nam, Y.-B. Kil, S. Wada, and T. Tsurumi, “Domain Switching Kinetics of Lead Zirconate Titinate Thin Films”, Jpn. J. Appl. Phys. **42**, L1519, 2003.
- [51] S. Ikeda, T. Fukada, and Y. Wada, “Effect of space charge on polarization reversal in a

- copolymer of vinylidene fluoride and trifluoroethylene”, J. Appl. Phys. **64**, 2026, 1988.
- [52] T. Yamaguchi, M. Koyama, A. Takashima, and S.-I. Takagi, “Improvement of Memory Characteristics of Metal-Ferroelectrics/Insulating Buffer Layer/Semiconductor Structures by Combination of Pulsed Laser Deposited SrBi₂Ta₂O₉ Films and Ultra-Thin SiN Buffer Layers”, Jpn. J. Appl. Phys., **39**, 2058, 2000.
- [53] K. Aizawa, and H. Ishiwara, “Praseodymium-Substituted Strontium Bismuth Tantalate Films with Saturated Remanent Polarization at 1 V”, Jpn. J. Appl. Phys., **42**, L840, 2003.
- [54] R. Iijima, “Factors controlling the a -axis orientation of strontium bismuth tantalate thin films fabricated by chemical solution deposition”, Appl. Phys. Lett., **79**, 2240, 2001.
- [55] G. D. Hu, I. H. Wilson, J. B. Xu, W. Y. Cheung, S. P. Wong, and H. K. Wong, “Structure control and characterization of SrBi₂Ta₂O₉ thin films by a modified annealing method”, Appl. Phys. Lett., **74**, 1221, 1991.
- [56] D. R. Das, P. Bhattacharya, R. S. Katiyar, and A. S. Bhalla, “Leakage current behavior of SrBi₂Ta₂O₉ ferroelectric thin films on different bottom electrodes”, J. Appl. Phys., **92**, 6160, 2002.
- [57] S. M. Sze, *Physics of Semiconductor Devices*, 2nd ed., Chap. 7, p. 403. Wiley-Interscience, New York, 1981.