

Table of Contents

Abstract (Chinese)	i
Abstract (English)	iii
Acknowledgement	v
Table of Contents	vi
Figure Captions	x
List of Tables	xv

Chapter 1 Introduction.....1

1.1 Microoptics	1
1.2 Liquid-crystal displays (LCDs).....	3
1.3 Portable LCDs - Reflective/transflective LCDs	5
1.3.1 Reflective LCDs	6
1.3.2 Transflective LCDs	7
1.4 Microoptics in portable LCDs	8
1.4.1 Microoptics in reflective LCDs	9
1.4.2 Microoptics in transflective LCDs.....	11
1.5 Motivation and objective of this thesis	12
1.6 Organization of this thesis.....	14

Chapter 2 Principles of microoptics and portable LCDs.....16

2.1 Principle of microoptical components	16
2.1.1 Binary micro-gratings	17
2.1.2 Fresnel microlens	21
2.2 Principle of portable LCD technologies	25
2.2.1 Mixed-mode twisted nematic LCDs (MTN-LCDs).....	25
2.2.2 Super-twisted nematic LCDs (STN-LCDs)	29
2.2.3 Polymer dispersed liquid crystal (PDLC)	33
2.2.4 Cholesteric LCDs (Ch-LCDs)	36
2.2.5 Transflective LCDs (TR-LCDs)	41
2.3 Summary	44

Chapter 3	Fabrication Technologies	
	and Measurement Instruments	45
3.1	Introduction.....	45
3.2	Fabrication of surface relief microoptical components	47
3.2.1	Semiconductor process and plastic replication for binary relief optical components	49
3.2.2	Half-tone mask technology equipped with Excimer laser micromachining for continuous relief structures	51
3.3	Measurement instruments	56
3.3.1	Scanning electron microscope (SEM)	56
3.3.2	Atomic force microscope (AFM).....	57
3.3.3	Conoscopic system	58
Chapter 4	Light Control Films on Portable Displays	
	for Reflective Image Quality Enhancement	61
4.1	Introduction.....	61
4.2	Optical design of multidirectional AMA-LCF	64
4.2.1	Color dispersion.....	64
4.2.2	Moiré pattern.....	66
4.2.3	Surface scattering.....	69
4.3	Reflective LCDs with MAMA-LCF	70
4.3.1	Reflective color STN	70
4.3.2	Reflective PDLC.....	71
4.3.3	Reflective cholesteric LCD.....	72
4.4	Experiments	73
4.4.1	Fabrication of multidirectional AMA-LCF	73
4.4.2	LCD parameters	74
4.4.3	Evaluation of morphological and optical properties.....	75
4.5	Experimental results of MAMA-LCF	75
4.5.1	Surface reflection of MAMA-LCF	77
4.5.2	Image improvement by MAMA-LCF.....	80
4.6	Random grating LCF for larger size portable LCDs.....	84

4.6.1 Optical design of RG-LCF	85
4.6.2 Experimental results of RG-LCF	86
4.7 Discussion	87
4.8 Summary	88
Chapter 5 Image-Enhanced Reflector on Transflective LCDs for Transmissive Image Improvement	90
5.1 Introduction.....	90
5.1.1 Conventional transflective TFT-LCDs.....	90
5.1.2 Conventional transflective cholesteric LCDs (Ch-LCDs)	92
5.2 Image-enhanced reflector (IER)	94
5.2.1 IER for TFT-LCDs.....	94
5.2.2 IER for Ch-LCDs.....	99
5.3 Experiments	101
5.3.1 Fabrication of image-enhanced reflector	101
5.3.2 Evaluation of morphological and optical properties.....	102
5.4 Simulation and experimental results.....	103
5.4.1 Results of IER in transflective TFT-LCDs	103
5.4.2 Results of IER in full color transflective Ch-LCDs.....	107
5.5 Summary	110
Chapter 6 Micro-tube Array on Transflective Displays for Backlight Efficiency Increase.....	112
6.1 Introduction.....	112
6.2 Micro-tube Array (MTA) for backlight efficiency enhancement.....	114
6.3 Optical design of micro-tube array	116
6.3.1 Numerical calculation	116
6.3.2 Optimized simulation.....	118
6.4 Experiments	120
6.4.1 Fabrication of micro-tube array	120
6.4.2 Evaluation of morphological and optical properties.....	121
6.5 Results and discussion	121

6.6 Summary	125
Chapter 7 Conclusions and Future Works	126
7.1 Conclusions.....	126
7.1.1 Light control films for improving reflective images	127
7.1.2 Image-enhanced reflector for enhancing transmissive images	128
7.1.3 Micro-tube array for increasing backlight efficiency	129
7.2 Future works	130
7.2.1 High efficiency microoptical layer for LCD-TVs	132
7.2.2 Active microoptics for novel portable displays	133
Reference	137
Appendix – Color Demo Photographs	142
Appendix – SID Awards.....	145
Publication List	146
Vita	151



Figure Captions

Fig. 1-1. Microoptical Components: (a) microlens, (b) micropisms, and (b) DOEs....	2
Fig. 1-2. The applicable applications of Microoptics ^[15]	3
Fig. 1-3. A transmissive type LC display with backlight system and the light transmittance after light passes through each component of the LCD.	4
Fig. 1-4. Demo photos of a transmissive type LCD at the indoor and outdoor environment.	5
Fig. 1-5. Schematic plot of a reflective type LCD using ambient light as the light source to display the image.	6
Fig. 1-6. A device configuration of a transfective LCD. (a) transmissive mode using in dark ambient, and (b) reflective mode using in bright ambient.	8
Fig. 1-7. Typical office illumination and the reflected light distribution of reflective LCDs.	9
Fig. 1-8. Optical configuration of a reflective LCD with the rough surface reflector ^[20]	10
Fig. 1-9. Optical configuration of a reflective LCD with the micro-slant reflector ^[21]	10
Fig. 1-10. Optical configuration of a transfective LCD with double-cell gap micro-structure to increase the transmissive light efficiency ^{[22], [23]}	11
Fig. 2-1. Ideal sawtooth thickness profile for a blazed grating, and binary optical approximation to that profile.	19
Fig. 2-2. The intensity in the diffraction orders for linear diffraction gratings with n phase levels.	20
Fig. 2-3. Diffraction microlens of continuous and binary phase structure.	22
Fig. 2-4. Efficiencies of diffractive lens at focal point vs. the number of phase levels ^[29] . Here N=1 refers to an amplitude of Fresnel zone plate.	24
Fig. 2-5. Schematic plot of the basic working principle of MTN LCD.	26
Fig. 2-6. The parameters of a general MTN display employing polarizer, retardation film and reflector.	27
Fig. 2-7. Simulated results of the normalized reflectance $R_{\perp}$ of a 90° MTN cell as a function of $d\Delta n/\lambda$ and β	28
Fig. 2-8. Normalized reflectance $R_{\perp}$ of R, G, and B colors of a 90° MTN cell ($d\Delta n = 240\text{nm}$ and $\beta=20^{\circ}$) used in a single-polarizer reflective display.	29
Fig. 2-9. The relationship between voltage selection ratio and multiplexing line.	30
Fig. 2-10. The parameters of a general STN display employing polarizer, retardation film and reflector.	31

Fig. 2-11. Simulated results of the normalized reflectance $R_{\perp}$ of a 210° STN cell as a function of $d\Delta n/\lambda$ and β .	31
Fig. 2-12. Normalized reflectance $R_{\perp}$ of R, G, and B colors of a 210° STN cell ($d\Delta n = 630\text{nm}$ and $\beta=10^{\circ}$) used in a single-polarizer reflective display.	32
Fig. 2-13. The wavelength-dependent light reflectance of reflective color-STN cell with double retardation film.	33
Fig. 2-14. Orientation of liquid crystal droplets in the off and on states in the PDLC.	34
Fig. 2-15. Schematic diagram showing the working principle of reflective PDLCs.	35
Fig. 2-16. Absorbance of the dye doped PDLC versus the applied field ^[49] .	35
Fig. 2-17. Reflection spectra of the reflector and the dichroic dye doped PDLC reflective display ^[50] .	36
Fig. 2-18. The structure of the cholesteric textures: (a) planar, (b) focal conic, and (c) homeotropic texture.	37
Fig. 2-19. The basic operation principle of a reflective cholesteric LCD at (a) Voltage-off and (b) Voltage-on state.	38
Fig. 2-20. The microphotographs of the gray scale states of the cholesteric display ^[17] .	39
Fig. 2-21. Reflection spectra of the stacked multiple color cholesteric display. Curve a: all off, curve b: blue on, curve c: green on, curve d: red on, curve e: all on ^[58] .	40
Fig. 2-22. The parameters of a general transfective LCD employing parallel polarizers, two retardation films, and transfective layer.	42
Fig. 2-23. Normalized reflectance and transmittance of transfective LC cell as a function of $d\Delta n/\lambda$.	43
Fig. 2-24. Schematic plot of transfective LCDs using (a) single cell gap and (b) double cell gap structure ^[22] .	43
Fig. 3-1. Detail processes of lithography and etching to realize the technology of half-tone mask.	50
Fig. 3-2. Replication processes and the corresponding techniques ^[61] .	51
Fig. 3-3. Flow of the traditional multi-binary mask lithography.	52
Fig. 3-4. Coded half-tone mask.	53
Fig. 3-5. Schematic diagram of excimer laser micromachining system.	54
Fig. 3-6. 3D structure fabricated by projection of a gray scale mask.	55
Fig. 3-7. Concept of half-tone mask in excimer laser micromachining system.	56
Fig. 3-8. Concept of AFM and the optical lever: (left) a cantilever touching a sample;	

(right) the optical lever.....	57
Fig. 3-9. Display measurement setup of ELDIM EZContrast 160R (a) transmissive and (b) reflective mode.....	60
Fig. 4-1. The panel configuration of a reflective display laminating an light control film for collecting and redirecting ambient illuminations.	62
Fig. 4-2. Example photograph of unidirectional AMA-LCF used for brightness enhancement.	63
Fig. 4-3. Simulated results of color dispersion.	65
Fig. 4-4. Contour map of occurrence of moiré patterns.....	67
Fig. 4-5. Plane view of (a) unidirectional and (b) multidirectional AMA-LCFs for a color STN-LCD of pixel size of $25 \times 50 \mu\text{m}$	68
Fig. 4-6. Enlarged photographs of a color STN-LCD with (a) a unidirectional LCF and visible oblique strip moiré patterns, and (b) a multidirectional LCF and non-visible moiré patterns.....	68
Fig. 4-7. The estimated reflective light efficiency of a reflective LCD.....	70
Fig. 4-8. Schematic plot of system configuration of the MAMA-LCF on a reflective color STN-LCD.	71
Fig. 4-9. Schematic plot of system configuration of the MAMA-LCF on a reflective PDLC.	72
Fig. 4-10. Schematic plot of system configuration of the MAMA-LCF on a reflective cholesteric LCD.	73
Fig. 4-11. (a) Plane view, (b) cross-sectional profile, and (c) 3D view of the asymmetrical microlens array structure.	76
Fig. 4-12. Measured reflectivity (left part) and photos (right part) of the dark state image of (a) Bare STN, (b) STN-A, and (c) STN-B.	78
Fig. 4-13. Measured results of the dark state reflectance of (a) PDLC-A and (b) Ch-LCD-A.....	79
Fig. 4-14. Measured (a) reflectivity and (b) contrast ratio of reflective color-STN LCD as a function of viewing angle under illumination from -30°	81
Fig. 4-15. Measured (a) reflectivity and (b) contrast ratio of reflective PDLC as a function of viewing angle under illumination from -30°	81
Fig. 4-16. Measured (a) reflectivity and (b) contrast ratio of reflective Ch-LCD as a function of viewing angle under illumination from -30°	82
Fig. 4-17. Sample photographs of (a) color-STN LCD, (b) PDLC, and (c) Ch-LCD. The displays with MAMA-LCF clearly show much better image quality. (Color photos are shown in appendix)	83
Fig. 4-18. Optical configuration of a reflective LCD with the RG-LCF laminated onto the front surface.	84

Fig. 4-19. The designed pattern of random grating LCF for a reflective LCD.....	85
Fig. 4-20. The 3D view of random grating LCF measured by using AFM.	86
Fig. 4-21. Reflectance profile of the random grating light control film laminated on a reflective LCD.	87
Fig. 5-1. Schematic plot of transfective LCD using (a) single and (b) double cell gap.	91
Fig. 5-2. Operation principle of reflective/transmissive cholesteric display. (a) Planar and (b) focal conic state.	93
Fig. 5-3. Optical configuration of a novel transfective LCD with image-enhanced reflector (IER) and light control film (LCF).....	95
Fig. 5-4. A single cell gap transfective LCD employing image-enhanced reflector around reflective portion, where the dimension is for a typical RGB pixel. .	96
Fig. 5-5. TFT and metal lines on top glass for efficient area utilization.....	96
Fig. 5-6. Operation principle of the proposed novel transfective LCD employing a vertical alignment LC cell.....	97
Fig. 5-7. Schematic plot of the proposed full color transfective cholesteric LCD with an IER and wide band reflective cholesteric liquid crystal. (a) Bright and (b) dark state.	100
Fig. 5-8. Cross-sectional plot of the transfective Ch-LCD with image enhanced reflector (IER) and light control film (LCF).....	101
Fig. 5-9. Flow of the fabrication process of prototype IER.	102
Fig. 5-10. Schematic diagram of the experimental setup for characterizing the light utilization efficiency of fabricated IER.....	103
Fig. 5-11. (a) Top view and (b) literal view of fabricated image enhanced reflector measured by using SEM and AFM, respectively.	104
Fig. 5-12. The transmissive light utilization of the novel and conventional TR-LCDs.	105
Fig. 5-13. The simulated (a) contrast profile and (b) reflectance and transmittance profile of the novel and conventional TR-LCDs.	106
Fig. 5-14. The calculated NTSC ratio of transmissive region in conventional and with IER's transfective LCD.....	107
Fig. 5-15. Simulation results of the birefringence dependent reflection bandwidth of a Ch-LCD.....	108
Fig. 5-16. (a) The experimental setup and (b) the measured output light efficiency of the IER function on Ch-LCD.....	109
Fig. 5-17. (a) The schematic plot of a simple test sample of monochrome Ch-LCD with conventional backlight and (b) The demo photos of the same color images for both reflective (left part) and transmissive (right part) modes. (Color photos	

are shown in appendix)	110
Fig. 6-1. Schematic diagram of a conventional transfective LCD with a backlight system.	113
Fig. 6-2. A 3-D schematic of a single microtube structure for backlight collection. .	115
Fig. 6-3. Schematic diagram of a single cell-gap transfective LCD with microtube array.....	115
Fig. 6-4. (a) Three key parameters of microtube array which affect the properties of backlight collection, and (b) schematic of the structure used for numerical calculation.	117
Fig. 6-5. Illustration of the relationship between enhancement and tube height (d) under the condition that upper aperture diameter of a microtube (AP) is fixed. ...	118
Fig. 6-6. Illustration of the relationship between enhancement and upper aperture (AP) under the condition that tube height (d) is fixed.	119
Fig. 6-7. Illustration of the relationship between enhancement and tilt angle (θ_{tube}) under the condition that upper aperture diameter of a microtube (AP) is 5 μm and tube height (d) is 3 μm	119
Fig. 6-8. The flowchart of fabrication process of the microtube array: (a) exposure of 1 st mask, (b) thermal reflow process, (c) exposure of 2 nd mask, and (d) removal of remaining photoresist and Al on upper aperture.	121
Fig. 6-9. The fabricated structure observed by (a) SEM and (b) AFM.....	122
Fig. 6-10. Measurement results of (a) luminance and (b) enhancement as a function of viewing angle for microtube array structure.	123
Fig. 6-11. Photographs of a transfective LCD with and without MTA structure viewed from (a) normal and (b) oblique directions. (Color photos are shown in appendix).....	124
Fig. 7-1. Configuration of novel high efficiency color filter with hybrid microoptical components, color separation grating and deflection microlens.....	131
Fig. 7-2. Schematic plot of high quality color sequential LCD-TV structure.	133
Fig. 7-3. The basic optical configuration of an active microoptical display, iMoD TM	134
Fig. 7-4. The interference of light for displaying color images.	134
Fig. 7-5. (a) Measured reflectance of color reflective displays, and (b) demo photos of B/W reflective displays.....	135

List of Tables

Table. 3-1. List of materials, patterning, and fabrication tools of continuous and binary surface relief structure.....	78
Table. 4-1. Configuration of the test panels.....	74
Table. 4-2. Parameters of reflective color-STN, PDLC, and Ch-LCD used.....	75
Table. 4-3. Comparison of conventional image enhanced components used for reflective displays.....	88

