

Reference

- [1] R. McNeill, D. E. Weiss, J. H. Wardlaw, and R. Siudak, "Electronic Conduction In Polymers.1. Chemical Structure Of Polypyrrole," Australian Journal Of Chemistry, 16, pp. 1056-&, 1963.
- [2] B. A. Bolto and D. E. Weiss, "Electronic Conduction In Polymers.2. Electrochemical Reduction Of Polypyrrole At Controlled Potential," Australian Journal Of Chemistry, 16, pp. 1076-&, 1963.
- [3] B. A. Bolto, R. McNeill, and D. E. Weiss, "Electronic Conduction In Polymers.3. Electronic Properties Of Polypyrrole," Australian Journal Of Chemistry, 16, pp. 1090-&, 1963.
- [4] J. G. Lee, Y. G. Seol, and N. E. Lee, "Polymer thin film transistor with electroplated source and drain electrodes on a flexible substrate," Thin Solid Films, 515, pp. 805-809, 2006.
- [5] G. H. Kim, S. M. Yoon, C. A. Kim, K. H. Baek, I. K. You, S. Y. Kang, S. D. Ahn, and K. S. Suh, "Plastic-based organic thin-film transistors with thermally cured polymeric gate dielectrics," Journal Of The Korean Physical Society, 49, pp. 1239-1242, 2006.
- [6] Y. Shao, G. C. Bazan, and A. J. Heeger, "Long-lifetime polymer light-emitting electrochemical cells," Advanced Materials, 19, pp. 365-+, 2007.
- [7] S. A. Haque, S. Koops, N. Tokmoldin, J. R. Durrant, J. S. Huang, D. D. C. Bradley, and E. Palomares, "A multilayered polymer light-emitting diode using a nanocrystalline metal-oxide film as a charge-injection electrode," Advanced Materials, 19, pp. 683-+, 2007.
- [8] C. M. Yang, C. H. Wu, H. H. Liao, K. Y. Lai, H. P. Cheng, S. F. Horng, H. F. Meng, and J. T. Shy, "Enhanced photovoltaic response of organic solar cell by

- singlet-to-triplet exciton conversion," *Appl. Phys. Lett.*, 90, 2007.
- [9] S. Gunes, H. Neugebauer, and N. S. Sariciftci, "Conjugated polymer-based organic solar cells," *Chemical Reviews*, 107, pp. 1324-1338, 2007.
- [10] S. K. Lee, K. C. Lee, and S. S. Lee, "A simple method for microlens fabrication by the modified LIGA process," *J. Micromech. Microeng.*, 12, pp. 334-340, 2002.
- [11] A. Y. Smuk and N. M. Lawandy, "Direct laser fabrication of dense microlens arrays in semiconductor-doped glass," *J. Appl. Phys.*, 87, pp. 4026-4030, 2000.
- [12] S. Mihailov and S. Lazare, "Fabrication Of Refractive Microlens Arrays By Excimer-Laser Ablation Of Amorphous Teflon," *Appl. Optics*, 32, pp. 6211-6218, 1993.
- [13] A. Bernanose and P. Vouaux, "*Electroluminescence Organique - Etude Du Mode Demission," *Journal De Chimie Physique Et De Physico-Chimie Biologique*, 50, pp. 261-&, 1953.
- [14] A. Bernanose, M. Comte, and P. Vouaux, "*Sur Un Nouveau Mode Demission Lumineuse Chez Certains Composes Organiques," *Journal De Chimie Physique Et De Physico-Chimie Biologique*, 50, pp. 64-68, 1953.
- [15] C. W. Tang and S. A. Vanslyke, "Organic Electroluminescent Diodes," *Appl. Phys. Lett.*, 51, pp. 913-915, 1987.
- [16] M. H. Lu and J. C. Sturm, "Optimization of external coupling and light emission in organic light-emitting devices: modeling and experiment," *J. Appl. Phys.*, 91, pp. 595-604, 2002.
- [17] M. H. Lu and J. C. Sturm, "External coupling efficiency in planar organic light-emitting devices," *Appl. Phys. Lett.*, 78, pp. 1927-1929, 2001.
- [18] S. Moller and S. R. Forrest, "Improved light out-coupling in organic light

emitting diodes employing ordered microlens arrays," *J. Appl. Phys.*, 91, pp. 3324-3327, 2002.

- [19] H. Hoppe and N. S. Sariciftci, "Organic solar cells: An overview," *J. Mater. Res.*, 19, pp. 1924-1945, 2004.
- [20] Q. M. Zhou, Q. Hou, L. P. Zheng, X. Y. Deng, G. Yu, and Y. Cao, "Fluorene-based low band-gap copolymers for high performance photovoltaic devices," *Appl. Phys. Lett.*, 84, pp. 1653-1655, 2004.
- [21] S. E. Shaheen, D. Vangeneugden, R. Kiebooms, D. Vanderzande, T. Fromherz, F. Padinger, C. J. Brabec, and N. S. Sariciftci, "Low band-gap polymeric photovoltaic devices," *Synth. Met.*, 121, pp. 1583-1584, 2001.
- [22] K. Hamanaka and H. Koshi, "An artificial compound eye using a microlens array and its application to scale-invariant processing," *Opt. Rev.*, 3, pp. 264-268, 1996.
- [23] N. Nordman and O. Nordman, "Optical properties of two photoresists designed for charge-coupled device microlenses," *Opt. Eng.*, 40, pp. 2572-2576, 2001.
- [24] R. Danzebrink and M. A. Aegeuter, "Deposition of micropatterned coating using an ink-jet technique," *Thin Solid Films*, 351, pp. 115-118, 1999.
- [25] D. L. Macfarlane, V. Narayan, J. A. Tatum, W. R. Cox, T. Chen, and D. J. Hayes, "Microjet Fabrication Of Microlens Arrays," *IEEE Photonics Technol. Lett.*, 6, pp. 1112-1114, 1994.
- [26] J. Sung, H. Hockel, J. Brown, and E. G. Johnson, "Refractive micro-optics fabrication with a 1-D binary phase grating mask applicable to MOEMS processing," *J. Microlithogr. Microfabr. Microsyst.*, 4, 2005.
- [27] C. W. Tang, "2-Layer Organic Photovoltaic Cell," *Appl. Phys. Lett.*, 48, pp. 183-185, 1986.

- [28] S. E. Shaheen, C. J. Brabec, N. S. Sariciftci, F. Padinger, T. Fromherz, and J. C. Hummelen, "2.5% efficient organic plastic solar cells," *Appl. Phys. Lett.*, 78, pp. 841-843, 2001.
- [29] F. Padinger, R. S. Rittberger, and N. S. Sariciftci, "Effects of postproduction treatment on plastic solar cells," *Adv. Funct. Mater.*, 13, pp. 85-88, 2003.
- [30] C. J. Ko, Y. K. Lin, F. C. Chen, and C. W. Chu, "Modified buffer layers for polymer photovoltaic devices," *Appl. Phys. Lett.*, 90, 2007.
- [31] E. Kim and G. M. Whitesides, "Use Of Minimal Free-Energy And Self-Assembly To Form Shapes," *Chem. Mat.*, 7, pp. 1257-1264, 1995.
- [32] H. A. Biebuyck and G. M. Whitesides, "Self-Organization Of Organic Liquids On Patterned Self-Assembled Monolayers Of Alkanethiolates On Gold," *Langmuir*, 10, pp. 2790-2793, 1994.
- [33] D. M. Hartmann, O. Kibar, and S. C. Esener, "Optimization and theoretical modeling of polymer microlens arrays fabricated with the hydrophobic effect," *Appl. Optics*, 40, pp. 2736-2746, 2001.
- [34] D. M. Hartmann, O. Kibar, and S. C. Esener, "Characterization of a polymer microlens fabricated by use of the hydrophobic effect," *Opt. Lett.*, 25, pp. 975-977, 2000.
- [35] M. Keil, M. Beck, T. G. I. Ling, M. Graczyk, L. Montelius, and B. Heidari, "Development and characterization of silane antisticking layers on nickel-based stamps designed for nanoimprint lithography," *J. Vac. Sci. Technol. B*, 23, pp. 575-584, 2005.
- [36] J. K. Chen, F. H. Ko, K. F. Hsieh, C. T. Chou, and F. C. Chang, "Effect of fluoroalkyl substituents on the reactions of alkylchlorosilanes with mold surfaces for nanoimprint lithography," *J. Vac. Sci. Technol. B*, 22, pp. 3233-3241, 2004.

- [37] T. Bailey, B. J. Choi, M. Colburn, M. Meissl, S. Shaya, J. G. Ekerdt, S. V. Sreenivasan, and C. G. Willson, "Step and flash imprint lithography: Template surface treatment and defect analysis," *J. Vac. Sci. Technol. B*, 18, pp. 3572-3577, 2000.
- [38] C. D. Muller, A. Falcou, N. Reckefuss, M. Rojahn, V. Wiederhirn, P. Rudati, H. Frohne, O. Nuyken, H. Becker, and K. Meerholz, "Multi-colour organic light-emitting displays by solution processing," *Nature*, 421, pp. 829-833, 2003.
- [39] Z. L. Shen, P. E. Burrows, V. Bulovic, S. R. Forrest, and M. E. Thompson, "Three-color, tunable, organic light-emitting devices," *Science*, 276, pp. 2009-2011, 1997.
- [40] P. K. H. Ho, D. S. Thomas, R. H. Friend, and N. Tessler, "All-polymer optoelectronic devices," *Science*, 285, pp. 233-236, 1999.
- [41] W. K. Huang, C. J. Ko, and F. C. Chen, "Organic selective-area patterning method for microlens array fabrication," *Microelectron. Eng.*, 83, pp. 1333-1335, 2006.
- [42] F. C. Chen, W. K. Huang, and C. J. Ko, "Self-organization of microlens arrays caused by the spin-coating-assisted hydrophobic effect," *IEEE Photonics Technol. Lett.*, 18, pp. 2454-2456, 2006.
- [43] J. L. Wilbur, A. Kumar, H. A. Biebuyck, E. Kim, and G. M. Whitesides, "Microcontact printing of self-assembled monolayers: Applications in microfabrication," *Nanotechnology*, 7, pp. 452-457, 1996.
- [44] N. S. Ong, Y. H. Koh, and Y. Q. Fu, "Microlens array produced using hot embossing process," *Microelectron. Eng.*, 60, pp. 365-379, 2002.
- [45] T. N. Oder, J. Shakya, J. Y. Lin, and H. X. Jiang, "Nitride microlens arrays for blue and ultraviolet wavelength applications," *Appl. Phys. Lett.*, 82, pp.

3692-3694, 2003.

- [46] S. D. Moon, N. Lee, and S. Kang, "Fabrication of a microlens array using micro-compression molding with an electroformed mold insert," J. Micromech. Microeng., 13, pp. 98-103, 2003.
- [47] G. Kopitkovas, T. Lippert, C. David, S. Canulescu, A. Wokaun, and J. Gobrecht, "Fabrication of beam homogenizers in quartz by laser micromachining," J. Photochem. Photobiol. A-Chem., 166, pp. 135-140, 2004.
- [48] S. Biehl, R. Danzebrink, P. Oliveira, and M. A. Aegeuter, "Refractive microlens fabrication by ink-jet process," J. Sol-Gel Sci. Technol., 13, pp. 177-182, 1998.
- [49] J. Z. Wang, Z. H. Zheng, H. W. Li, W. T. S. Huck, and H. Sirringhaus, "Dewetting of conducting polymer inkjet droplets on patterned surfaces," Nat. Mater., 3, pp. 171-176, 2004.
- [50] M. Keil, M. Beck, G. Frennesson, E. Theander, E. Bolmsjo, L. Montelius, and B. Heidari, "Process development and characterization of antisticking layers on nickel-based stamps designed for nanoimprint lithography," J. Vac. Sci. Technol. B, 22, pp. 3283-3287, 2004.
- [51] C. J. Brabec, "Organic photovoltaics: technology and market," Sol. Energy Mater. Sol. Cells, 83, pp. 273-292, 2004.
- [52] W. L. Ma, C. Y. Yang, X. Gong, K. Lee, and A. J. Heeger, "Thermally stable, efficient polymer solar cells with nanoscale control of the interpenetrating network morphology," Adv. Funct. Mater., 15, pp. 1617-1622, 2005.
- [53] G. Li, V. Shrotriya, J. S. Huang, Y. Yao, T. Moriarty, K. Emery, and Y. Yang, "High-efficiency solution processable polymer photovoltaic cells by self-organization of polymer blends," Nat. Mater., 4, pp. 864-868, 2005.
- [54] A. Moliton and J. M. Nunzi, "How to model the behaviour of organic

- photovoltaic cells," Polymer International, 55, pp. 583-600, 2006.
- [55] D. Chirvase, Z. Chiguvare, M. Knipper, J. Parisi, V. Dyakonov, and J. C. Hummelen, "Temperature dependent characteristics of poly(3 hexylthiophene)-fullerene based heterojunction organic solar cells," J. Appl. Phys., 93, pp. 3376-3383, 2003.
- [56] E. A. Katz, D. Faiman, S. M. Tuladhar, J. M. Kroon, M. M. Wienk, T. Fromherz, F. Padinger, C. J. Brabec, and N. S. Sariciftci, "Temperature dependence for the photovoltaic device parameters of polymer-fullerene solar cells under operating conditions," J. Appl. Phys., 90, pp. 5343-5350, 2001.
- [57] V. D. Mihailetti, P. W. M. Blom, J. C. Hummelen, and M. T. Rispens, "Cathode dependence of the open-circuit voltage of polymer: fullerene bulk heterojunction solar cells," J. Appl. Phys., 94, pp. 6849-6854, 2003.
- [58] S. M. Tuladhar, D. Poplavskyy, S. A. Choulis, J. R. Durrant, D. D. C. Bradley, and J. Nelson, "Ambipolar charge transport in films of methanofullerene and poly(phenylenevinylene)/methanofullerene blends," Adv. Funct. Mater., 15, pp. 1171-1182, 2005.
- [59] G. M. Wang, J. Swensen, D. Moses, and A. J. Heeger, "Increased mobility from regioregular poly(3-hexylthiophene) field-effect transistors," J. Appl. Phys., 93, pp. 6137-6141, 2003.