

## Figure Caption

Fig. 1-1 Image pipeline stage of DSC .....	1
Fig. 1-2 Main steps of AE process .....	2
Figs. 1-3 (a) Normal, (b) Overexposed and (c) Underexposed images .....	4
Figs. 1-4 (a) Spot metering, (b) Mean metering, and (c) Center-weighted metering modes .....	4
Figs. 1-5 Images in special lighting conditions: (a) Backlighting, (b) Strong frontlighting, (c) Highlight, (d) Dark environment .....	5
Fig. 2-1 Configuration of the major parts of the imaging system .....	9
Fig. 2-2 The displacement of EV curve after EV compensation .....	14
Fig. 2-3 Exposure parameters are extracted from light meter .....	15
Fig. 3-1 Gray level from dark state to bright state .....	17
Fig. 3-2 Light metering method based on constant gray value to control the exposure time .....	17
Fig. 3-3 AE system based on LUTs propose by Kuno et al. ....	18
Fig. 3-4 Sampling area of the imaging sensor CCD .....	19
Fig. 3-5 Configuration of LUTs with address value n .....	20
Figs. 3-6 (a) The HIST distribution of the normal lighting state and (b) The HIST distribution of the backlighting state .....	23
Fig. 3-7 The features of HIST information in high contrast conditions .....	23
Figs. 3-8 (a) Photography and histogram in normal lighting state and (b) Photography and histogram in backlighting state .....	25
Fig. 3-9 High chroma images: (a) Background with blue sky before exposure compensation and (b) Background with white sky after exposure compensation .....	27
Fig. 3-10 Low chroma images: (a) Background with gray clouds before exposure	

compensation and (b) Background with white clouds after exposure compensation	.27
Fig. 3-11 Low chroma images: waterfall become bluish due to wrong AWB	.....27
Figs. 4-1 Photographs and histograms in special lighting conditions: (a) Highlight, (b) Backlighting, (c) Dark environment and (d) Strong frontlighting	.....32
Fig. 4-2 Image database in the over_bound1 and lower_bound2 plane	.....35
Fig. 4-3 Image database in the angle and distance plane	.....35
Fig. 4-4 Image database and membership functions of proposed 2-D scene analysis method	.....38
Fig. 4-5 The compensation amounts of different lighting regions	.....38
Fig. 5-1 Experimental flow chart of luminance detection models	.....41
Fig. 5-2 Configuration of the light metering system in simulation	.....42
Fig. 5-3 Linear regression of the experimental data	.....44
Fig. 5-4 Small angle inclination of the optical axis	.....45
Fig. 5-5 Experimental flow chart of scene analysis method	.....47
Fig. 5-6 Block diagrams of experiment and simulation configuration	.....48
Fig. 5-7 Total distance of the gravities in different kinds of database	.....50
Fig. 5-8 Total distance of the gravities of database in angle and distance directions	..50
Fig. 5-9 Plot of the percentage of image database as a function of angle	.....51
Fig. 5-10 Plot of the percentage of image database at as a function of distance	.....52
Fig. 5-11 Schematic diagram of the AE simulation process	.....53
Fig. 6-1 K value of Kuno model is a function of AGC gain (G), and mean integrated luminance signal value $\sum_m$ is a function of AGC gain (G)	.....57
Fig. 6-2 K value of Kuno model is a function of exposure time (T), and mean integrated luminance signal value $\sum_m$ is a function of exposure time (T)	.....57
Fig. 6-3 Constant K ( offset ) value as a function of F-number (A)	.....58

Fig. 6-4 Constant K( offset )value as a function of exposure time T .....	59
Fig. 6-5 Constant K ( offset ) value as a function of gain value (G) .....	59
Fig. 6-6 K value as a function of EV in small angle inclination ( $EV = \log_2(A^2/T)$ ), K value is a constant .....	60
Fig. 6-7 offset value as a function of EV in small angle inclination ( $EV = \log_2(A^2/T)$ ), offset value is a constant .....	61
Fig. 6-8 Light metering results of CS100 and Canon G5 ( $L$ ( $cd/m^2$ )) .....	62
Fig. 6-9 Performance of the parameters in different partition methods, $n_x$ = number of partition regions in angle axis, $n_y$ = number of partition regions in distance axis .....	63
Fig. 6-10 Results of degree of membership as a function of angle and five membership functions: VS, S, M, B, VB .....	64
Fig. 6-11 Results of degree of membership as a function of distance and five membership functions: VS, S, M, B, VB .....	65
Fig. 6-12 Results of compensation amount $\delta EV$ for each region; $\delta EV = \log_2 (T_2/T_1)$ , $T_1$ : exposure time before compensation, $T_2$ : exposure time after compensation .....	65
Fig. 6-13 Results of defuzzified compensation amount $\delta EV$ ; $\delta EV = \log_2 (T_2/T_1)$ , $T_1$ : exposure time before compensation, $T_2$ : exposure time after compensation, (angle is the ratio of dark to bright areas in a whole picture, and distance is the total ratio of dark and bright areas in a whole picture.) .....	66
Fig. 6-14 Results of defuzzified compensation amount $\delta EV$ ; $\delta EV = \log_2 (T_2/T_1)$ , $T_1$ : exposure time before compensation, $T_2$ : exposure time after compensation .....	66
Fig. 6-15 Comparison of strong backlighting condition for different light metering methods, CW = Center-Weighted metering mode .....	68
Fig. 6-16 Comparison of backlighting condition for different light metering methods .....	68
Fig. 6-17 Comparison of strong frontlighting condition for different light metering	

methods .....69

Fig. 6-18 Comparison of normal lighting condition for different light metering methods .....69

Fig. 6-19 Comparison of highlight condition for different light metering methods ...70

Fig. 6-20 Comparison of dark environment condition for different light metering methods .....70

Fig. 7-1 Pictures and database in the transition region .....74

