

# Contents

|                               |      |
|-------------------------------|------|
| Abstract ( in Chinese ) ..... | i    |
| Abstract ( in English ) ..... | ii   |
| Acknowledgement.....          | iii  |
| Contents .....                | iv   |
| Table Captions .....          | vii  |
| Figure Captions .....         | viii |

## Chapter 1 Introduction

|   |   |
|---|---|
| 1.1 Background .....  | 1 |
| 1.2 The issue of the existing process .....                 | 2 |
| 1.3 The advantage of the supercritical fluids process ..... | 4 |
| 1.4 Thesis organization .....                               | 5 |

## Chapter 2 The Purpose and Method of This Study

|   |    |
|---|----|
| 2.1 The purpose of this experiment .....    | 7  |
| 2.2 The apparatus for the experiment .....  | 7  |
| 2.3 The subject of this experiment .....    | 10 |
| 2.3.1 The first stage .....                 | 11 |
| 2.3.2 The second stage .....                | 11 |
| 2.3.3 The third stage .....                 | 11 |
| 2.4 The method for the experiment [4].....  | 11 |
| 2.4.1 Load, Purge, Pressurize chamber ..... | 12 |
| 2.4.2 Fill chamber.....                     | 13 |
| 2.4.3 Soak .....                            | 13 |
| 2.4.4 Agitation and Flush .....             | 13 |
| 2.4.5 Rinse .....                           | 14 |

2.4.6 Dry, Vent, Unload .....15

**Chapter 3 Theory**

3.1 Supercritical fluid [2].....17  
3.2 Supercritical carbon dioxide .....18  
3.3 The mechanism of the photoresist removal using supercritical fluid .....21

**Chapter 4 The Experiment**

4.1 The procedure of this experiment .....28  
4.2 The first stage, removal of photoresist after hard-bake on the bare silicon wafer  
4.2.1 The preparation of samples .....32  
4.2.2 The procedure of photoresist removal after hard-bake .....32  
4.3 The second stage, removal of photoresist after ion implantation process on the bare silicon wafer  
4.3.1 The preparation of samples .....33  
4.3.2 The procedure of photoresist removal after Arsenic ion implantation .....34  
4.4 The third stage, removal of photoresist and residue after silicon dioxide etched process  
4.4.1 The preparation of samples .....34  
4.4.2 The procedure for the removal of photoresist and residue after silicon dioxide etched process .....36

**Chapter 5 Result and Discussion**

5.1 The first stage, removal of photoresist after hard-bake on the bare silicon wafer  
.....37  
5.2 The removal of photoresist after ion implantation process  
5.2.1 After Arsenic ion implantation .....39

5.3 The removal of photoresist and residue after silicon dioxide etched process .....42

**Chapter 6 The Conclusion and Future Work**

6.1 The condition of photoresist removal using SCORR process .....61

6.2 The job we have to do before the SCORR process .....62

6.3 The issue of co-solvent remained on the wafer .....63

6.4 The conclusion.....63

6.5 Future work .....64

Reference .....65

Vita .....68

]



## Table Captions

|                |   |           |
|----------------|---|-----------|
| <b>Table 1</b> | <b>Comparison of physical-chemical properties in vapor, liquid and supercritical fluid of typical organic fluid [ 1 ] .....</b> | <b>5</b>  |
| <b>Table 2</b> | <b>Critical temperature and pressure for some common fluids [ 1 ] .....</b>   | <b>19</b> |
| <b>Table 3</b> | <b>Physical-chemical properties for CO<sub>2</sub> [3] .....</b>  | <b>20</b> |



## Figure Captions

|                  |  |           |
|------------------|--|-----------|
| <b>Figure 1</b>  | <b>Enable sub-130 nm residue removal .....</b>   | <b>4</b>  |
| <b>Figure 2</b>  | <b>Isco supercritical fluid extraction system .....</b>  | <b>8</b>  |
| <b>Figure 3</b>  | <b>Syringe pump .....</b>  | <b>8</b>  |
| <b>Figure 4</b>  | <b>The structure of extractor inside .....</b>   | <b>9</b>  |
| <b>Figure 5</b>  | <b>Cartridge .....</b>   | <b>9</b>  |
| <b>Figure 6</b>  | <b>The flowchart of the process sequence [4] .....</b>   | <b>16</b> |
| <b>Figure 7</b>  | <b>Opened container .....</b>  | <b>18</b> |
| <b>Figure 8</b>  | <b>Sealed container .....</b>  | <b>18</b> |
| <b>Figure 9</b>  | <b>The phase change from liquid and gas phases to supercritical phase .....</b>  | <b>18</b> |
| <b>Figure 10</b> | <b>Phase diagram of CO<sub>2</sub> .....</b>   | <b>21</b> |
| <b>Figure 11</b> | <b>The mechanism of P/R removal .....</b>  | <b>25</b> |
| <b>Figure 12</b> | <b>The hard crust of photoresist after the ion implantation or etching process, and indicating the direction of diffusion and solution of SCCO<sub>2</sub> and co-solvent .....</b>                                | <b>27</b> |
| <b>Figure 13</b> | <b>The time line chart of pressure in the chamber .....</b>  | <b>31</b> |
| <b>Figure 14</b> | <b>The sample preparation for the second stage .....</b>   | <b>33</b> |
| <b>Figure 15</b> | <b>The sample preparation of the third stage .....</b>   | <b>35</b> |
| <b>Figure 16</b> | <b>FTIR analysis of bare Si wafer, hard-bake wafer before and after SCORR treatment .....</b>  | <b>38</b> |
| <b>Figure 17</b> | <b>XPS analysis ( a ) before SCORR treatment, ( b ) bare Si wafer with SCORR treatment ( c ) the soak pressure = 3000 psi, ( d ) the soak pressure = 5000 psi, ( e ) the soak pressure = 7000 psi .....</b>        | <b>42</b> |
| <b>Figure 18</b> | <b>An OM picture that ( a ) oxide lines, after SCCO<sub>2</sub> and co-solvent treatment. ( b ) oxide lines, after H<sub>2</sub>SO<sub>4</sub> and H<sub>2</sub>O<sub>2</sub> treatment, and the P/R have been</b> |           |

stripped. ( c ) oxide pillars, after SCCO<sub>2</sub> and co-solvent treatment. ( b ) oxide pillarss, after H<sub>2</sub>SO<sub>4</sub> and H<sub>2</sub>O<sub>2</sub> treatment, and the P/R have been stripped .....43

**Figure 19** An SEM micrograph before SCORR treatment .....44

**Figure 20** An SEM micrograph of the oxide line in clean region after SCORR treatment .....44

**Figure 21** An SEM micrograph of the oxide line in non-clean region after SCORR treatment .....45

**Figure 22** An SEM micrograph of the P/R upon oxide line is swollen .....46

**Figure 23** An SEM micrograph of the P/R upon oxide line is large swollen and broken .....46

**Figure 24** An SEM micrograph of the photoresist of swell has been removed from the surface of oxide line .....47

**Figure 25** An SEM micrograph of the photoresist contamination, partially removed and entire removal of the photoresist .....48

**Figure 26** An OM picture of the sample after the treatment with SCCO<sub>2</sub> and the co-solvent in the same condition except the soak pressure. ( a ) 3000 psi, ( b ) 5000 psi, ( c ) 7000 psi .....53

**Figure 27** The influence of pressure on the removal of P/R using supercritical fluid .....54

**Figure 28** An OM picture of the sample after the treatment with SCCO<sub>2</sub> and the co-solvent in the same condition except the chamber temberature. ( a ) 70 , ( b ) 90 , ( c ) 110 .....55

**Figure 29** The influence of temperature on the removal of P/R using supercritical fluid .....56

|                  |  |           |
|------------------|--|-----------|
| <b>Figure 30</b> | <b>An OM picture of the sample after the treatment with SCCO<sub>2</sub> and the co-solvent in the same condition except the proportion of co-solvent in SCCO<sub>2</sub>. ( a ) 5 vol.%, ( b ) 7 vol.%, ( c ) 9 vol.% .....</b> | <b>57</b> |
| <b>Figure 31</b> | <b>The influence of co-solvent on the removal of P/R using supercritical fluid .....</b>   | <b>58</b> |
| <b>Figure 32</b> | <b>An OM picture of the sample after the treatment with SCCO<sub>2</sub> and the co-solvent in the same condition except the cycles for agitation step. ( a ) 4 cycles, ( b ) 6 cycles, ( c ) 8 cycles .....</b>                 | <b>59</b> |
| <b>Figure 33</b> | <b>The influence of fluid flow in flush step on the removal of P/R using supercritical fluid .....</b>   | <b>60</b> |
| <b>Figure 34</b> | <b>The conditions of photoresist removal using SCORR process .....</b>   | <b>61</b> |
| <b>Figure 35</b> | <b>Vapor-liquid critical surface extrapolated from data given in [10]. The PCO<sub>3</sub>-CO<sub>2</sub> mixture is signal-phase at all conditions above the surface [8] .....</b>  | <b>62</b> |

