

## References

- [1] M. Case, S. A. Maas, L. Larson, D. Rensch, D. Harame, and B. Meyerson, “An X-band monolithic active mixer in SiGe HBT technology,” in *IEEE MTT-S Dig.*, 1996, pp. 655–658.
- [2] J. S. Rieh, L. H. Lu, L. P. B. Katehi, P. Bhattacharya, E. T. Croke, G. E. Ponchak, and S. A. Alterovitz, “X- and Ku-band amplifiers based on Si/SiGe HBT’s and micromachined lumped components,” *IEEE Trans. Microw. Theory Tech.*, vol. 46, no. 5, pp. 685–694, May 1998.
- [3] U. Schaper and B. Holzapfi, “Analytical parameter extraction of the HBT equivalent circuit with T-like topology from measured parameters,” *IEEE Trans. Electron Devices*, vol. 43, pp. 493-498, Mar. 1995.
- [4] D. Costa, W. L. Liu, and J. S. Harris, “Direct extraction of the AlGaAs/GaAs heterojunction bipolar transistor small-signal equivalent circuit,” *IEEE Trans. Electron Devices*, vol. 38, pp. 2018-2024, Sept. 1991.
- [5] D. R. Pehlke and D. Pavlidis, “Evaluation of the factors determining HBT high-frequency performance by direct analysis of S-parameter data,” *IEEE Trans. Microwave Theory Tech.*, vol. 40, pp. 2367-2373, Dec. 1992.
- [6] D. Wu, D. L. Miller, M. Fukuda, and Y. Yun, “Unique determination of AlGaAs/GaAs HBT’s small-signal equivalent circuit parameters,” *GaAs IC Symp. 93 Tech. Dig.*, 1993. pp. 259-262.
- [7] T. K. Johansen, J. Vidkjær, and Viktor Krozer, “Substrate Effects in SiGe HBT Modeling,” in *Proc. GAAS Conf.*, 2003, pp. 445–448.
- [8] T. H. Teo, Y. Z. Xiong, J. S. Fu, H. Liao, J. Shi, M. Yu, and W. Li, “Systematic

Direct Parameter Extraction with Substrate Network of SiGe HBT,” in *Proc. RFIC Conf.*, 2004, pp. 603–606.

- [9] U. Basaran, N. Wieser, G. Feiler, and M. Berroth, “Small-Signal and High-Frequency Noise Modeling of SiGe HBTs,” *IEEE Trans. Microw. Theory Tech.*, vol. 53, no. 3, pp. 919–928, Mar. 2005.
- [10] K. Lee, K. Choi, S.-H. Kook, D.-H. Cho, K.-W. Park, and B. Kim, “Direct Parameter Extraction of SiGe HBTs for the VBIC Bipolar Compact Model”, *IEEE Trans. Electron Devices*, vol. 52, no. 3, pp. 375–384, Mar. 2005.
- [11] K.-M. Chen, A.-S. Peng, G.-W. Huang, H.-Y. Chen, S.-Y. Huang, C.-Y. Chang, H.-C. Tseng, T.-L. Hsu, and V. Liang, “Linearity and Power Characteristics of SiGe HBTs at High Temperatures for RF Applications”, *IEEE Trans. Electron Devices*, vol. 52, no. 7, pp. 1452–1458, Jul. 2005.
- [12] S. Lee, C. S. Kim, and H. K. Yu, “A Small-Signal RF Model and Its Parameter Extraction for Substrate Effects in RF MOSFETs”, *IEEE Trans. Electron Devices*, vol. 48, no. 7, pp. 1374–1379, Jul. 2001.
- [13] Y. Govert, P. J. Tasker, and K. H. Bachem, “A physical, yet simple, small-signal equivalent circuit for the heterojunction bipolar transistor,” *IEEE Trans. Microw. Theory Tech.*, vol. 45, no. 1, pp. 149–153, Jan. 1997.
- [14] B. Li, S. Prasad, L. W. Yang, and S. C. Wang, “A semianalytical parameter-extraction procedure for HBT equivalent circuit,” *IEEE Trans. Microw. Theory Tech.*, vol. 46, no. 10, pp. 1427–1435, Oct. 1998.
- [15] U. Basaran, and M. Berroth, “High Frequency Noise Modeling of SiGe HBTs Using Direct Parameter Extraction Technique”, in *IEEE MTT-S Int. Dig.*, Jun. 2002, pp. 189–195.

- [16] S. Bousnina, P. Mandeville, A. B. Kouki, R. Surridge, and F. M. Ghannouchi, “Direct Parameter-Extraction Method for HBT Small-Signal Model,” *IEEE Trans. Microw. Theory Tech.*, vol. 50, no. 2, pp. 529–536, Feb. 2002.
- [17] B. Sheinman, E. Wasige, M. Rudolph, R. Doerner, V. Sidorov, S. Cohen, and D. Ritter, “A Peeling Algorithm for Extraction of the HBT Small-Signal Equivalent Circuit,” *IEEE Trans. Microw. Theory Tech.*, vol. 50, no. 12, pp. 2804–2810, Dec. 2002.
- [18] F. Lenk, and M. Rudolph, “New Extraction Algorithm for GaAs-HBTs With Low Intrinsic Base Resistance”, in *IEEE MTT-S Int. Dig.*, Jun. 2002, pp. 725–728.
- [19] H.-Y. Chen, K.-M. Chen, G.-W. Huang, C.-Y. Chang, “A Novel Approach for Parameter Determination of HBT Small-Signal Equivalent Circuit”, *IEICE Trans. Electronics* , vol. E88-C, no. 6, pp. 1133–1141, Jun. 2005.
- [20] I. Kwon, M. Je, K. Lee, and H. Shin, “A Simple and Analytical Parameter-Extraction Method of a Microwave MOSFET,” *IEEE Trans. Microw. Theory Tech.*, vol. 50, no. 6, pp. 1503–1509, Jun. 2002.
- [21] Seonghearn Lee, “Improved Modeling for Transit Time and Excess Phase Delay of Advanced Bipolar Transistors at high Current Densities,” MWSCAS 2001. Proceeding of the 44<sup>th</sup> IEEE
- [22] Bahman Meskoob, Sheila Prasad, Mankuan Vai, James C. Vicek, Hiroya Sato, and Clifton G. Fonstad, “Bias-Dependence of the Intrinsic Element Values of InGaAs/InAlAs/InP inverted Heterjunction Bipolar Transistor,” *IEEE Trans. Microw. Theory Tech.*, vol. 40, no 5, May 1992.
- [23] Stanley Wolf, “Silicon Processing For The VLSI ERA vol 2: pp.474”
- [24] Shiming Zhang, Guofu Niu, John D. Cressler, Alvin J. Joseph\*. Greg Freemanpp, and D.L. Garame\*, “The Effects of Geometrical Scaling on the RF Performance of SiGe HBTs,” IEEE 2000

[25] Martins, E. Swart, J.W. Akpinar, M. Wolff,U. UNICAMP, Sao Paulo."A new thermal model for HBT RF circuit simulation" SEMO/IEEE MTT-S IMOC"97 Proceedings

