

# Bibliography

- [1] IEEE 802.16-2004, Part 16: Air Interface for Fixed Broadband Wireless Access Systems, Draft Standard for Local and metropolitan area networks, June 2004.
- [2] IEEE 802.16e/D12-2005, Part 16: Air Interface for Fixed and Mobile Broadband Wireless Access Systems—Amendment for Physical and Medium Access Control Layers for Combined Fixed and Mobile Operation in Licensed Bands, Oct. 2005.
- [3] Z. Abichar, Yanlin Peng, and J.M. Chang, “WiMax: The Emergence of Wireless Broadband,” IT Professional, vol.8, pp.44 - 48 July-Aug. 2006
- [4] N.O. Sokal and A.D Sokal, “Class E-A new class of high-efficiency tuned single-ended switching power amplifiers,” IEEE J. Solid-State Circuits, vol. 10, pp. 168 - 176, Jun. 1975.
- [5] F. H. Raab, “Idealized operation of the class E tuned power amplifier,” IEEE Trans. Circuits Syst., vol. 24, no. 12, pp. 725–735, Dec. 1977.
- [6] F. H. Raab and N. O. Sokal, “Transistor power losses in class-E tuned power amplifier,” IEEE J. Solid-State Circuits, vol. 13, pp. 912–914, Apr. 1978.
- [7] F. H. Raab, “Effects of circuit variations on the class E tuned power amplifier,” IEEE J. Solid-State Circuits, vol. 13, pp. 239-247, 1978.
- [8] R. Zulinski and J. Steadman, “Class E Power Amplifiers and Frequency Multipliers with finite DC-Feed Inductance,” IEEE Trans. Circuits System, vol. 34, pp. 1074-1087, Sep. 1987.
- [9] M. J. Chudobiak, “The use of parasitic nonlinear capacitors in Class-E amplifiers,” IEEE Trans. Circuits System I, Fundam. Theory Application, vol. 41, no. 12, pp. 941–944, Dec. 1994.
- [10] P. Alinikula, X. Choi, and S. L. Long, “Design of Class-E power amplifier with nonlinear parasitic output capacitance,” IEEE Trans. Circuits System II, Analog Digit. Signal Processing, vol. 46, no. 2, pp. 114–119, Feb. 1999.
- [11] S. Tawfik, Tian Tong, T.S. Nielsen, and T. Larsen, “A 1.9 GHz CMOS class E power

amplifier with +29 dBm output power and 58% PAE,” IEEE European Conference of Circuit Theory and Design, Vol. 1, pp. I/87 - I/90, 28 Aug.-2 Sept. 2005.

- [12] D. Milosevic, J. Van Der Tang, and A. Van Roermund , “Explicit design equations for class-E power amplifiers with small DC-feed inductance,” IEEE European Conference of Circuit Theory and Design, Vol. 3,pp. III/101 - III/104, 28 Aug.-2 Sept. 2005
- [13] Hyoung-Seok Oh, Taeksang Song, Sang-Hyun Baek, Euisik Yoon, and Choong-Ki Kim, “A fully integrated 1 V, +9.5 dBm, 43%-PAE injection-locked Class-E power amplifier for wireless sensor network,” IEEE Radio and Wireless Symposium, pp. 235-238, 17-19 Jan. 2006.
- [14] K.-C. Tsai and P. R. Gray, “A 1.9-GHz, 1-W CMOS class E power amplifier for wireless communications,” IEEE J. Solid-State Circuits, vol. 34, no. 7, pp. 962–970, Jul. 1999.
- [15] Changsik Yoo and Qiuting Huang, “A common-gate switched 0.9-W class-E power amplifier with 41% PAE in 0.25- $\mu$ m CMOS,” IEEE J. Solid-State Circuits, vol. 36, pp. 823 – 830, May 2001.
- [16] N. O. Sokal, “Class-E power amplifiers,” QEX/Communications Quarterly, pp. 9–20, Jan./Feb. 2001.
- [17] A. Mazzanti, L. Larcher, R. Brama, and F. Svelto, “Analysis of reliability and power efficiency in cascode class-E PAs,” IEEE J. Solid-State Circuits, vol. 41, pp. 1222 – 1229, May 2006.
- [18] Ka-Wai Ho and H.C. Luong, “A 1-V CMOS power amplifier for Bluetooth applications,” IEEE Trans. Circuits System II, Analog Digit. Signal Processing, vol. 50, pp.445 – 449, Aug. 2003.
- [19] F. H. Raab, “Class-E, Class-C, and Class-F Power Amplifiers Based Upon a Finite Number of Harmonics,” IEEE Transactions Microwave Theory and Techniques, vol. 49, pp. 1462 – 1468, Aug. 2001.
- [20] R. Negra and W. Bächtold, “Lumped-Element Load-Network Design for Class-E Power Amplifiers,” IEEE Transactions Microwave Theory and Techniques, vol. 54, pp. 2684-2690, June 2006.

- [21] Andrei Grebennikov, RF and Microwave Power Amplifier Design. New York: McGraw-Hill, 2005.
- [22] F. H. Raab and N. O. Sokal, "Transistor power losses in class-E tuned power amplifier," IEEE J. Solid-State Circuits, vol. 13, pp. 912–914, 1978.
- [23] T. Lee, The Design of CMOS Radio-Frequency Integrated Circuits, 2<sup>nd</sup> ed. Cambridge, U.K.: Cambridge Univ. Press, 2004.
- [24] A. Mazzanti, L. Larcher, R. Brama, and F. Svelto, "Analysis of reliability and power efficiency in cascode class-E PAs," Volume 41, pp. 1222 - 1229 May 2006
- [25] V. Saari, P. Juurakko, J. Ryynanen, and K. Halonen, "Integrated 2.4 GHz class-E CMOS power amplifier," IEEE RFIC, pp. 645- 648, June 2005.
- [26] S. Tawfik, Tian Tong, T.S. Nielsen, and T. Larsen, "A 1.9 GHz CMOS class E power amplifier with +29 dBm output power and 58% PAE," European Conference of Circuit Theory and Design, vol. 1,pp. I/87- I/90, 2005.
- [27] J. A. Herrera and J. L. Del Valle, "900 MHz band class E PA using high voltage n-channel transistors in standard CMOS technology," 2005 2nd International Conference on Electrical and Electronics Engineering, pp. 400- 403, 2005.
- [28] Tang Tat Hung and M. N. El-Gamal, "Class-E CMOS power amplifiers for RF applications," ISCAS 2003
- [29] Heydari P., Ying Zhang, "A novel high frequency, high-efficiency, differential class-E power amplifier in 0.18 um CMOS," Low Power Electronics and Design, 2003.
- [30] P. Luengvongsakorn and A. Thanachayanont, "A 0.1-W CMOS class-E power amplifier for Bluetooth applications," TENCON 2003.
- [31] Mertens, K.L.R.; Steyaert, M.S.J., " A 700-MHz 1-W fully differential CMOS class-E power amplifier," JSSC 2002.
- [32] David M. Pozar, Microwave engineering, 3rd ed. NJ, John Wiley & Sons, Inc., 2005.
- [33] M. J. Chudobiak, "The use of parasitic nonlinear capacitors in Class-E amplifiers," IEEE

Trans. Circuits Syst. I, Fundam. Theory Applicat., vol. 41, no. 12, pp. 941–944, Dec. 1994.

- [34] P. Alinikula, X. Choi, and S. L. Long, “Design of Class-E power amplifier with nonlinear parasitic output capacitance,” IEEE Trans. Circuits Syst. II, Analog Digit. Signal Process., vol. 46, no. 2, pp. 114–119, Feb. 1999.

