

# 附錄一 營建物料採購 Schema 標準 1.0 版文件

## Schema P-1 廠商登記審查表

```
<?xml version="1.0" encoding="UTF-8"?>
<!-- edited with XMLSPY v2004 rel. 4 U (http://www.xmlspy.com) by orion (ORiON) -->
<!-- edited with XML Spy v4.4 U (http://www.xmlspy.com) by http://soft163.com (http://soft163.com) -->
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema" elementFormDefault="qualified"
attributeFormDefault="unqualified">
  <xs:element name="CompanyInformation">
    <xs:annotation>
      <xs:documentation>Root Element</xs:documentation>
    </xs:annotation>
    <xs:complexType>
      <xs:sequence>
        <xs:element name="ComTypeNo" type="xs:string" maxOccurs="unbounded"/>
        <xs:element name="ComName" type="xs:string" maxOccurs="unbounded"/>
        <xs:element name="ComType" type="xs:string" minOccurs="0"/>
        <xs:element name="BusinessItem" type="BusinessItem" maxOccurs="unbounded"/>
        <xs:element name="Expertise" type="Expertise" minOccurs="0"/>
        <xs:element name="ApplicationDate" type="xs:date" minOccurs="0"/>
        <xs:element name="DateOfReceipt" type="xs:date" minOccurs="0"/>
        <xs:element name="DateOfPermission" type="xs:date" minOccurs="0"/>
        <xs:element name="ComName" type="xs:string"/>
        <xs:element name="ComNameForeign" type="xs:string" minOccurs="0"/>
        <xs:element name="EstablishDate" type="xs:date" minOccurs="0"/>
        <xs:element name="Comaddress" type="xs:string" minOccurs="0"/>
        <xs:element name="ComTaxNo" type="xs:string"/>
        <xs:element name="TaxID" type="xs:string" minOccurs="0"/>
        <xs:element name="PlantRegistrationNo" type="xs:string" minOccurs="0"/>
        <xs:element name="ComOwner" type="ComOwner"/>
        <xs:element name="CapitalAmount" type="UnitPrice" minOccurs="0"/>
        <xs:element name="EmployeesAmount" type="xs:positiveInteger" minOccurs="0"/>
        <xs:element name="InvoiceAddress" type="Address"/>
        <xs:element name="ContactAddress" type="Address"/>
        <xs:element name="ComPhoneNo" type="xs:string"/>
        <xs:element name="SheetTitle" type="SheetTitle" minOccurs="0"/>
        <xs:element name="Contact" type="Contact" maxOccurs="4"/>
        <xs:element name="LicensedEngineer" minOccurs="0" maxOccurs="unbounded">
          <xs:complexType>
            <xs:sequence>
              <xs:element name="Contact" type="Contact"/>
              <xs:element name="LicenseNo" type="xs:string"/>
            </xs:sequence>
          </xs:complexType>
        </xs:element>
        <xs:element name="SaftyHygieneEngineer" minOccurs="0" maxOccurs="unbounded">
          <xs:complexType>
            <xs:sequence>
              <xs:element name="Contact" type="Contact"/>
              <xs:element name="LicenseNo" type="xs:string"/>
            </xs:sequence>
          </xs:complexType>
        </xs:element>
        <xs:element name="WorkExperience" minOccurs="0" maxOccurs="unbounded">
          <xs:complexType>
```

```

<xs:sequence>
  <xs:element name="ProjectOwner" type="xs:string"/>
  <xs:element name="ContractName" type="xs:string"/>
  <xs:element name="ContractLocation" type="xs:string"/>
  <xs:element name="ComContractBookletNo" type="xs:string"/>
  <xs:element name="MainWorkItem" type="xs:string"/>
  <xs:element name="ContractAmount" type="totalAmount"/>
  <xs:element name="ContractPeriod">
    <xs:complexType>
      <xs:sequence>
        <xs:element name="ContractStartDate" type="xs:date"/>
        <xs:element name="EvalutaionCompleteDate" type="xs:date"/>
        <xs:element name="ActualCompletionDate" type="xs:date"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="CreditEvaluation" minOccurs="0">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="EvalutaionDate" type="xs:date"/>
      <xs:element name="Description" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="Attachment" type="xs:anyType" minOccurs="0"/>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:complexType name="SheetTitle">
  <xs:annotation>
    <xs:documentation>SheetTitle Common Element</xs:documentation>
  </xs:annotation>
  <xs:sequence>
    <xs:element name="SheetName" type="xs:string" minOccurs="0"/>
    <xs:element name="SheetID" type="xs:string" minOccurs="0"/>
    <xs:element name="ApplicationProccesNo" type="xs:string" minOccurs="0"/>
    <xs:element name="SheetDate" type="xs:date" minOccurs="0"/>
    <xs:element name="SchemaVersion" type="xs:string" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="Address">
  <xs:annotation>
    <xs:documentation>Address Common Element</xs:documentation>
  </xs:annotation>
  <xs:sequence>
    <xs:element name="Postal" type="xs:positiveInteger" minOccurs="0"/>
    <xs:element name="Area" type="xs:string" minOccurs="0"/>
    <xs:element name="City" type="xs:string" minOccurs="0"/>
    <xs:choice>
      <xs:element name="Line1" type="xs:string"/>
      <xs:element name="ContactAddress"/>
    </xs:choice>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="Contact">
  <xs:annotation>

```

```

    <xs:documentation>Contact Common Element</xs:documentation>
</xs:annotation>
<xs:sequence>
  <xs:element name="Name" type="xs:string"/>
  <xs:element name="Title" type="xs:string" minOccurs="0"/>
  <xs:choice>
    <xs:element name="PhoneNo" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
    <xs:element name="MobileNo" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
    <xs:element name="FaxNo" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
    <xs:element name="EmailAddress" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
  </xs:choice>
</xs:sequence>
</xs:complexType>
<xs:complexType name="Item">
  <xs:annotation>
    <xs:documentation>Item Common Element</xs:documentation>
  </xs:annotation>
  <xs:sequence>
    <xs:element name="ItemNo" type="xs:positiveInteger"/>
    <xs:element name="ItemName">
      <xs:complexType>
        <xs:simpleContent>
          <xs:extension base="xs:string">
            <xs:attribute name="PCCItemCode" type="xs:string" use="required"/>
          </xs:extension>
        </xs:simpleContent>
      </xs:complexType>
    </xs:element>
    <xs:element name="ItemNameForeign">
      <xs:complexType>
        <xs:simpleContent>
          <xs:extension base="xs:string">
            <xs:attribute name="ItemCode" type="xs:string" use="required"/>
          </xs:extension>
        </xs:simpleContent>
      </xs:complexType>
    </xs:element>
    <xs:element name="ItemCode">
      <xs:complexType>
        <xs:attribute name="ItemUnit" type="xs:string" use="required"/>
        <xs:attribute name="ItemUnitForeign" type="xs:string"/>
      </xs:complexType>
    </xs:element>
    <xs:element name="Spec">
      <xs:complexType>
        <xs:sequence>
          <xs:element name="Drescription"/>
          <xs:element name="IndustrySpec"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element name="Quantity" type="xs:positiveInteger"/>
    <xs:element name="Remark" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="UnitPrice">
  <xs:annotation>
    <xs:documentation>UnitPrice Common Element</xs:documentation>
  </xs:annotation>

```

```

<xs:sequence>
  <xs:element name="Amount" type="xs:float"/>
  <xs:element name="Currency" type="xs:string"/>
</xs:sequence>
</xs:complexType>
<xs:complexType name="totalAmount">
  <xs:annotation>
    <xs:documentation>totalAmount Common Element</xs:documentation>
  </xs:annotation>
  <xs:sequence>
    <xs:element name="totalAmountBeforeTax">
      <xs:complexType>
        <xs:simpleContent>
          <xs:extension base="xs:decimal">
            <xs:attribute name="Currency" type="xs:string" use="required"/>
          </xs:extension>
        </xs:simpleContent>
      </xs:complexType>
    </xs:element>
    <xs:element name="TaxType" type="xs:string" minOccurs="0"/>
    <xs:element name="TaxPercentage" type="xs:decimal" minOccurs="0"/>
    <xs:element name="TaxAmount" type="xs:positiveInteger"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="Payment">
  <xs:sequence>
    <xs:element name="PaymentType">
      <xs:complexType>
        <xs:all>
          <xs:element name="Cash">
            <xs:complexType>
              <xs:choice>
                <xs:element name="Percentage">
                  <xs:complexType>
                    <xs:simpleContent>
                      <xs:extension base="xs:decimal"/>
                    </xs:simpleContent>
                  </xs:complexType>
                </xs:element>
                <xs:element name="Amount">
                  <xs:complexType>
                    <xs:simpleContent>
                      <xs:extension base="xs:positiveInteger">
                        <xs:attribute name="Currency" type="xs:string" use="required"/>
                      </xs:extension>
                    </xs:simpleContent>
                  </xs:complexType>
                </xs:element>
              </xs:choice>
            </xs:complexType>
          </xs:element>
          <xs:element name="Check">
            <xs:complexType>
              <xs:sequence>
                <xs:element name="DuePeriod">
                  <xs:complexType>
                    <xs:attribute name="DueType" use="required">
                    <xs:simpleType>
                      <xs:restriction base="xs:string">

```

```

        <xs:enumeration value="天"/>
        <xs:enumeration value="月"/>
    </xs:restriction>
</xs:simpleType>
</xs:attribute>
</xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="Transferring">
    <xs:complexType>
        <xs:sequence>
            <xs:element name="BankNo" type="xs:positiveInteger"/>
            <xs:element name="BankAccount" type="xs:positiveInteger"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
</xs:all>
</xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
<xs:complexType name="BusinessItem">
    <xs:sequence>
        <xs:element name="ItemCode" type="xs:string" minOccurs="0"/>
        <xs:element name="ItemNo" type="xs:string"/>
        <xs:element name="ItemName" type="xs:string" maxOccurs="unbounded"/>
        <xs:element name="PCCMasterItemCode" type="xs:string" minOccurs="0"/>
        <xs:element name="WorkingArea" type="xs:string" minOccurs="0"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="Expertise">
    <xs:sequence>
        <xs:element name="ExpertiseNo" type="xs:string" minOccurs="0"/>
        <xs:element name="ExpertiseNote" type="xs:string" minOccurs="0"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="ComOwner">
    <xs:sequence>
        <xs:element name="Name" type="xs:string"/>
        <xs:element name="IDNo" type="xs:string" minOccurs="0"/>
    </xs:sequence>
</xs:complexType>
</xs:schema>

```

## Schema P-2 詢價單

```
<?xml version="1.0" encoding="UTF-8"?>
<!-- edited with XMLSPY v2004 rel. 4 U (http://www.xmlspy.com) by orion (ORiON) -->
<!-- edited with XML Spy v4.4 U (http://www.xmlspy.com) by http://soft163.com (http://soft163.com) -->
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema" elementFormDefault="qualified"
attributeFormDefault="unqualified">
  <xs:element name="RequestForQuotation">
    <xs:annotation>
      <xs:documentation>Root Element</xs:documentation>
    </xs:annotation>
    <xs:complexType>
      <xs:sequence>
        <xs:element name="SheetTitle" type="SheetTitle" minOccurs="0"/>
        <xs:element name="InvitationDate" type="xs:date"/>
        <xs:element name="QuotationDeadline" type="xs:date"/>
        <xs:element name="InvitationVersion" type="xs:string" minOccurs="0"/>
        <xs:element name="InvitedCom" minOccurs="0">
          <xs:complexType>
            <xs:sequence>
              <xs:element name="ComName" type="xs:string" minOccurs="0"/>
              <xs:element name="ComTaxNo" type="xs:string" minOccurs="0"/>
              <xs:element name="Address" type="Address" minOccurs="0"/>
              <xs:element name="Contact" type="Contact" maxOccurs="4"/>
            </xs:sequence>
          </xs:complexType>
        </xs:element>
        <xs:element name="Project">
          <xs:complexType>
            <xs:sequence>
              <xs:element name="ProjectNo" type="xs:string" minOccurs="0"/>
              <xs:element name="ProjectName" type="xs:string"/>
              <xs:element name="ProjectLocation" type="xs:string" minOccurs="0"/>
            </xs:sequence>
          </xs:complexType>
        </xs:element>
        <xs:element name="SubContract">
          <xs:complexType>
            <xs:sequence>
              <xs:element name="Name" type="xs:string"/>
              <xs:element name="No" type="xs:string" minOccurs="0"/>
            </xs:sequence>
          </xs:complexType>
        </xs:element>
        <xs:element name="Item" type="Item" maxOccurs="unbounded"/>
        <xs:element name="QuotationNotes" type="xs:string" minOccurs="0"/>
        <xs:element name="DeliveryLocation" type="xs:string"/>
        <xs:element name="DeliveryDescription" type="xs:string" minOccurs="0"/>
        <xs:element name="PaymentTerm" minOccurs="0">
          <xs:complexType>
            <xs:sequence>
              <xs:element name="PaymentOnDelivery" type="Payment" minOccurs="0"/>
              <xs:element name="AdvancePayment" type="Payment" minOccurs="0"/>
              <xs:element name="Retention" type="Payment" minOccurs="0"/>
              <xs:element name="DownPayment" type="Payment" minOccurs="0"/>
              <xs:element name="PaymentApplicationDeadlineInMonth" type="xs:positiveInteger"
minOccurs="0"/>
              <xs:element name="EndPayment" type="Payment" minOccurs="0"/>
            </xs:sequence>
          </xs:complexType>
        </xs:element>
      </xs:sequence>
    </xs:complexType>
  </xs:element>

```

```

        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="AcceptTerm" minOccurs="0" maxOccurs="unbounded">
    <xs:complexType>
        <xs:sequence>
            <xs:element name="TermNo" type="xs:string"/>
            <xs:element name="TermContent" type="xs:string"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="DelayPenalty" minOccurs="0">
    <xs:complexType>
        <xs:sequence>
            <xs:choice>
                <xs:element name="PenaltyPercentage" type="xs:float" minOccurs="0"/>
                <xs:element name="PenaltyAmount" type="xs:positiveInteger" minOccurs="0"/>
            </xs:choice>
            <xs:choice>
                <xs:element name="PenaltyPercentageLimit" type="xs:float" minOccurs="0"/>
                <xs:element name="PenaltyAmountLimit" type="xs:positiveInteger" minOccurs="0"/>
            </xs:choice>
        </xs:sequence>
    </xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:complexType name="SheetTitle">
    <xs:annotation>
        <xs:documentation>SheetTitle Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
        <xs:element name="SheetName" type="xs:string" minOccurs="0"/>
        <xs:element name="SheetID" type="xs:string" minOccurs="0"/>
        <xs:element name="ApplicationProccesNo" type="xs:string" minOccurs="0"/>
        <xs:element name="SheetDate" type="xs:date" minOccurs="0"/>
        <xs:element name="SchemaVersion" type="xs:string" minOccurs="0"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="Address">
    <xs:annotation>
        <xs:documentation>Address Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
        <xs:element name="Postal" type="xs:string" minOccurs="0"/>
        <xs:element name="Area" type="xs:string" minOccurs="0"/>
        <xs:element name="City" type="xs:string" minOccurs="0"/>
        <xs:element name="Line1" type="xs:string" minOccurs="0"/>
        <xs:element name="ContactAddress" type="xs:string"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="Contact">
    <xs:annotation>
        <xs:documentation>Contact Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
        <xs:element name="Name" type="xs:string"/>
        <xs:element name="Title" type="xs:string" minOccurs="0"/>

```

```

    <xs:choice>
      <xs:element name="PhoneNo" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
      <xs:element name="MobileNo" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
      <xs:element name="FaxNo" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
      <xs:element name="EmailAddress" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
    </xs:choice>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="Item">
  <xs:annotation>
    <xs:documentation>Item Common Element</xs:documentation>
  </xs:annotation>
  <xs:sequence>
    <xs:element name="ItemNo" type="xs:string" minOccurs="0"/>
    <xs:element name="ItemName" type="xs:string"/>
    <xs:element name="ItemNameForeign" type="xs:string" minOccurs="0"/>
    <xs:element name="ItemCode" type="xs:string" minOccurs="0"/>
    <xs:element name="ItemUnit" type="xs:string" minOccurs="0"/>
    <xs:element name="ItemUnitForeign" type="xs:string" minOccurs="0"/>
    <xs:element name="IndustrySpec">
      <xs:complexType>
        <xs:sequence>
          <xs:element name="IndustryName" type="xs:string" minOccurs="0"/>
          <xs:element name="IndustryID" type="xs:string"/>
          <xs:element name="Spec" maxOccurs="unbounded">
            <xs:complexType>
              <xs:sequence>
                <xs:element name="SpecName" type="xs:string"/>
                <xs:element name="SpecUnit" type="xs:string"/>
              </xs:sequence>
            </xs:complexType>
          </xs:element>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element name="Remark" type="xs:string" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="Payment">
  <xs:annotation>
    <xs:documentation>Payment Common Element</xs:documentation>
  </xs:annotation>
  <xs:sequence>
    <xs:element name="PaymentName" type="xs:string"/>
    <xs:element name="PaymentType">
      <xs:complexType>
        <xs:choice>
          <xs:element name="Cash">
            <xs:complexType>
              <xs:choice>
                <xs:element name="Percentage" type="xs:float" minOccurs="0"/>
                <xs:element name="Amount" type="xs:float" minOccurs="0"/>
                <xs:element name="Currency" type="xs:string" minOccurs="0"/>
              </xs:choice>
            </xs:complexType>
          </xs:element>
          <xs:element name="Check">
            <xs:complexType>
              <xs:sequence>

```



```

        <xs:element name="DuePeriod" type="xs:positiveInteger" minOccurs="0"/>
        <xs:element name="DueType" type="xs:string" minOccurs="0"/>
    </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="Transferring">
    <xs:complexType>
        <xs:sequence>
            <xs:element name="BankNo" type="xs:string" minOccurs="0"/>
            <xs:element name="BankAccount" type="xs:string" minOccurs="0"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
</xs:choice>
</xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:schema>

```



## SchemaP-3 報價單

```
<?xml version="1.0" encoding="UTF-8"?>
<!-- edited with XMLSPY v2004 rel. 4 U (http://www.xmlspy.com) by orion (ORiON) -->
<!-- edited with XML Spy v4.4 U (http://www.xmlspy.com) by http://soft163.com (http://soft163.com) -->
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema" elementFormDefault="qualified"
attributeFormDefault="unqualified">
  <xs:element name="Quotation">
    <xs:annotation>
      <xs:documentation>Root Element</xs:documentation>
    </xs:annotation>
    <xs:complexType>
      <xs:sequence>
        <xs:element name="RequestForQuotationID" type="xs:string" minOccurs="0"/>
        <xs:element name="SheetTitle" type="SheetTitle" minOccurs="0"/>
        <xs:element name="QuotationDate" type="xs:date"/>
        <xs:element name="QuotationVersion" type="xs:string" minOccurs="0"/>
        <xs:element name="QuotationCom">
          <xs:complexType>
            <xs:sequence>
              <xs:element name="ComName" type="xs:string"/>
              <xs:element name="ComTaxNo" type="xs:string"/>
              <xs:element name="Address" type="Address" minOccurs="0"/>
              <xs:element name="ComPhoneNo" type="xs:string"/>
              <xs:element name="Contact" type="Contact" maxOccurs="4"/>
            </xs:sequence>
          </xs:complexType>
        </xs:element>
        <xs:element name="Project" type="Project"/>
        <xs:element name="SubContract">
          <xs:complexType>
            <xs:sequence>
              <xs:element name="Name" type="xs:string"/>
              <xs:element name="No" type="xs:string" minOccurs="0"/>
            </xs:sequence>
          </xs:complexType>
        </xs:element>
        <xs:element name="QuotationItem" maxOccurs="unbounded">
          <xs:complexType>
            <xs:sequence>
              <xs:element name="Item" type="Item"/>
              <xs:element name="Unit" type="xs:string"/>
              <xs:element name="Quantity" type="xs:string"/>
              <xs:element name="UnitPice" type="UnitPrice"/>
              <xs:element name="ItemAmount" type="ItemAmount" minOccurs="0"/>
            </xs:sequence>
          </xs:complexType>
        </xs:element>
        <xs:element name="TotalAmount" type="totalAmount"/>
        <xs:element name="Remark" type="xs:string" minOccurs="0"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:complexType name="SheetTitle">
    <xs:annotation>
      <xs:documentation>SheetTitle Common Element</xs:documentation>
    </xs:annotation>
  </xs:complexType>
</xs:schema>
```

```

    <xs:element name="SheetName" type="xs:string" minOccurs="0"/>
    <xs:element name="SheetID" type="xs:string" minOccurs="0"/>
    <xs:element name="ApplicationProccesNo" type="xs:string" minOccurs="0"/>
    <xs:element name="SheetDate" type="xs:date" minOccurs="0"/>
    <xs:element name="SchemaVersion" type="xs:string" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="Address">
  <xs:annotation>
    <xs:documentation>Address Common Element</xs:documentation>
  </xs:annotation>
  <xs:sequence>
    <xs:element name="Postal" type="xs:string" minOccurs="0"/>
    <xs:element name="Area" type="xs:string" minOccurs="0"/>
    <xs:element name="City" type="xs:string" minOccurs="0"/>
    <xs:element name="Line1" type="xs:string" minOccurs="0"/>
    <xs:element name="ContactAddress" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="Contact">
  <xs:annotation>
    <xs:documentation>Contact Common Element</xs:documentation>
  </xs:annotation>
  <xs:sequence>
    <xs:element name="Name" type="xs:string"/>
    <xs:element name="Title" type="xs:string" minOccurs="0"/>
    <xs:choice>
      <xs:element name="PhoneNo" type="xs:string" minOccurs="0"/>
      <xs:element name="MobileNo" type="xs:string" minOccurs="0"/>
      <xs:element name="FaxNo" type="xs:string" minOccurs="0"/>
      <xs:element name="EmailAddress" type="xs:string" minOccurs="0"/>
    </xs:choice>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="Item">
  <xs:annotation>
    <xs:documentation>Item Common Element</xs:documentation>
  </xs:annotation>
  <xs:sequence>
    <xs:element name="ItemNo" type="xs:string" minOccurs="0"/>
    <xs:element name="ItemName" type="xs:string"/>
    <xs:element name="ItemNameForeign" type="xs:string" minOccurs="0"/>
    <xs:element name="ItemCode" type="xs:string" minOccurs="0"/>
    <xs:element name="ItemUnit" type="xs:string" minOccurs="0"/>
    <xs:element name="ItemUnitForeign" type="xs:string" minOccurs="0"/>
    <xs:element name="IndustrySpec">
      <xs:complexType>
        <xs:sequence>
          <xs:element name="IndustryName" type="xs:string" minOccurs="0"/>
          <xs:element name="IndustryID" type="xs:string"/>
          <xs:element name="Spec" maxOccurs="unbounded">
            <xs:complexType>
              <xs:sequence>
                <xs:element name="SpecName" type="xs:string"/>
                <xs:element name="SpecUnit" type="xs:string"/>
              </xs:sequence>
            </xs:complexType>
          </xs:element>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
  </xs:sequence>

```

```

        </xs:complexType>
    </xs:element>
    <xs:element name="Remark" type="xs:string" minOccurs="0"/>
</xs:sequence>
</xs:complexType>
<xs:complexType name="UnitPrice">
    <xs:annotation>
        <xs:documentation>UnitPrice Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
        <xs:element name="Amount" type="xs:float"/>
        <xs:element name="Currency" type="xs:string"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="ItemAmount">
    <xs:annotation>
        <xs:documentation>UnitPrice and ItemAmount Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
        <xs:element name="Amount" type="xs:float"/>
        <xs:element name="Currency" type="xs:string"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="totalAmount">
    <xs:annotation>
        <xs:documentation>totalAmount Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
        <xs:element name="totalAmountBeforeTax">
            <xs:complexType>
                <xs:simpleContent>
                    <xs:extension base="xs:decimal">
                        <xs:attribute name="Currency" type="xs:string" use="required"/>
                    </xs:extension>
                </xs:simpleContent>
            </xs:complexType>
        </xs:element>
        <xs:element name="TaxType" type="xs:string" minOccurs="0"/>
        <xs:element name="TaxPercentage" type="xs:decimal" minOccurs="0"/>
        <xs:element name="TaxAmount" type="xs:positiveInteger"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="Project">
    <xs:sequence>
        <xs:element name="ProjectNo" type="xs:string" minOccurs="0"/>
        <xs:element name="ProjectName" type="xs:string"/>
        <xs:element name="ProjectLocation" type="xs:string" minOccurs="0"/>
    </xs:sequence>
</xs:complexType>
</xs:schema>

```

## Schema P-4 採購單

```
<?xml version="1.0" encoding="UTF-8"?>
<!-- edited with XMLSPY v2004 rel. 4 U (http://www.xmlspy.com) by orion (ORiON) -->
<!-- edited with XML Spy v4.4 U (http://www.xmlspy.com) by http://soft163.com (http://soft163.com) -->
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema" elementFormDefault="qualified"
attributeFormDefault="unqualified">
  <xs:element name="PurchaseOrder">
    <xs:annotation>
      <xs:documentation>Root Element</xs:documentation>
    </xs:annotation>
    <xs:complexType>
      <xs:sequence>
        <xs:element name="SheetTitle" type="SheetTitle" minOccurs="0"/>
        <xs:element name="OrderDate" type="xs:date"/>
        <xs:element name="Supplier">
          <xs:complexType>
            <xs:sequence>
              <xs:element name="SupplierID" type="xs:string" minOccurs="0"/>
              <xs:element name="Name" type="xs:string"/>
              <xs:element name="Address" type="Address" minOccurs="0"/>
              <xs:element name="Contact" type="Contact" minOccurs="1" maxOccurs="4"/>
            </xs:sequence>
          </xs:complexType>
        </xs:element>
        <xs:element name="Buyer">
          <xs:complexType>
            <xs:sequence>
              <xs:element name="BuyerID" type="xs:string" minOccurs="0"/>
              <xs:element name="Name" type="xs:string"/>
              <xs:element name="InvoiceAddress" type="Address" minOccurs="0"/>
              <xs:element name="ContactAddress" type="Address" minOccurs="0"/>
              <xs:element name="ComTaxNo" type="xs:string" minOccurs="0"/>
              <xs:element name="Contact" type="Contact" minOccurs="0"/>
            </xs:sequence>
          </xs:complexType>
        </xs:element>
        <xs:element name="Project">
          <xs:complexType>
            <xs:sequence>
              <xs:element name="ProjectNo" type="xs:string" minOccurs="0"/>
              <xs:element name="ProjectName" type="xs:string"/>
              <xs:element name="ProjectLocation" type="xs:string" minOccurs="0"/>
            </xs:sequence>
          </xs:complexType>
        </xs:element>
        <xs:element name="SubContract">
          <xs:complexType>
            <xs:sequence>
              <xs:element name="Name" type="xs:string"/>
              <xs:element name="No" type="xs:string" minOccurs="0"/>
            </xs:sequence>
          </xs:complexType>
        </xs:element>
        <xs:element name="PurchaseItem" maxOccurs="unbounded">
          <xs:complexType>
            <xs:sequence>
              <xs:element name="Item" type="Item"/>
            </xs:sequence>
          </xs:complexType>
        </xs:element>
      </xs:sequence>
    </xs:complexType>
  </xs:element>

```

```

        <xs:element name="Unit" type="xs:string"/>
        <xs:element name="Quantity" type="xs:string"/>
        <xs:element name="UnitPice" type="UnitPrice"/>
        <xs:element name="ItemAmount" type="ItemAmount" minOccurs="0"/>
    </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="TotalAmount" type="TotalAmount"/>
<xs:element name="DeliveryNotice" minOccurs="0">
    <xs:complexType>
        <xs:sequence>
            <xs:element name="Address" type="Address"/>
            <xs:element name="DeliveryDescription" type="xs:string" minOccurs="0"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="PaymentTerm" minOccurs="0">
    <xs:complexType>
        <xs:sequence>
            <xs:element name="PaymentOnDelivery" type="Payment" minOccurs="0"/>
            <xs:element name="AdvancePayment" type="Payment" minOccurs="0"/>
            <xs:element name="Retention" type="Payment" minOccurs="0"/>
            <xs:element name="DownPayment" type="Payment" minOccurs="0"/>
            <xs:element name="PaymentApplicationDeadlineInMonth" type="xs:positiveInteger"
minOccurs="0"/>
            <xs:element name="EndPayment" type="Payment" minOccurs="0"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="AcceptTerm" minOccurs="0" maxOccurs="unbounded">
    <xs:complexType>
        <xs:sequence>
            <xs:element name="TermNo" type="xs:string" minOccurs="0"/>
            <xs:element name="TermContent" type="xs:string" minOccurs="0"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="DelayPenalty" minOccurs="0">
    <xs:complexType>
        <xs:sequence>
            <xs:choice>
                <xs:element name="PenaltyPercentage" type="xs:float" minOccurs="0"/>
                <xs:element name="PenaltyAmount" type="xs:positiveInteger" minOccurs="0"/>
            </xs:choice>
            <xs:choice>
                <xs:element name="PenaltyPercentageLimit" type="xs:float" minOccurs="0"/>
                <xs:element name="PenaltyAmountLimit" type="xs:positiveInteger" minOccurs="0"/>
            </xs:choice>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="Remark" type="xs:string" minOccurs="0"/>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:complexType name="SheetTitle">
    <xs:annotation>
        <xs:documentation>SheetTitle Common Element</xs:documentation>
    </xs:annotation>

```

```

<xs:sequence>
  <xs:element name="SheetName" type="xs:string" minOccurs="0"/>
  <xs:element name="SheetID" type="xs:string" minOccurs="0"/>
  <xs:element name="ApplicationProccesNo" type="xs:string" minOccurs="0"/>
  <xs:element name="SheetDate" type="xs:date" minOccurs="0"/>
  <xs:element name="SchemaVersion" type="xs:string" minOccurs="0"/>
</xs:sequence>
</xs:complexType>
<xs:complexType name="Address">
  <xs:annotation>
    <xs:documentation>Address Common Element</xs:documentation>
  </xs:annotation>
  <xs:sequence>
    <xs:element name="Postal" type="xs:string" minOccurs="0"/>
    <xs:element name="Area" type="xs:string" minOccurs="0"/>
    <xs:element name="City" type="xs:string" minOccurs="0"/>
    <xs:element name="Line1" type="xs:string" minOccurs="0"/>
    <xs:element name="ContactAddress" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="Contact">
  <xs:annotation>
    <xs:documentation>Contact Common Element</xs:documentation>
  </xs:annotation>
  <xs:sequence>
    <xs:element name="Name" type="xs:string"/>
    <xs:element name="Title" type="xs:string" minOccurs="0"/>
    <xs:choice>
      <xs:element name="PhoneNo" type="xs:string" minOccurs="0"/>
      <xs:element name="MobileNo" type="xs:string" minOccurs="0"/>
      <xs:element name="FaxNo" type="xs:string" minOccurs="0"/>
      <xs:element name="EmailAddress" type="xs:string" minOccurs="0"/>
    </xs:choice>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="Item">
  <xs:annotation>
    <xs:documentation>Item Common Element</xs:documentation>
  </xs:annotation>
  <xs:sequence>
    <xs:element name="ItemNo" type="xs:string" minOccurs="0"/>
    <xs:element name="ItemName" type="xs:string"/>
    <xs:element name="ItemNameForeign" type="xs:string" minOccurs="0"/>
    <xs:element name="ItemCode" type="xs:string" minOccurs="0"/>
    <xs:element name="ItemUnit" type="xs:string" minOccurs="0"/>
    <xs:element name="ItemUnitForeign" type="xs:string" minOccurs="0"/>
    <xs:element name="IndustrySpec">
      <xs:complexType>
        <xs:sequence>
          <xs:element name="IndustryName" type="xs:string" minOccurs="0"/>
          <xs:element name="IndustryID" type="xs:string"/>
          <xs:element name="Spec" maxOccurs="unbounded">
            <xs:complexType>
              <xs:sequence>
                <xs:element name="SpecName" type="xs:string"/>
                <xs:element name="SpecUnit" type="xs:string"/>
              </xs:sequence>
            </xs:complexType>
          </xs:element>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
  </xs:sequence>
</xs:complexType>

```

```

        </xs:sequence>
    </xs:complexType>
</xs:element>
    <xs:element name="Remark" type="xs:string" minOccurs="0"/>
</xs:sequence>
</xs:complexType>
<xs:complexType name="UnitPrice">
    <xs:annotation>
        <xs:documentation>UnitPrice Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
        <xs:element name="Amount" type="xs:float"/>
        <xs:element name="Currency" type="xs:string"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="ItemAmount">
    <xs:annotation>
        <xs:documentation>UnitPrice and ItemAmount Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
        <xs:element name="Amount" type="xs:float"/>
        <xs:element name="Currency" type="xs:string"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="TotalAmount">
    <xs:annotation>
        <xs:documentation>totalAmount Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
        <xs:element name="TotalAmountBeforeTax" type="xs:float"/>
        <xs:element name="Currency" type="xs:string"/>
        <xs:element name="TaxType" type="xs:string" minOccurs="0"/>
        <xs:element name="TaxPercentage" type="xs:float" minOccurs="0"/>
        <xs:element name="TaxAmount" type="xs:float" minOccurs="0"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="Payment">
    <xs:annotation>
        <xs:documentation>Payment Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
        <xs:element name="PaymentName" type="xs:string"/>
        <xs:element name="PaymentType">
            <xs:complexType>
                <xs:choice>
                    <xs:element name="Cash">
                        <xs:complexType>
                            <xs:choice>
                                <xs:element name="Percentage" type="xs:float" minOccurs="0"/>
                                <xs:element name="Amount" type="xs:float" minOccurs="0"/>
                                <xs:element name="Currency" type="xs:string" minOccurs="0"/>
                            </xs:choice>
                        </xs:complexType>
                    </xs:element>
                    <xs:element name="Check">
                        <xs:complexType>
                            <xs:sequence>
                                <xs:element name="DuePeriod" type="xs:positiveInteger" minOccurs="0"/>
                                <xs:element name="DueType" type="xs:string" minOccurs="0"/>
                            </xs:sequence>
                        </xs:complexType>
                    </xs:element>
                </xs:choice>
            </xs:complexType>
        </xs:element>
    </xs:sequence>

```



```
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element name="Transferring">
      <xs:complexType>
        <xs:sequence>
          <xs:element name="BankNo" type="xs:string" minOccurs="0"/>
          <xs:element name="BankAccount" type="xs:string" minOccurs="0"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
  </xs:choice>
</xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:schema>
```



## Schema P-5 訂貨/委送單

```
<?xml version="1.0" encoding="UTF-8"?>
<!-- edited with XMLSPY v2004 rel. 4 U (http://www.xmlspy.com) by gary (ORiON) -->
<!-- edited with XML Spy v4.4 U (http://www.xmlspy.com) by http://soft163.com (http://soft163.com) -->
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema" elementFormDefault="qualified"
attributeFormDefault="unqualified">
  <xs:element name="Order">
    <xs:annotation>
      <xs:documentation>P-15Order</xs:documentation>
    </xs:annotation>
    <xs:complexType>
      <xs:sequence>
        <xs:element name="SheetTitle" type="SheetTitle" minOccurs="0"/>
        <xs:element name="ContractNumber" type="xs:string"/>
        <xs:element name="OrderDate" type="xs:date"/>
        <xs:element name="PurchaseNumber" type="xs:string"/>
        <xs:element name="Contract" type="Contract"/>
        <xs:element name="Project" type="Project"/>
        <xs:element name="Certificate" type="xs:string"/>
        <xs:element name="NonRadiation" type="xs:string"/>
        <xs:element name="Payment" type="Payment"/>
        <xs:element name="TransactionTerms" type="xs:string"/>
        <xs:element name="WeightHouse" type="xs:string"/>
        <xs:element name="NoticeDate" type="xs:date"/>
        <xs:element name="Supplier" type="Supplier"/>
        <xs:element name="DeliveryTerms" type="xs:string"/>
        <xs:element name="Dueday" type="Dueday"/>
        <xs:element name="DeliveryDestination" type="DeliveryDestination"/>
        <xs:element name="Item" type="Item" maxOccurs="unbounded"/>
        <xs:element name="TotalProductWeight" type="xs:float"/>
        <xs:element name="InvoiceFormat" type="xs:string"/>
        <xs:element name="TotalAmount" type="TotalAmount"/>
        <xs:element name="Buyer" type="Buyer"/>
        <xs:element name="Remark" type="xs:string"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:complexType name="SheetTitle">
    <xs:annotation>
      <xs:documentation>SheetTitle Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
      <xs:element name="SheetName" type="xs:string" minOccurs="0"/>
      <xs:element name="SheetID" type="xs:string" minOccurs="0"/>
      <xs:element name="ApplicationProccesNo" type="xs:string" minOccurs="0"/>
      <xs:element name="SheetDate" type="xs:date" minOccurs="0"/>
      <xs:element name="SchemaVersion" type="xs:string" minOccurs="0"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="Contract">
    <xs:sequence>
      <xs:element name="ContractName" type="xs:string" minOccurs="0"/>
      <xs:element name="ContractNumber" type="xs:string" minOccurs="0"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="Project">
    <xs:sequence>
```

```

        <xs:element name="ProjectName" type="xs:string"/>
        <xs:element name="ProjectNumber" type="xs:string" minOccurs="0"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="DeliveryDestination">
    <xs:sequence>
        <xs:element name="Company" type="xs:string" minOccurs="0"/>
        <xs:element name="Address" type="Address"/>
        <xs:element name="Contact" type="Contact" minOccurs="0"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="Buyer">
    <xs:sequence>
        <xs:element name="BuyerID" type="xs:string" minOccurs="0"/>
        <xs:element name="Name" type="xs:string"/>
        <xs:element name="InvoiceAddress" type="Address"/>
        <xs:element name="ContactAddress" type="Address"/>
        <xs:element name="ComTaxNo" type="xs:string"/>
        <xs:element name="Contact" type="Contact"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="Dueday">
    <xs:sequence>
        <xs:element name="Startday" type="xs:date" minOccurs="0"/>
        <xs:element name="Endday" type="xs:date" minOccurs="0"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="Supplier">
    <xs:sequence>
        <xs:element name="SupplierID" type="xs:string" minOccurs="0"/>
        <xs:element name="Name" type="xs:string"/>
        <xs:element name="Address">
            <xs:complexType>
                <xs:sequence>
                    <xs:element name="Postal" type="xs:positiveInteger" minOccurs="0"/>
                    <xs:element name="Area" type="xs:string" minOccurs="0"/>
                    <xs:element name="City" type="xs:string" minOccurs="0"/>
                    <xs:element name="Line1" type="xs:string" minOccurs="0"/>
                    <xs:element name="ContactAddress" type="xs:string" minOccurs="0"/>
                </xs:sequence>
            </xs:complexType>
        </xs:element>
        <xs:element name="Contact" type="Contact" minOccurs="0"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="Contact">
    <xs:annotation>
        <xs:documentation>Contact Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
        <xs:element name="Name" type="xs:string"/>
        <xs:element name="Title" type="xs:string"/>
        <xs:element name="PhoneNo" type="xs:string" minOccurs="0"/>
        <xs:element name="MobileNo" type="xs:string" minOccurs="0"/>
        <xs:element name="FaxNo" type="xs:string" minOccurs="0"/>
        <xs:element name="EmailAddress" type="xs:string" minOccurs="0"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="Payment">

```

```

<xs:sequence>
  <xs:element name="PaymentType">
    <xs:complexType>
      <xs:all>
        <xs:element name="Percentage" type="xs:decimal"/>
        <xs:element name="Amount">
          <xs:complexType>
            <xs:simpleContent>
              <xs:extension base="xs:decimal">
                <xs:attribute name="Currency" type="xs:string" use="required"/>
              </xs:extension>
            </xs:simpleContent>
          </xs:complexType>
        </xs:element>
        <xs:element name="DuePeriod">
          <xs:complexType>
            <xs:simpleContent>
              <xs:extension base="xs:positiveInteger">
                <xs:attribute name="Unit" type="xs:string" use="required"/>
              </xs:extension>
            </xs:simpleContent>
          </xs:complexType>
        </xs:element>
        <xs:element name="BankNo" type="xs:positiveInteger"/>
        <xs:element name="BankAccount" type="xs:positiveInteger"/>
      </xs:all>
      <xs:attribute name="PaymentType" type="xs:string" use="required"/>
    </xs:complexType>
  </xs:element>
</xs:sequence>
</xs:complexType>
<xs:complexType name="TotalAmount">
  <xs:annotation>
    <xs:documentation>totalAmount Common Element</xs:documentation>
  </xs:annotation>
  <xs:sequence>
    <xs:element name="TotalAmountBeforeTax">
      <xs:complexType>
        <xs:simpleContent>
          <xs:extension base="xs:decimal">
            <xs:attribute name="Currency" type="xs:string" use="required"/>
          </xs:extension>
        </xs:simpleContent>
      </xs:complexType>
    </xs:element>
    <xs:element name="TaxType" type="xs:string"/>
    <xs:element name="TaxPercentage" type="xs:decimal" minOccurs="0"/>
    <xs:element name="TaxAmount" type="xs:positiveInteger"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="Address">
  <xs:annotation>
    <xs:documentation>Address Common Element</xs:documentation>
  </xs:annotation>
  <xs:sequence>
    <xs:element name="Postal" type="xs:string" minOccurs="0"/>
    <xs:element name="Area" type="xs:string" minOccurs="0"/>
    <xs:element name="City" type="xs:string" minOccurs="0"/>
    <xs:element name="Line1" type="xs:string" minOccurs="0"/>
  </xs:sequence>

```

```

    <xs:element name="ContactAddress" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="Item">
  <xs:annotation>
    <xs:documentation>Item Common Element</xs:documentation>
  </xs:annotation>
  <xs:sequence>
    <xs:element name="ItemNo" type="xs:string" minOccurs="0"/>
    <xs:element name="ItemName" type="xs:string"/>
    <xs:element name="ItemNameForeign" type="xs:string" minOccurs="0"/>
    <xs:element name="ItemCode" type="xs:string" minOccurs="0"/>
    <xs:element name="ItemUnit" type="xs:string" minOccurs="0"/>
    <xs:element name="ItemUnitForeign" type="xs:string" minOccurs="0"/>
    <xs:element name="IndustrySpec">
      <xs:complexType>
        <xs:sequence>
          <xs:element name="IndustryName" type="xs:string" minOccurs="0"/>
          <xs:element name="IndustryID" type="xs:string"/>
          <xs:element name="Spec" maxOccurs="unbounded">
            <xs:complexType>
              <xs:sequence>
                <xs:element name="SpecName" type="xs:string"/>
                <xs:element name="SpecUnit" type="xs:string"/>
              </xs:sequence>
            </xs:complexType>
          </xs:element>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element name="Remark" type="xs:string" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>
</xs:schema>

```



## Schema P-6 出貨/料通知單

```
<?xml version="1.0" encoding="UTF-8"?>
<!-- edited with XMLSPY v2004 rel. 4 U (http://www.xmlspy.com) by gary (ORiON) -->
<!-- edited with XML Spy v4.4 U (http://www.xmlspy.com) by http://soft163.com (http://soft163.com) -->
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema" elementFormDefault="qualified"
attributeFormDefault="unqualified">
  <xs:element name="DeliveryNotice">
    <xs:annotation>
      <xs:documentation>P-15</xs:documentation>
    </xs:annotation>
    <xs:complexType>
      <xs:sequence>
        <xs:element name="SheetTitle" type="SheetTitle" minOccurs="0"/>
        <xs:element name="DeliveryNumber" type="xs:string"/>
        <xs:element name="OrderNumber" type="xs:string"/>
        <xs:element name="BuyerNumber" type="xs:string"/>
        <xs:element name="SellerNumber" type="xs:string"/>
        <xs:element name="Contact" type="Contact"/>
        <xs:element name="NoticeDate" type="xs:date"/>
        <xs:element name="PreDeliveryDate" type="xs:date"/>
        <xs:element name="WeightHouse" type="xs:string"/>
        <xs:element name="Carrier" type="Carrier"/>
        <xs:element name="DeliveryDestination" type="DeliveryDestination"/>
        <xs:element name="Item" type="Item" maxOccurs="unbounded"/>
        <xs:element name="Certificate" type="xs:string"/>
        <xs:element name="NonRadiation" type="xs:string"/>
        <xs:element name="Remark" type="xs:string"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:complexType name="Carrier">
    <xs:sequence>
      <xs:element name="CarrierNumber" type="xs:string" minOccurs="0"/>
      <xs:element name="CarrierName" type="xs:string" minOccurs="0"/>
      <xs:element name="VehicleIdNum" type="xs:string" minOccurs="0"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="DeliveryDestination">
    <xs:sequence>
      <xs:element name="Company" type="xs:string" minOccurs="0"/>
      <xs:element name="Address" type="Address"/>
      <xs:element name="Contact" type="Contact" minOccurs="0"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="Item">
    <xs:annotation>
      <xs:documentation>Item Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
      <xs:element name="ItemNo" type="xs:string" minOccurs="0"/>
      <xs:element name="ItemName" type="xs:string"/>
      <xs:element name="ItemNameForeign" type="xs:string" minOccurs="0"/>
      <xs:element name="ItemCode" type="xs:string" minOccurs="0"/>
      <xs:element name="ItemUnit" type="xs:string" minOccurs="0"/>
      <xs:element name="ItemUnitForeign" type="xs:string" minOccurs="0"/>
      <xs:element name="IndustrySpec">
        <xs:complexType>
```

```

        <xs:sequence>
            <xs:element name="IndustryName" type="xs:string" minOccurs="0"/>
            <xs:element name="IndustryID" type="xs:string"/>
            <xs:element name="Spec" maxOccurs="unbounded">
                <xs:complexType>
                    <xs:sequence>
                        <xs:element name="SpecName" type="xs:string"/>
                        <xs:element name="SpecUnit" type="xs:string"/>
                    </xs:sequence>
                </xs:complexType>
            </xs:element>
        </xs:sequence>
    </xs:complexType>
    <xs:element name="Remark" type="xs:string" minOccurs="0"/>
</xs:sequence>
</xs:complexType>
<xs:complexType name="SheetTitle">
    <xs:annotation>
        <xs:documentation>SheetTitle Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
        <xs:element name="SheetName" type="xs:string" minOccurs="0"/>
        <xs:element name="SheetID" type="xs:string" minOccurs="0"/>
        <xs:element name="ApplicationProccesNo" type="xs:string" minOccurs="0"/>
        <xs:element name="SheetDate" type="xs:date" minOccurs="0"/>
        <xs:element name="SchemaVersion" type="xs:string" minOccurs="0"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="Contact">
    <xs:annotation>
        <xs:documentation>Contact Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
        <xs:element name="Name" type="xs:string"/>
        <xs:element name="Title" type="xs:string" minOccurs="0"/>
        <xs:choice>
            <xs:element name="PhoneNo" type="xs:string" minOccurs="0"/>
            <xs:element name="MobileNo" type="xs:string" minOccurs="0"/>
            <xs:element name="FaxNo" type="xs:string" minOccurs="0"/>
            <xs:element name="EmailAddress" type="xs:string" minOccurs="0"/>
        </xs:choice>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="Address">
    <xs:annotation>
        <xs:documentation>Address Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
        <xs:element name="Postal" type="xs:string" minOccurs="0"/>
        <xs:element name="Area" type="xs:string" minOccurs="0"/>
        <xs:element name="City" type="xs:string" minOccurs="0"/>
        <xs:element name="Line1" type="xs:string" minOccurs="0"/>
        <xs:element name="ContactAddress" type="xs:string"/>
    </xs:sequence>
</xs:complexType>
</xs:schema>

```

## Schema P-7 出貨單

```
<?xml version="1.0" encoding="UTF-8"?>
<!-- edited with XMLSPY v2004 rel. 4 U (http://www.xmlspy.com) by orion (ORiON) -->
<!-- edited with XML Spy v4.4 U (http://www.xmlspy.com) by http://soft163.com (http://soft163.com) -->
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema" elementFormDefault="qualified"
attributeFormDefault="unqualified">
  <xs:element name="Delivery">
    <xs:annotation>
      <xs:documentation>P-08</xs:documentation>
    </xs:annotation>
    <xs:complexType>
      <xs:sequence>
        <xs:element name="SheetTitle" type="SheetTitle"/>
        <xs:element name="DeliveryNumber" type="xs:string" minOccurs="0"/>
        <xs:element name="DeliveryNoteNumber" type="xs:string" minOccurs="0"/>
        <xs:element name="OrderNumber" type="xs:string" minOccurs="0"/>
        <xs:element name="DeliveryDate" type="xs:date"/>
        <xs:element name="Carrier" type="Carrier" minOccurs="0"/>
        <xs:element name="DeliveryDestination" type="DeliveryDestination" minOccurs="0"/>
        <xs:element name="Item" type="Item" maxOccurs="unbounded"/>
        <xs:element name="Contact" type="Contact"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:complexType name="Carrier">
    <xs:sequence>
      <xs:element name="CarrierNumber" type="xs:string" minOccurs="0"/>
      <xs:element name="CarrierName" type="xs:string" minOccurs="0"/>
      <xs:element name="VehicleIdNum" type="xs:string" minOccurs="0"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="DeliveryDestination">
    <xs:sequence>
      <xs:element name="Company" type="xs:string" minOccurs="0"/>
      <xs:element name="Address" type="Address"/>
      <xs:element name="Contact" type="Contact" minOccurs="0"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="SheetTitle">
    <xs:annotation>
      <xs:documentation>SheetTitle Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
      <xs:element name="SheetName" type="xs:string" minOccurs="0"/>
      <xs:element name="SheetID" type="xs:string" minOccurs="0"/>
      <xs:element name="ApplicationProccesNo" type="xs:string" minOccurs="0"/>
      <xs:element name="SheetDate" type="xs:date" minOccurs="0"/>
      <xs:element name="SchemaVersion" type="xs:string" minOccurs="0"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="Address">
    <xs:annotation>
      <xs:documentation>Address Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
      <xs:element name="Postal" type="xs:string" minOccurs="0"/>
      <xs:element name="Area" type="xs:string" minOccurs="0"/>
    </xs:sequence>
  </xs:complexType>
</xs:schema>
```



```

        <xs:element name="City" type="xs:string" minOccurs="0"/>
        <xs:element name="Line1" type="xs:string" minOccurs="0"/>
        <xs:element name="ContactAddress" type="xs:string"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="Contact">
    <xs:annotation>
        <xs:documentation>Contact Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
        <xs:element name="Name" type="xs:string"/>
        <xs:element name="Title" type="xs:string" minOccurs="0"/>
        <xs:choice>
            <xs:element name="PhoneNo" type="xs:string" minOccurs="0"/>
            <xs:element name="MobileNo" type="xs:string" minOccurs="0"/>
            <xs:element name="FaxNo" type="xs:string" minOccurs="0"/>
            <xs:element name="EmailAddress" type="xs:string" minOccurs="0"/>
        </xs:choice>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="Item">
    <xs:annotation>
        <xs:documentation>Item Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
        <xs:element name="ItemNo" type="xs:string" minOccurs="0"/>
        <xs:element name="ItemName" type="xs:string"/>
        <xs:element name="ItemNameForeign" type="xs:string" minOccurs="0"/>
        <xs:element name="ItemCode" type="xs:string" minOccurs="0"/>
        <xs:element name="ItemUnit" type="xs:string" minOccurs="0"/>
        <xs:element name="ItemUnitForeign" type="xs:string" minOccurs="0"/>
        <xs:element name="IndustrySpec">
            <xs:complexType>
                <xs:sequence>
                    <xs:element name="IndustryName" type="xs:string" minOccurs="0"/>
                    <xs:element name="IndustryID" type="xs:string"/>
                    <xs:element name="Spec" maxOccurs="unbounded">
                        <xs:complexType>
                            <xs:sequence>
                                <xs:element name="SpecName" type="xs:string"/>
                                <xs:element name="SpecUnit" type="xs:string"/>
                            </xs:sequence>
                        </xs:complexType>
                    </xs:element>
                </xs:sequence>
            </xs:complexType>
        </xs:element>
        <xs:element name="Remark" type="xs:string" minOccurs="0"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="UnitPrice">
    <xs:annotation>
        <xs:documentation>UnitPrice Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
        <xs:element name="Amount" type="xs:float"/>
        <xs:element name="Currency" type="xs:string"/>
    </xs:sequence>
</xs:complexType>

```

```

<xs:complexType name="ItemAmount">
  <xs:annotation>
    <xs:documentation>UnitPrice and ItemAmount Common Element</xs:documentation>
  </xs:annotation>
  <xs:sequence>
    <xs:element name="Amount" type="xs:float"/>
    <xs:element name="Currency" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="TotalAmount">
  <xs:annotation>
    <xs:documentation>totalAmount Common Element</xs:documentation>
  </xs:annotation>
  <xs:sequence>
    <xs:element name="TotalAmountBeforeTax" type="xs:float"/>
    <xs:element name="Currency" type="xs:string"/>
    <xs:element name="TaxType" type="xs:string" minOccurs="0"/>
    <xs:element name="TaxPercentage" type="xs:float" minOccurs="0"/>
    <xs:element name="TaxAmount" type="xs:float" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="Payment">
  <xs:annotation>
    <xs:documentation>Payment Common Element</xs:documentation>
  </xs:annotation>
  <xs:sequence>
    <xs:element name="PaymentName" type="xs:string"/>
    <xs:element name="PaymentType">
      <xs:complexType>
        <xs:choice>
          <xs:element name="Cash">
            <xs:complexType>
              <xs:choice>
                <xs:element name="Percentage" type="xs:float" minOccurs="0"/>
                <xs:element name="Amount" type="xs:float" minOccurs="0"/>
                <xs:element name="Currency" type="xs:string" minOccurs="0"/>
              </xs:choice>
            </xs:complexType>
          </xs:element>
          <xs:element name="Check">
            <xs:complexType>
              <xs:sequence>
                <xs:element name="DuePeriod" type="xs:positiveInteger" minOccurs="0"/>
                <xs:element name="DueType" type="xs:string" minOccurs="0"/>
              </xs:sequence>
            </xs:complexType>
          </xs:element>
          <xs:element name="Transferring">
            <xs:complexType>
              <xs:sequence>
                <xs:element name="BankNo" type="xs:string" minOccurs="0"/>
                <xs:element name="BankAccount" type="xs:string" minOccurs="0"/>
              </xs:sequence>
            </xs:complexType>
          </xs:element>
        </xs:choice>
      </xs:complexType>
    </xs:element>
  </xs:sequence>
</xs:complexType>

```

```
</xs:complexType>  
</xs:schema>
```



## Schema P-8 退貨通知單

```
<?xml version="1.0" encoding="UTF-8"?>
<!-- edited with XMLSPY v2004 rel. 4 U (http://www.xmlspy.com) by orion (ORiON) -->
<!-- edited with XML Spy v4.4 U (http://www.xmlspy.com) by http://soft163.com (http://soft163.com) -->
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema" elementFormDefault="qualified"
attributeFormDefault="unqualified">
  <xs:element name="RejectionNote">
    <xs:annotation>
      <xs:documentation>P-09</xs:documentation>
    </xs:annotation>
    <xs:complexType>
      <xs:sequence>
        <xs:element name="SheetTitle" type="SheetTitle" minOccurs="0"/>
        <xs:element name="RejectionNumber" type="xs:string" minOccurs="0"/>
        <xs:element name="InspectUnit" type="InspectUnit" minOccurs="0"/>
        <xs:element name="Supplier" type="Supplier"/>
        <xs:element name="Contract" type="Contract" minOccurs="0"/>
        <xs:element name="Project" type="Project"/>
        <xs:element name="Rejection" type="Rejection" minOccurs="0"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:complexType name="InspectUnit">
    <xs:sequence>
      <xs:element name="Name" type="xs:string" minOccurs="0"/>
      <xs:element name="InspectNo" type="xs:string" minOccurs="0"/>
      <xs:element name="Contact" type="Contact"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="Supplier">
    <xs:sequence>
      <xs:element name="ComName" type="xs:string"/>
      <xs:element name="Contact">
        <xs:complexType>
          <xs:sequence>
            <xs:element name="Name" type="xs:string"/>
            <xs:element name="Title" type="xs:string" minOccurs="0"/>
            <xs:choice>
              <xs:element name="PhoneNo" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
              <xs:element name="MobileNo" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
              <xs:element name="FaxNo" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
              <xs:element name="EmailAddress" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
            </xs:choice>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element name="CompanyNumber" type="xs:string" minOccurs="0"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="Contract">
    <xs:sequence>
      <xs:element name="ContractName" type="xs:string"/>
      <xs:element name="ContractNumber" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="Rejection">
    <xs:sequence>
```

```

        <xs:element name="DeliveryNumber" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
        <xs:element name="Item" type="Item" maxOccurs="unbounded"/>
        <xs:element name="Reason" type="xs:string" minOccurs="0"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="SheetTitle">
    <xs:annotation>
        <xs:documentation>SheetTitle Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
        <xs:element name="SheetName" type="xs:string" minOccurs="0"/>
        <xs:element name="SheetID" type="xs:string" minOccurs="0"/>
        <xs:element name="ApplicationProccesNo" type="xs:string" minOccurs="0"/>
        <xs:element name="SheetDate" type="xs:date" minOccurs="0"/>
        <xs:element name="SchemaVersion" type="xs:string" minOccurs="0"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="Address">
    <xs:annotation>
        <xs:documentation>Address Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
        <xs:element name="Postal" type="xs:string" minOccurs="0"/>
        <xs:element name="Area" type="xs:string" minOccurs="0"/>
        <xs:element name="City" type="xs:string" minOccurs="0"/>
        <xs:element name="Line1" type="xs:string" minOccurs="0"/>
        <xs:element name="ContactAddress" type="xs:string"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="Contact">
    <xs:annotation>
        <xs:documentation>Contact Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
        <xs:element name="Name" type="xs:string"/>
        <xs:element name="Title" type="xs:string" minOccurs="0"/>
        <xs:choice>
            <xs:element name="PhoneNo" type="xs:string" minOccurs="0"/>
            <xs:element name="MobileNo" type="xs:string" minOccurs="0"/>
            <xs:element name="FaxNo" type="xs:string" minOccurs="0"/>
            <xs:element name="EmailAddress" type="xs:string" minOccurs="0"/>
        </xs:choice>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="Project">
    <xs:sequence>
        <xs:element name="ProjectNo" type="xs:string"/>
        <xs:element name="ProjectName" type="xs:string"/>
        <xs:element name="ProjectLocation" type="xs:string"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="Item">
    <xs:annotation>
        <xs:documentation>Item Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
        <xs:element name="ItemNo" type="xs:string" minOccurs="0"/>
        <xs:element name="ItemName" type="xs:string"/>
        <xs:element name="ItemNameForeign" type="xs:string" minOccurs="0"/>
    </xs:sequence>
</xs:complexType>

```

```


<xs:element name="ItemCode" type="xs:string" minOccurs="0"/>
<xs:element name="ItemUnit" type="xs:string" minOccurs="0"/>
<xs:element name="ItemUnitForeign" type="xs:string" minOccurs="0"/>
<xs:element name="IndustrySpec">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="IndustryName" type="xs:string" minOccurs="0"/>
      <xs:element name="IndustryID" type="xs:string"/>
      <xs:element name="Spec" maxOccurs="unbounded">
        <xs:complexType>
          <xs:sequence>
            <xs:element name="SpecName" type="xs:string"/>
            <xs:element name="SpecUnit" type="xs:string"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="Remark" type="xs:string" minOccurs="0"/>
</xs:sequence>
</xs:complexType>
<xs:complexType name="UnitPrice">
  <xs:annotation>
    <xs:documentation>UnitPrice Common Element</xs:documentation>
  </xs:annotation>
  <xs:sequence>
    <xs:element name="Amount" type="xs:float"/>
    <xs:element name="Currency" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="ItemAmount">
  <xs:annotation>
    <xs:documentation>UnitPrice and ItemAmount Common Element</xs:documentation>
  </xs:annotation>
  <xs:sequence>
    <xs:element name="Amount" type="xs:float"/>
    <xs:element name="Currency" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="TotalAmount">
  <xs:annotation>
    <xs:documentation>totalAmount Common Element</xs:documentation>
  </xs:annotation>
  <xs:sequence>
    <xs:element name="TotalAmountBeforeTax" type="xs:float"/>
    <xs:element name="Currency" type="xs:string"/>
    <xs:element name="TaxType" type="xs:string" minOccurs="0"/>
    <xs:element name="TaxPercentage" type="xs:float" minOccurs="0"/>
    <xs:element name="TaxAmount" type="xs:float" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="Payment">
  <xs:annotation>
    <xs:documentation>Payment Common Element</xs:documentation>
  </xs:annotation>
  <xs:sequence>
    <xs:element name="PaymentName" type="xs:string"/>
    <xs:element name="PaymentType">

```

```

<xs:complexType>
  <xs:choice>
    <xs:element name="Cash">
      <xs:complexType>
        <xs:choice>
          <xs:element name="Percentage" type="xs:float" minOccurs="0"/>
          <xs:element name="Amount" type="xs:float" minOccurs="0"/>
          <xs:element name="Currency" type="xs:string" minOccurs="0"/>
        </xs:choice>
      </xs:complexType>
    </xs:element>
    <xs:element name="Check">
      <xs:complexType>
        <xs:sequence>
          <xs:element name="DuePeriod" type="xs:positiveInteger" minOccurs="0"/>
          <xs:element name="DueType" type="xs:string" minOccurs="0"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element name="Transferring">
      <xs:complexType>
        <xs:sequence>
          <xs:element name="BankNo" type="xs:string" minOccurs="0"/>
          <xs:element name="BankAccount" type="xs:string" minOccurs="0"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
  </xs:choice>
</xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:schema>

```



## Schema P-9 追加減明細表

```
<?xml version="1.0" encoding="UTF-8"?>
<!-- edited with XMLSPY v2004 rel. 4 U (http://www.xmlspy.com) by orion (ORiON) -->
<!-- edited with XML Spy v4.4 U (http://www.xmlspy.com) by http://soft163.com (http://soft163.com) -->
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema" elementFormDefault="qualified"
attributeFormDefault="unqualified">
  <xs:element name="AdjustmentDetail">
    <xs:annotation>
      <xs:documentation>P-10</xs:documentation>
    </xs:annotation>
    <xs:complexType>
      <xs:sequence>
        <xs:element name="SheetTitle" type="SheetTitle"/>
        <xs:element name="Contract" type="Contract" minOccurs="0"/>
        <xs:element name="Project" type="Project"/>
        <xs:element name="Date" type="xs:date" minOccurs="0"/>
        <xs:element name="Buyer" type="Buyer"/>
        <xs:element name="Supplier" type="Supplier"/>
        <xs:element name="Item" type="Item" maxOccurs="unbounded"/>
        <xs:element name="AdjustmentTotalAmount">
          <xs:complexType>
            <xs:sequence>
              <xs:element name="TotalAmount" type="TotalAmount"/>
            </xs:sequence>
          </xs:complexType>
        </xs:element>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:complexType name="Contract">
    <xs:sequence>
      <xs:element name="ContractName" type="xs:string"/>
      <xs:element name="ContractNumber" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="Buyer">
    <xs:sequence>
      <xs:element name="ComName" type="xs:string"/>
      <xs:element name="ComNumber" type="xs:string" minOccurs="0"/>
      <xs:element name="Contact" type="Contact"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="Supplier">
    <xs:sequence>
      <xs:element name="ComName" type="xs:string"/>
      <xs:element name="ComNumber" type="xs:string" minOccurs="0"/>
      <xs:element name="Contact" type="Contact"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="SheetTitle">
    <xs:annotation>
      <xs:documentation>SheetTitle Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
      <xs:element name="SheetName" type="xs:string" minOccurs="0"/>
      <xs:element name="SheetID" type="xs:string" minOccurs="0"/>
      <xs:element name="ApplicationProccesNo" type="xs:string" minOccurs="0"/>
    </xs:sequence>
  </xs:complexType>

```



```

        <xs:element name="SheetDate" type="xs:date" minOccurs="0"/>
        <xs:element name="SchemaVersion" type="xs:string" minOccurs="0"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="Contact">
    <xs:annotation>
        <xs:documentation>Contact Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
        <xs:element name="Name" type="xs:string"/>
        <xs:element name="Title" type="xs:string" minOccurs="0"/>
        <xs:choice>
            <xs:element name="PhoneNo" type="xs:string" minOccurs="0"/>
            <xs:element name="MobileNo" type="xs:string" minOccurs="0"/>
            <xs:element name="FaxNo" type="xs:string" minOccurs="0"/>
            <xs:element name="EmailAddress" type="xs:string" minOccurs="0"/>
        </xs:choice>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="Project">
    <xs:sequence>
        <xs:element name="ProjectNo" type="xs:string" minOccurs="0"/>
        <xs:element name="ProjectName" type="xs:string"/>
        <xs:element name="ProjectLocation" type="xs:string" minOccurs="0"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="Item">
    <xs:annotation>
        <xs:documentation>Item Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
        <xs:element name="ItemNo" type="xs:string" minOccurs="0"/>
        <xs:element name="ItemName" type="xs:string"/>
        <xs:element name="ItemNameForeign" type="xs:string" minOccurs="0"/>
        <xs:element name="ItemCode" type="xs:string" minOccurs="0"/>
        <xs:element name="ItemUnit" type="xs:string" minOccurs="0"/>
        <xs:element name="ItemUnitForeign" type="xs:string" minOccurs="0"/>
        <xs:element name="IndustrySpec">
            <xs:complexType>
                <xs:sequence>
                    <xs:element name="IndustryName" type="xs:string" minOccurs="0"/>
                    <xs:element name="IndustryID" type="xs:string"/>
                    <xs:element name="Spec" maxOccurs="unbounded">
                        <xs:complexType>
                            <xs:sequence>
                                <xs:element name="SpecName" type="xs:string"/>
                                <xs:element name="SpecUnit" type="xs:string"/>
                            </xs:sequence>
                        </xs:complexType>
                    </xs:element>
                </xs:sequence>
            </xs:complexType>
        </xs:element>
        <xs:element name="Remark" type="xs:string" minOccurs="0"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="TotalAmount">
    <xs:annotation>
        <xs:documentation>totalAmount Common Element</xs:documentation>
    </xs:annotation>

```

```
</xs:annotation>
<xs:sequence>
  <xs:element name="TotalAmountBeforeTax" type="xs:float"/>
  <xs:element name="Currency" type="xs:string"/>
  <xs:element name="TaxType" type="xs:string" minOccurs="0"/>
  <xs:element name="TaxPercentage" type="xs:float" minOccurs="0"/>
  <xs:element name="TaxAmount" type="xs:float" minOccurs="0"/>
</xs:sequence>
</xs:complexType>
</xs:schema>
```



## Schema P-10 物料驗收單

```
<?xml version="1.0" encoding="UTF-8"?>
<!-- edited with XML Spy v4.4 U (http://www.xmlspy.com) by http://soft163.com (http://soft163.com) -->
<!-- edited with XMLSPY v2004 rel. 4 U (http://www.xmlspy.com) by orion (ORiON) -->
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema" elementFormDefault="qualified"
attributeFormDefault="unqualified">
  <xs:element name="MaterialReceipt">
    <xs:annotation>
      <xs:documentation>P-11</xs:documentation>
    </xs:annotation>
    <xs:complexType>
      <xs:sequence>
        <xs:element name="SheetTitle" type="SheetTitle" minOccurs="0"/>
        <xs:element name="ReceiptNumber" type="xs:string" minOccurs="0"/>
        <xs:element name="OrderNumber" type="xs:string" minOccurs="0"/>
        <xs:element name="DeliveryNumber" type="xs:string" minOccurs="0"/>
        <xs:element name="Supplier" type="Supplier"/>
        <xs:element name="Contract" type="Contract" minOccurs="0"/>
        <xs:element name="Project" type="Project"/>
        <xs:element name="InspectorContact" type="Contact"/>
        <xs:element name="Signature" type="Signature" minOccurs="0"/>
        <xs:element name="Comment" type="xs:string" minOccurs="0"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:complexType name="Supplier">
    <xs:sequence>
      <xs:element name="ComName"/>
      <xs:element name="Contact">
        <xs:complexType>
          <xs:sequence>
            <xs:element name="Name" type="xs:string"/>
            <xs:element name="Title" type="xs:string" minOccurs="0"/>
            <xs:choice>
              <xs:element name="PhoneNo" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
              <xs:element name="MobileNo" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
              <xs:element name="FaxNo" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
              <xs:element name="EmailAddress" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
            </xs:choice>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="Contract">
    <xs:sequence>
      <xs:element name="ContractName" type="xs:string" minOccurs="0"/>
      <xs:element name="ContractNumber" type="xs:string" minOccurs="0"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="Signature">
    <xs:sequence>
      <xs:element name="Item" type="Item" maxOccurs="unbounded"/>
      <xs:element name="Notes" type="xs:string" minOccurs="0"/>
      <xs:element name="IndustrySpec">
        <xs:complexType>
          <xs:sequence/>
        </xs:complexType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:schema>
```

```

        </xs:complexType>
    </xs:element>
</xs:sequence>
</xs:complexType>
<xs:complexType name="SheetTitle">
    <xs:annotation>
        <xs:documentation>SheetTitle Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
        <xs:element name="SheetName" type="xs:string" minOccurs="0"/>
        <xs:element name="SheetID" type="xs:string" minOccurs="0"/>
        <xs:element name="ApplicationProccesNo" type="xs:string" minOccurs="0"/>
        <xs:element name="SheetDate" type="xs:date" minOccurs="0"/>
        <xs:element name="SchemaVersion" type="xs:string" minOccurs="0"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="Contact">
    <xs:annotation>
        <xs:documentation>Contact Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
        <xs:element name="Name" type="xs:string"/>
        <xs:element name="Title" type="xs:string" minOccurs="0"/>
        <xs:choice>
            <xs:element name="PhoneNo" type="xs:string" minOccurs="0"/>
            <xs:element name="MobileNo" type="xs:string" minOccurs="0"/>
            <xs:element name="FaxNo" type="xs:string" minOccurs="0"/>
            <xs:element name="EmailAddress" type="xs:string" minOccurs="0"/>
        </xs:choice>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="Item">
    <xs:annotation>
        <xs:documentation>Item Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
        <xs:element name="ItemNo" type="xs:string" minOccurs="0"/>
        <xs:element name="ItemName" type="xs:string"/>
        <xs:element name="ItemNameForeign" type="xs:string" minOccurs="0"/>
        <xs:element name="ItemCode" type="xs:string" minOccurs="0"/>
        <xs:element name="ItemUnit" type="xs:string" minOccurs="0"/>
        <xs:element name="ItemUnitForeign" type="xs:string" minOccurs="0"/>
        <xs:element name="IndustrySpec">
            <xs:complexType>
                <xs:sequence>
                    <xs:element name="IndustryName" type="xs:string" minOccurs="0"/>
                    <xs:element name="IndustryID" type="xs:string"/>
                    <xs:element name="Spec" maxOccurs="unbounded">
                        <xs:complexType>
                            <xs:sequence>
                                <xs:element name="SpecName" type="xs:string"/>
                                <xs:element name="SpecUnit" type="xs:string"/>
                            </xs:sequence>
                        </xs:complexType>
                    </xs:element>
                </xs:sequence>
            </xs:complexType>
        </xs:element>
    </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="Remark" type="xs:string" minOccurs="0"/>

```

```
</xs:sequence>
</xs:complexType>
<xs:complexType name="Project">
  <xs:sequence>
    <xs:element name="ProjectNo" type="xs:string"/>
    <xs:element name="ProjectName" type="xs:string"/>
    <xs:element name="ProjectLocation" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
</xs:schema>
```



## Schema P-11 計價申請單/估驗計價單

```
<?xml version="1.0" encoding="UTF-8"?>
<!-- edited with XMLSPY v2004 rel. 4 U (http://www.xmlspy.com) by orion (ORiON) -->
<!-- edited with XML Spy v4.4 U (http://www.xmlspy.com) by http://soft163.com (http://soft163.com) -->
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema" elementFormDefault="qualified"
attributeFormDefault="unqualified">
  <xs:element name="PaymentApplication">
    <xs:annotation>
      <xs:documentation>P-12</xs:documentation>
    </xs:annotation>
    <xs:complexType>
      <xs:sequence>
        <xs:element name="SheetTitle" type="SheetTitle"/>
        <xs:element name="PaymentNumber" type="xs:string" minOccurs="0"/>
        <xs:element name="PrintDate" type="xs:date" minOccurs="0"/>
        <xs:element name="ReceiptNumber" type="xs:string" minOccurs="0"/>
        <xs:element name="Site" type="Site"/>
        <xs:element name="Supplier" type="Supplier"/>
        <xs:element name="Contract" type="Contract"/>
        <xs:element name="Project" type="Project"/>
        <xs:element name="Valuation" type="Valuation"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:complexType name="Site">
    <xs:sequence>
      <xs:element name="SiteName"/>
      <xs:element name="ComTaxNumber" type="xs:string"/>
      <xs:element name="Contact" type="Contact"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="Supplier">
    <xs:sequence>
      <xs:element name="SupplierName" type="xs:string"/>
      <xs:element name="ComTaxNumber" type="xs:string" minOccurs="0"/>
      <xs:element name="Contact" type="Contact"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="Contract">
    <xs:sequence>
      <xs:element name="ContractName" type="xs:string" minOccurs="0"/>
      <xs:element name="ContractNumber" type="xs:string" minOccurs="0"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="Project">
    <xs:sequence>
      <xs:element name="ProjectNo" type="xs:string" minOccurs="0"/>
      <xs:element name="ProjectName" type="xs:string"/>
      <xs:element name="ProjectLocation" type="xs:string" minOccurs="0"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="Valuation">
    <xs:annotation>
      <xs:documentation>Differ from Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
      <xs:element name="Month" type="xs:string" minOccurs="0"/>
    </xs:sequence>
  </xs:complexType>

```

```

<xs:element name="Period" type="xs:string" minOccurs="0"/>
<xs:element name="Date" type="xs:date" minOccurs="0"/>
<xs:element name="AccPeriod" type="xs:string" minOccurs="0"/>
<xs:element name="TotPrice" type="xs:float"/>
<xs:element name="Invoice" maxOccurs="unbounded">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="InvoiceNumber" type="xs:string" minOccurs="0"/>
      <xs:element name="InvoiceDate" type="xs:date" minOccurs="0"/>
      <xs:element name="WeightListNo" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
      <xs:element name="RevenuePayment" type="xs:float" minOccurs="0"/>
      <xs:element name="DepositPayment" type="xs:float" minOccurs="0"/>
      <xs:element name="InvoicePrice" type="TotalAmount" minOccurs="0"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
<xs:complexType name="SheetTitle">
  <xs:annotation>
    <xs:documentation>SheetTitle Common Element</xs:documentation>
  </xs:annotation>
  <xs:sequence>
    <xs:element name="SheetName" type="xs:string" minOccurs="0"/>
    <xs:element name="SheetID" type="xs:string" minOccurs="0"/>
    <xs:element name="ApplicationProccesNo" type="xs:string" minOccurs="0"/>
    <xs:element name="SheetDate" type="xs:date" minOccurs="0"/>
    <xs:element name="SchemaVersion" type="xs:string" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="Contact">
  <xs:annotation>
    <xs:documentation>Contact Common Element</xs:documentation>
  </xs:annotation>
  <xs:sequence>
    <xs:element name="Name" type="xs:string"/>
    <xs:element name="Title" type="xs:string" minOccurs="0"/>
    <xs:choice>
      <xs:element name="PhoneNo" type="xs:string" minOccurs="0"/>
      <xs:element name="MobileNo" type="xs:string" minOccurs="0"/>
      <xs:element name="FaxNo" type="xs:string" minOccurs="0"/>
      <xs:element name="EmailAddress" type="xs:string" minOccurs="0"/>
    </xs:choice>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="TotalAmount">
  <xs:annotation>
    <xs:documentation>totalAmount Common Element</xs:documentation>
  </xs:annotation>
  <xs:sequence>
    <xs:element name="TotalAmountBeforeTax" type="xs:float"/>
    <xs:element name="Currency" type="xs:string"/>
    <xs:element name="TaxType" type="xs:string" minOccurs="0"/>
    <xs:element name="TaxPercentage" type="xs:float" minOccurs="0"/>
    <xs:element name="TaxAmount" type="xs:float" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>
</xs:schema>

```

## Schema P-12 領款通知單

```
<?xml version="1.0" encoding="UTF-8"?>
<!-- edited with XMLSPY v2004 rel. 4 U (http://www.xmlspy.com) by orion (ORiON) -->
<!-- edited with XML Spy v4.4 U (http://www.xmlspy.com) by http://soft163.com (http://soft163.com) -->
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema" elementFormDefault="qualified"
attributeFormDefault="unqualified">
  <xs:element name="PaymentNote">
    <xs:annotation>
      <xs:documentation>P-13</xs:documentation>
    </xs:annotation>
    <xs:complexType>
      <xs:sequence>
        <xs:element name="SheetTitle" type="SheetTitle" minOccurs="0"/>
        <xs:element name="NoteNumber" type="xs:string" minOccurs="0"/>
        <xs:element name="PaymentNoteNumber" type="xs:string" minOccurs="0"/>
        <xs:element name="InvoiceNumber" type="xs:string" minOccurs="0"/>
        <xs:element name="PaymentApplicationNumber" type="xs:string" minOccurs="0"/>
        <xs:element name="Contract" type="Contract" minOccurs="0"/>
        <xs:element name="Project" type="Project"/>
        <xs:element name="Site" type="Site"/>
        <xs:element name="Supplier" type="Supplier"/>
        <xs:element name="Payment" type="Payment" minOccurs="0"/>
        <xs:element name="Remark" type="xs:string" minOccurs="0"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:complexType name="Contract">
    <xs:sequence>
      <xs:element name="ContractName" type="xs:string"/>
      <xs:element name="ContractNumber" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="Project">
    <xs:sequence>
      <xs:element name="ProjectNo" type="xs:string"/>
      <xs:element name="ProjectName" type="xs:string"/>
      <xs:element name="ProjectLocation" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="Site">
    <xs:sequence>
      <xs:element name="SiteName" type="xs:string"/>
      <xs:element name="ComTaxNumber" type="xs:string" minOccurs="0"/>
      <xs:element name="Contact" type="Contact"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="Contact">
    <xs:sequence>
      <xs:element name="Name" type="xs:string"/>
      <xs:element name="Title" type="xs:string" minOccurs="0"/>
      <xs:choice>
        <xs:element name="PhoneNo" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
        <xs:element name="MobileNo" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
        <xs:element name="FaxNo" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
        <xs:element name="EmailAddress" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
      </xs:choice>
    </xs:sequence>
  </xs:complexType>
</xs:schema>
```



```

</xs:complexType>
<xs:complexType name="Supplier">
  <xs:sequence>
    <xs:element name="SupplierName" type="xs:string"/>
    <xs:element name="ComTaxNumber" type="xs:string" minOccurs="0"/>
    <xs:element name="Contact" type="Contact"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="SheetTitle">
  <xs:annotation>
    <xs:documentation>SheetTitle Common Element</xs:documentation>
  </xs:annotation>
  <xs:sequence>
    <xs:element name="SheetName" type="xs:string" minOccurs="0"/>
    <xs:element name="SheetID" type="xs:string" minOccurs="0"/>
    <xs:element name="ApplicationProccesNo" type="xs:string" minOccurs="0"/>
    <xs:element name="SheetDate" type="xs:date" minOccurs="0"/>
    <xs:element name="SchemaVersion" type="xs:string" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="Payment">
  <xs:annotation>
    <xs:documentation>Payment Common Element</xs:documentation>
  </xs:annotation>
  <xs:sequence>
    <xs:element name="PaymentName" type="xs:string"/>
    <xs:element name="PaymentType">
      <xs:complexType>
        <xs:choice>
          <xs:element name="Cash">
            <xs:complexType>
              <xs:choice>
                <xs:element name="Percentage" type="xs:float" minOccurs="0"/>
                <xs:element name="Amount" type="xs:float" minOccurs="0"/>
                <xs:element name="Currency" type="xs:string" minOccurs="0"/>
              </xs:choice>
            </xs:complexType>
          </xs:element>
          <xs:element name="Check">
            <xs:complexType>
              <xs:sequence>
                <xs:element name="DuePeriod" type="xs:positiveInteger" minOccurs="0"/>
                <xs:element name="DueType" type="xs:string" minOccurs="0"/>
              </xs:sequence>
            </xs:complexType>
          </xs:element>
          <xs:element name="Transferring">
            <xs:complexType>
              <xs:sequence>
                <xs:element name="BankNo" type="xs:string" minOccurs="0"/>
                <xs:element name="BankAccount" type="xs:string" minOccurs="0"/>
              </xs:sequence>
            </xs:complexType>
          </xs:element>
        </xs:choice>
      </xs:complexType>
    </xs:element>
  </xs:sequence>
</xs:complexType>

```

</xs:schema>



## Schema P-13 施工日報表

```
<?xml version="1.0" encoding="UTF-8" standalone="no"?>
<!-- edited with XMLSPY v2004 rel. 2 U (http://www.xmlspy.com) by A3 (GG) -->
<xsd:schema targetNamespace="http://pcstd.pcc.gov.tw/2003/G2Bproject" xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns="http://pcstd.pcc.gov.tw/2003/G2Bproject" xmlns:et="http://pcstd.pcc.gov.tw/2003/G2B"
xmlns:mml="http://www.w3.org/1998/Math/MathML" elementFormDefault="qualified" version="v0.1" id="BasicInformation">
  <!--G2B日報表-->
  <xsd:import namespace="http://www.w3.org/1998/Math/MathML" schemaLocation="mathml2.xsd"/>
  <xsd:import namespace="http://pcstd.pcc.gov.tw/2003/G2B" schemaLocation="common-types.xsd"/>
  <xsd:include schemaLocation="ProjectInformation.xsd"/>
  <xsd:include schemaLocation="WorkItem.xsd"/>
  <xsd:include schemaLocation="ActivityItem.xsd"/>
  <xsd:include schemaLocation="Rechecker.xsd"/>
  <!--根元素宣告 -->
  <xsd:element name="DailyReport">
    <xsd:complexType>
      <xsd:complexContent>
        <xsd:extension base="DailyReportType">
          <xsd:attribute name="documentType" use="required">
            <xsd:simpleType>
              <xsd:restriction base="xsd:string">
                <xsd:enumeration value="日進度表"/>
                <xsd:enumeration value="施工日報表"/>
                <xsd:enumeration value="監工日報表"/>
              </xsd:restriction>
            </xsd:simpleType>
          </xsd:attribute>
        </xsd:extension>
      </xsd:complexContent>
    </xsd:complexType>
  </xsd:element>
  <!--複雜型別宣告-->
  <!--定義DailyReportType資料型態-->
  <xsd:complexType name="DailyReportType">
    <xsd:sequence>
      <xsd:element ref="ProjectInformation"/>
      <xsd:element name="DailyData" type="DailyDataType"/>
      <xsd:element name="LabourUsage" type="ResourceType" maxOccurs="unbounded"/>
      <xsd:element name="EquipmentUsage" type="ResourceType" maxOccurs="unbounded"/>
      <xsd:element name="MaterialUsage" type="MaterialUsageType" maxOccurs="unbounded"/>
      <xsd:element name="ImportantEventJobsite" type="et:string_200" maxOccurs="unbounded"/>
      <xsd:element name="SpecialEventJobsite" type="et:string_200" minOccurs="0" maxOccurs="unbounded"/>
      <xsd:element name="TestingSample" type="TestingSampleType" minOccurs="0" maxOccurs="unbounded"/>
      <xsd:element name="SafetyInspect" type="SafetyInspectType" minOccurs="0"/>
      <xsd:element ref="InstructionLog" minOccurs="0"/>
      <xsd:element ref="WorkItem" minOccurs="0" maxOccurs="unbounded"/>
      <xsd:element ref="ActivityItem" minOccurs="0" maxOccurs="unbounded"/>
      <xsd:element name="Attachment" type="AttachmentType" minOccurs="0" maxOccurs="unbounded"/>
      <xsd:element ref="Rechecker" maxOccurs="unbounded"/>
      <!-- ProjectInformation 計畫基本資料-->
      <!--DailyData施工天候、進度及工作天計算基本資料 -->
      <!-- LabourUsage人工出工數統計資料 -->
      <!--EquipmentUsage機具出動統計資料 -->
      <!-- MaterialUsage材料使用統計資料 -->
      <!--ImportantEventJobsite本日施工情形及重要工作記載-->
      <!--SpecialEventJobsite異常狀況記載如停復工及工程停滯-->
      <!-- TestingSample材料取樣及試驗情形 -->
    </xsd:sequence>
  </xsd:complexType>
</xsd:schema>
```

```

        <!-- SafetyInspect勞工安全查核事項 -->
        <!--InstructionLog各級長官指導、指示事項 -->
        <!--WorkItem契約工項完成數量統計 -->
        <!--ActivityItem作業項目進度資料 -->
        <!-- Attachment附件 -->
        <!--Rechecker審核人員，包括單位、職稱、姓名-->
    </xsd:sequence>
</xsd:complexType>
<!--定義日報基本資料DailyDataType資料型態-->
<xsd:complexType name="DailyDataType">
    <xsd:sequence>
        <xsd:element name="CreateDate" type="xsd:date"/>
        <xsd:element name="WeatherCondition" maxOccurs="2">
            <xsd:complexType>
                <xsd:simpleContent>
                    <xsd:extension base="WeatherConditionType">
                        <xsd:attribute name="am_pm" use="optional">
                            <xsd:simpleType>
                                <xsd:restriction base="xsd:string">
                                    <xsd:enumeration value="am"/>
                                    <xsd:enumeration value="pm"/>
                                    <xsd:enumeration value="allDay"/>
                                </xsd:restriction>
                            </xsd:simpleType>
                        </xsd:attribute>
                    </xsd:extension>
                </xsd:simpleContent>
            </xsd:complexType>
        </xsd:element>
        <xsd:element name="DurationList" type="DurationListType"/>
        <xsd:element name="ProgressList" type="ProgressListType" minOccurs="0"/>
        <!-- 填報日期-->
        <!-- 天氣狀況，內含am_pm屬性區分為上、下午or 全天天氣記載-->
        <!-- DurationList已進行工作天數 計算-->
        <!-- ProgressList進度資料 -->
    </xsd:sequence>
</xsd:complexType>
<xsd:simpleType name="WeatherConditionType">
    <xsd:restriction base="xsd:string">
        <xsd:enumeration value="晴"/>
        <xsd:enumeration value="陰"/>
        <xsd:enumeration value="雨"/>
        <xsd:enumeration value="颱風"/>
    </xsd:restriction>
</xsd:simpleType>
<!--定義進度Progress資料型態-->
<xsd:complexType name="ProgressListType">
    <xsd:sequence>
        <xsd:element name="ScheduleProgress" type="ProgressType"/>
        <xsd:element name="CertificatePaymentProgress" type="ProgressType"/>
        <xsd:element name="ActualProgress" type="ProgressType"/>
        <xsd:element name="CriticalPathProgress" type="ProgressType" minOccurs="0"/>
        <!-- ScheduleProgress預定進度-->
        <!-- CertificatePaymentProgress估驗進度-->
        <!-- ActualProgress實作數量進度-->
        <!-- CriticalPathProgress要徑進度，已完成要徑作業項目工作天數/預定工作天數-->
    </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="ProgressType">

```

```

<xsd:simpleContent>
  <xsd:extension base="et:decimal_10_2">
    <xsd:attribute name="unit" type="et:string_20" use="required"/>
  </xsd:extension>
</xsd:simpleContent>
</xsd:complexType>
<!--定義工作天資料型態-->
<xsd:complexType name="DurationListType">
  <xsd:sequence>
    <xsd:element name="WorkDay" type="WorkDay.Type" minOccurs="0"/>
    <xsd:element name="ScheduledDuration" type="et:DurationType"/>
    <xsd:element name="CompletedDuration" type="et:DurationType"/>
    <xsd:element name="RemainDuration" type="et:DurationType" minOccurs="0"/>
    <xsd:element name="DurationtoComplete" type="et:DurationType" minOccurs="0"/>
    <!-- WorkDay當日計入工作天數，ex 1 /0.5 /0-->
    <!-- ScheduledDuration預計工作天-->
    <!-- CompletedDuration 已完成工作天-->
    <!-- RemainDuration剩餘工作天= 預計工作天 - 已完成工作天-->
    <!-- DurationtoComplete殘餘要徑工期-->
  </xsd:sequence>
</xsd:complexType>
<xsd:simpleType name="WorkDay.Type">
  <xsd:restriction base="xsd:decimal">
    <xsd:totalDigits value="2"/>
    <xsd:fractionDigits value="1"/>
    <xsd:minInclusive value="0"/>
    <xsd:maxInclusive value="1"/>
  </xsd:restriction>
</xsd:simpleType>
<!--定義ResourceListType(人機出工使用狀況)資料型態-->
<xsd:element name="LabourUsage" type="ResourceType"/>
<xsd:element name="EquipmentUsage" type="ResourceType"/>
<xsd:complexType name="ResourceType">
  <xsd:sequence>
    <xsd:element name="Item" type="et:description.type" maxOccurs="2"/>
    <xsd:element name="DailyNumber" type="et:decimal_20_4"/>
    <xsd:element name="DailyHour" type="et:decimal_20_4"/>
    <xsd:element name="AccumulatedNumber" type="et:decimal_20_4"/>
    <xsd:element name="AccumulatedHour" type="et:decimal_20_4"/>
    <xsd:element name="WorkPlace" type="et:string_60" minOccurs="0"/>
    <xsd:element ref="mml:math" minOccurs="0"/>
    <!-- Item資源項目-->
    <!-- DailyNumber本日數量-->
    <!-- DailyHour本日時數-->
    <!-- AccumulatedNumber累計數量-->
    <!-- AccumulatedHour累計時數-->
    <!-- WorkPlace施作地點-->
    <!-- mml:math計算公式-->
  </xsd:sequence>
  <xsd:attribute name="itemKey" type="et:string_20" use="optional"/>
  <xsd:attribute name="itemNo" type="et:string_20" use="optional"/>
  <xsd:attribute name="refItemCode" type="et:string_20" use="optional"/>
  <xsd:attribute name="itemKind" type="itemKind.type" use="optional"/>
</xsd:complexType>
<!--定義MaterialUsageType(材料使用情形)資料型態-->
<xsd:complexType name="MaterialUsageType">
  <xsd:sequence>
    <xsd:element name="Item" maxOccurs="2">
      <xsd:complexType>

```

```

        <xsd:simpleContent>
            <xsd:extension base="et:description.type">
                <xsd:attribute name="bureaSupply" type="et:YesNoOptionalType" use="optional" default="N"/>
            </xsd:extension>
        </xsd:simpleContent>
    </xsd:complexType>
</xsd:element>
<xsd:element name="EstimatedQuantity" type="et:decimal_20_4"/>
<xsd:element name="QuantityMaterialImportToday" type="et:decimal_20_4"/>
<xsd:element name="AccumulatedQuantityMaterialImport" type="et:decimal_20_4"/>
<xsd:element name="QuantityMaterialUsageToday" type="et:decimal_20_4"/>
<xsd:element name="AccumulatedQuantityMaterialUsage" type="et:decimal_20_4"/>
<xsd:element name="WorkPlace" type="et:string_60" minOccurs="0"/>
<xsd:element ref="mml:math" minOccurs="0"/>
<!-- Item 材料項目，內含bureaSupply屬性記載是否為局供材料-->
<!-- EstimatedQuantity預算數量-->
<!-- QuantityMaterialImportToday本日材料進場數量-->
<!-- AccumulatedQuantityMaterialImport累計材料進場數量-->
<!-- QuantityMaterialUsageToday本日材料使用數量-->
<!-- AccumulatedQuantityMaterialUsage累計材料使用數量-->
<!-- WorkPlace施作地點-->
<!-- mml:math計算公式-->
</xsd:sequence>
<xsd:attribute name="itemKey" type="et:string_20" use="optional"/>
<xsd:attribute name="itemNo" type="et:string_20" use="optional"/>
<xsd:attribute name="refItemCode" type="et:string_20" use="optional"/>
<xsd:attribute name="itemKind" type="itemKind.type" use="optional"/>
</xsd:complexType>
<!-- 定義TestingSampleType(材料取樣及試驗情形)資料型態-->
<xsd:complexType name="TestingSampleType">
    <xsd:sequence>
        <xsd:element name="SamplingItem" type="et:description.type"/>
        <xsd:element name="SamplingQuantity" type="et:decimal_20_4"/>
        <xsd:element name="DesignStrength">
            <xsd:complexType>
                <xsd:simpleContent>
                    <xsd:extension base="et:decimal_20_4">
                        <xsd:attribute name="unit" type="xsd:string" use="required"/>
                    </xsd:extension>
                </xsd:simpleContent>
            </xsd:complexType>
        </xsd:element>
        <xsd:element name="SamplingPosition" type="et:string_200"/>
        <xsd:element name="Remark" type="et:string_200"/>
        <!-- 取樣項目-->
        <!-- 代表數量-->
        <!-- 設計強度-->
        <!-- 取樣位置-->
        <!-- 備註 -->
    </xsd:sequence>
</xsd:complexType>
<!-- 定義勞工安全查核事項SafetyInspectType資料型態-->
<xsd:complexType name="SafetyInspectType">
    <xsd:sequence>
        <xsd:element name="Comment" type="et:string_200"/>
        <xsd:element name="DealWith" type="et:string_200"/>
        <!-- Comment檢查項目-->
        <!-- DealWith違反規定處理情形-->
    </xsd:sequence>
</xsd:complexType>

```

```

</xsd:complexType>
<!--定義InstructionLogType長官指示事項-->
<xsd:element name="InstructionLog" type="InstructionLog.type"/>
<xsd:complexType name="InstructionLog.type">
  <xsd:sequence>
    <xsd:element name="Entity" type="et:string_60"/>
    <xsd:element name="Title" type="et:string_40"/>
    <xsd:element name="Name" type="et:string_40"/>
    <xsd:element name="Instruction" type="et:string_200"/>
    <!-- Entity單位-->
    <!-- Title職稱 -->
    <!-- Name姓名 -->
    <!-- Instruction指導及指示事項 -->
  </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="AttachmentType">
  <xsd:sequence>
    <xsd:element name="DocumentName" type="et:string_200"/>
    <xsd:element name="FileName" type="et:string_200"/>
    <!-- DocumentName文件名稱-->
    <!-- FileName 檔案路徑及名稱-->
  </xsd:sequence>
</xsd:complexType>
</xsd:schema>

```



## 共同元素

```
<?xml version="1.0" encoding="UTF-8"?>
<!-- edited with XMLSPY v2004 rel. 4 U (http://www.xmlspy.com) by orion (ORiON) -->
<!-- edited with XML Spy v4.4 U (http://www.xmlspy.com) by http://soft163.com (http://soft163.com) -->
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema" elementFormDefault="qualified"
attributeFormDefault="unqualified">
  <xs:element name="CommonElement">
    <xs:annotation>
      <xs:documentation>Root Element</xs:documentation>
    </xs:annotation>
    <xs:complexType>
      <xs:sequence>
        <xs:element name="SheetTitle" type="SheetTitle"/>
        <xs:element name="Address" type="Address"/>
        <xs:element name="Contact" type="Contact"/>
        <xs:element name="Item" type="Item"/>
        <xs:element name="UnitPrice" type="UnitPrice"/>
        <xs:element name="ItemAmount" type="ItemAmount"/>
        <xs:element name="TotalAmount" type="TotalAmount"/>
        <xs:element name="Payment" type="Payment"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:complexType name="SheetTitle">
    <xs:annotation>
      <xs:documentation>SheetTitle Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
      <xs:element name="SheetName" type="xs:string" minOccurs="0"/>
      <xs:element name="SheetID" type="xs:string" minOccurs="0"/>
      <xs:element name="ApplicationProccesNo" type="xs:string" minOccurs="0"/>
      <xs:element name="SheetDate" type="xs:date" minOccurs="0"/>
      <xs:element name="SchemaVersion" type="xs:string" minOccurs="0"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="Address">
    <xs:annotation>
      <xs:documentation>Address Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
      <xs:element name="Postal" type="xs:string" minOccurs="0"/>
      <xs:element name="Area" type="xs:string" minOccurs="0"/>
      <xs:element name="City" type="xs:string" minOccurs="0"/>
      <xs:element name="Line1" type="xs:string" minOccurs="0"/>
      <xs:element name="ContactAddress" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="Contact">
    <xs:annotation>
      <xs:documentation>Contact Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
      <xs:element name="Name" type="xs:string"/>
      <xs:element name="Title" type="xs:string" minOccurs="0"/>
      <xs:choice>
        <xs:element name="PhoneNo" type="xs:string" minOccurs="0"/>
        <xs:element name="MobileNo" type="xs:string" minOccurs="0"/>
      </xs:choice>
    </xs:sequence>
  </xs:complexType>
</xs:schema>
```



```

        <xs:element name="FaxNo" type="xs:string" minOccurs="0"/>
        <xs:element name="EmailAddress" type="xs:string" minOccurs="0"/>
    </xs:choice>
</xs:sequence>
</xs:complexType>
<xs:complexType name="Item">
    <xs:annotation>
        <xs:documentation>Item Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
        <xs:element name="ItemNo" type="xs:string" minOccurs="0"/>
        <xs:element name="ItemName" type="xs:string"/>
        <xs:element name="ItemNameForeign" type="xs:string" minOccurs="0"/>
        <xs:element name="ItemCode" type="xs:string" minOccurs="0"/>
        <xs:element name="ItemUnit" type="xs:string" minOccurs="0"/>
        <xs:element name="ItemUnitForeign" type="xs:string" minOccurs="0"/>
        <xs:element name="IndustrySpec">
            <xs:complexType>
                <xs:sequence>
                    <xs:element name="IndustryName" type="xs:string" minOccurs="0"/>
                    <xs:element name="IndustryID" type="xs:string"/>
                    <xs:element name="Spec" maxOccurs="unbounded">
                        <xs:complexType>
                            <xs:sequence>
                                <xs:element name="SpecName" type="xs:string"/>
                                <xs:element name="SpecUnit" type="xs:string"/>
                            </xs:sequence>
                        </xs:complexType>
                    </xs:element>
                </xs:sequence>
            </xs:complexType>
        </xs:element>
        <xs:element name="Remark" type="xs:string" minOccurs="0"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="UnitPrice">
    <xs:annotation>
        <xs:documentation>UnitPrice Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
        <xs:element name="Amount" type="xs:float"/>
        <xs:element name="Currency" type="xs:string"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="ItemAmount">
    <xs:annotation>
        <xs:documentation>UnitPrice and ItemAmount Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
        <xs:element name="Amount" type="xs:float"/>
        <xs:element name="Currency" type="xs:string"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="TotalAmount">
    <xs:annotation>
        <xs:documentation>totalAmount Common Element</xs:documentation>
    </xs:annotation>
    <xs:sequence>
        <xs:element name="TotalAmountBeforeTax" type="xs:float"/>

```

```

    <xs:element name="Currency" type="xs:string"/>
    <xs:element name="TaxType" type="xs:string" minOccurs="0"/>
    <xs:element name="TaxPercentage" type="xs:float" minOccurs="0"/>
    <xs:element name="TaxAmount" type="xs:float" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="Payment">
  <xs:annotation>
    <xs:documentation>Payment Common Element</xs:documentation>
  </xs:annotation>
  <xs:sequence>
    <xs:element name="PaymentName" type="xs:string"/>
    <xs:element name="PaymentType">
      <xs:complexType>
        <xs:choice>
          <xs:element name="Cash">
            <xs:complexType>
              <xs:choice>
                <xs:element name="Percentage" type="xs:float" minOccurs="0"/>
                <xs:element name="Amount" type="xs:float" minOccurs="0"/>
                <xs:element name="Currency" type="xs:string" minOccurs="0"/>
              </xs:choice>
            </xs:complexType>
          </xs:element>
          <xs:element name="Check">
            <xs:complexType>
              <xs:sequence>
                <xs:element name="DuePeriod" type="xs:positiveInteger" minOccurs="0"/>
                <xs:element name="DueType" type="xs:string" minOccurs="0"/>
              </xs:sequence>
            </xs:complexType>
          </xs:element>
          <xs:element name="Transferring">
            <xs:complexType>
              <xs:sequence>
                <xs:element name="BankNo" type="xs:string" minOccurs="0"/>
                <xs:element name="BankAccount" type="xs:string" minOccurs="0"/>
              </xs:sequence>
            </xs:complexType>
          </xs:element>
        </xs:choice>
      </xs:complexType>
    </xs:element>
  </xs:sequence>
</xs:complexType>
</xs:schema>

```

## 附錄二 中華營建資訊標準協會驗證申請單填寫範本

申請驗證單位：交通大學土木系營建管理組	
申請負責人：王聖賢	聯絡電話：(03)571-2177
聯絡地址：新竹市大學路 1001 號	
E-Mail：polyaheng@yahoo.com.tw	
驗證系統名稱：電子採購文件系統	
<p>選取驗證文件：</p> <p> <input type="checkbox"/> 廠商登記審查表      <input checked="" type="checkbox"/> 詢價單      <input checked="" type="checkbox"/> 報價單  <input type="checkbox"/> 採購單      <input type="checkbox"/> 訂貨委送單      <input type="checkbox"/> 出貨料通知單  <input checked="" type="checkbox"/> 出貨單      <input type="checkbox"/> 退貨通知單      <input type="checkbox"/> 追加減明細表  <input checked="" type="checkbox"/> 物料驗收單      <input checked="" type="checkbox"/> 計價單      <input type="checkbox"/> 領款通知單         </p>	
<p>審查結果：</p> <p><b>審查通過，請於 95 年 7 月 14 日至中華營建資訊標準協會(交大工程一館 208 室)執行系統驗證</b></p>	
驗證單位負責人：王世旭	日期：95 年 7 月 7 日
備註：	

### 附錄三 中華營建資訊標準協會驗證報告書填寫範本

驗證結果： <input type="checkbox"/> 通過 <input checked="" type="checkbox"/> 不通過	報告書編號：No.00001
申請驗證單位：交大營管組	受驗單位代表：王聖賢
驗證日期：95年7月14日	驗證軟體名稱：電子採購系統
<p>驗證文件名稱：</p> <p> <input type="checkbox"/> 廠商登記審查表    <input checked="" type="checkbox"/> 詢價單    <input checked="" type="checkbox"/> 報價單  <input type="checkbox"/> 採購單    <input type="checkbox"/> 訂貨委送單    <input type="checkbox"/> 出貨料通知單  <input checked="" type="checkbox"/> 出貨單    <input type="checkbox"/> 退貨通知單    <input type="checkbox"/> 追加減明細表  <input checked="" type="checkbox"/> 物料驗收單    <input checked="" type="checkbox"/> 計價單    <input type="checkbox"/> 領款通知單         </p>	
<p>報告內容：</p> <p>壹、通過文件項目：</p> <p> <input type="checkbox"/> 廠商登記審查表    <input type="checkbox"/> 詢價單    <input type="checkbox"/> 報價單  <input type="checkbox"/> 採購單    <input type="checkbox"/> 訂貨委送單    <input type="checkbox"/> 出貨料通知單  <input checked="" type="checkbox"/> 出貨單    <input type="checkbox"/> 退貨通知單    <input type="checkbox"/> 追加減明細表  <input type="checkbox"/> 物料驗收單    <input checked="" type="checkbox"/> 計價單    <input type="checkbox"/> 領款通知單         </p> <p style="text-align: right;">合計共 <u>  2  </u> 項文件通過驗證</p> <p>貳、不通過事由：(文件名稱及錯誤描述欄位視情況增加)</p>	

1.  文件不符合 XML 文件規則

文件名稱：\_\_\_\_\_

錯誤描述：\_\_\_\_\_

2.  文件不符合 Schema 標準文件規定

(1)  缺乏必要元素

文件名稱：(1)詢價單、(2)報價單\_\_\_\_\_

錯誤描述：(1) 詢價單中缺少元素<InvitationDate>  
(2) 報價單中缺少元素<ComTaxNo>

(2)  必要元素名稱錯誤

文件名稱：詢價單\_\_\_\_\_

錯誤描述：將元素<DeliveryLocation>寫成  
<SendAddress>

(3)  非必要元素名稱錯誤

文件名稱：\_\_\_\_\_

錯誤描述：\_\_\_\_\_

(4)  必要元素資料型態錯誤

文件名稱：詢價單\_\_\_\_\_

錯誤描述：元素< InvitationDate>以 01/01/2006 形態表示，

非「Date」型態

(5)  非必要元素資料型態錯誤

文件名稱：\_\_\_\_\_

錯誤描述：\_\_\_\_\_

(6)  未定義元素資料型態錯誤

文件名稱：\_\_\_\_\_

錯誤描述：\_\_\_\_\_

(7)  必要元素出現次數錯誤

文件名稱：\_\_\_\_\_

錯誤描述：\_\_\_\_\_

(8)  非必要元素出現次數錯誤

文件名稱：\_\_\_\_\_

錯誤描述：\_\_\_\_\_

(9)  未定義元素出現次數錯誤

文件名稱：物料驗收單

錯誤描述：元素< ProjectStartDate>出現兩次

3.  受驗系統無法將測試文件近似呈現

合計共 3 項文件未通過驗證

驗證雙方代表簽名：王聖賢、王世旭

備註：