

CONTENTS

ABSTRACT.....	i
ACKNOWLEDGMENT.....	iv
CONTENTS.....	v
LIST OF TABLES.....	vii
LIST OF FIGURES.....	viii
Chapter 1 Introduction	1
Chapter 2 Chaos in Integral and Fractional Order Double Mackey-Glass Systems	5
2.1 Chaos in integral order double Mackey -Glass system	5
2.2 Definition and approximation of fractional order operator	6
2.3 The results of numerical simulations for fractional order systems	7
Chapter 3 Temporary Lag and Anticipated Synchronization and Anti-Synchronization of Uncoupled Double Mackey-Glass Systems	19
3.1 Temporary lag and anticipated synchronization and temporary lag and anticipated anti-synchronization of uncoupled time-delayed chaotic systems	19
3.2 The lag and anticipated synchronization of two identical double Mackey-Glass systems	20
3.3 The lag and anticipated anti-synchronization of two identical double Mackey-Glass systems	23
Chapter 4 Chaos Control and Synchronization of Double Mackey -Glass System by Noise Excitation of Parameters	30
4.1 Chaos control and synchronization for uncoupled double Mackey -Glass system by parameter excited method	30
4.2 Numerical simulations of chaos control	31
4.2.1 Gaussian noise	31
4.2.2 Rayleigh noise	32
4.2.3 Rician noise	32
4.2.4 Uniform noise	33
4.3 Numerical simulations of chaos synchronizations	33
4.3.1 Gaussian noise	34

4.3.2	Rayleigh noise	34
4.3.3	Rician noise	35
4.3.4	Uniform noise	36
Chapter 5	Robust Chaos Lag Synchronization of Double Mackey -Glass System by Noise Excitation of Parameters.....	46
5.1	Lag synchronization of double Mackey -Glass system by parameter excited method	46
5.2	Numerical simulation results of lag synchronizations	47
Chapter 6	Conclusions	57
References	59
Appendix	67



LIST OF TABLES

Table I	Relation between orders of derivatives and existence of chaos.	8
Table II	The length of temporary lag (anticipated) synchronization and the lag (lead) of x_1, x_2 to y_1, y_2 .	22
Table III	The lengths of the first time intervals of TLS and TAS where the initial values are varied from 0.00001 to 0.1 .	22
Table IV	The time histories of double Mackey -Glass system with negative initial values.	24



LIST OF FIGURES

Figure 2.1	The phase portraits and the bifurcation diagram for Double Mackey-Glass system with order $q_1 = 1$ and $q_2 = 1$, $\tau_2 = 20$.	9
Figure 2.2	The phase portraits and the bifurcation diagram for Double Mackey-Glass system with order $q_1 = 1$ and $q_2 = 1$.	10
Figure 2.3	The phase portraits and the bifurcation diagram for Double Mackey-Glass system with order $q_1 = 1$ and $q_2 = 1$, $b_2 = 0.2$, $r = 0.1$, $\tau_1 = \tau_2 = 20$.	11
Figure 2.4	The phase portraits and the bifurcation diagram for Double Mackey-Glass system with order $q_1 = 0.9$ and $q_2 = 0.9$, $\tau_2 = 20$.	12
Figure 2.5	The phase portraits and the bifurcation diagram for Double Mackey-Glass system with order $q_1 = 0.8$ and $q_2 = 0.8$, $\tau_2 = 20$.	13
Figure 2.6	The phase portraits and the bifurcation diagram for Double Mackey-Glass system with order $q_1 = 0.1$ and $q_2 = 0.1$, $\tau_2 = 20$.	14
Figure 2.7	The phase portraits and the bifurcation diagram for Double Mackey-Glass system with order $q_1 = 0.9$ and $q_2 = 0.9$.	15
Figure 2.8	The phase portraits and the bifurcation diagram for Double Mackey-Glass system with order $q_1 = 0.8$ and $q_2 = 0.8$.	16
Figure 2.9	The phase portraits and the bifurcation diagram for Double Mackey-Glass system with order $q_1 = 0.1$ and $q_2 = 0.1$.	17
Figure 2.10	The phase portraits for Double Mackey-Glass system with order $q_1 = 0.7$ and $q_2 = 0.7$.	18
Figure 2.11	The phase portraits for Double Mackey-Glass system with order $q_1 = 0.2$ and $q_2 = 0.2$.	18
Figure 2.12	The phase portraits for Double Mackey-Glass system with order $q_1 = 0.5$ and $q_2 = 0.5$.	18
Figure 3.1	(a)~(f) The time histories of x_1 (blue) and y_1 (red) and (g)~(l) error $e_1 = x_{1T_j} - y_1$ of double Mackey-Glass systems with initial conditions $(x_{10}, x_{20}) = (0.001, 0.001)$, $(y_{10}, y_{20}) = (0.0015, 0.0015)$	27
Figure 3.2	The curve fitting of initial condition x_0 to the length of temporary lag or anticipated synchronization L_1 .	28
Figure 3.3	The curve fitting of initial condition x_0 to the length of temporary lag or anticipated synchronization L_2 .	28
Figure 3.4	(a)~(f) The time histories of x_1 (blue) and y_1 (red) and (g)~(l) error $e_1 = x_{1T_j} + y_1$ of double Mackey-Glass systems with initial conditions $(x_{10}, x_{20}) = (-0.001, 0.001)$, $(y_{10}, y_{20}) = (0.0015, 0.0015)$.	29
Figure 4.1	The time histories of x_1 (red) and x_2 (blue) of the double	37

	Mackey-Glass system when parameter b is substituted by a Gaussian noise with noise strength $p_1 = 0.5$.	
Figure 4.2	The time histories of x_1 (red) and x_2 (blue) of the double Mackey-Glass system when parameter b is substituted by a Rayleigh noise with noise strength $p_2 = 0.2$.	37
Figure 4.3	The time histories of x_1 (red) and x_2 (blue) of the double Mackey-Glass system when parameter b is substituted by a Rician noise with noise strength $p_3 = 0.1$.	38
Figure 4.4	The time histories of x_1 (red) and x_2 (blue) of the double Mackey-Glass system when parameter b is substituted by a uniform noise with noise strength $p_4 = 0.5$.	38
Figure 4.5	The error states and the time histories of x_1, x_2 (red) and y_1, y_2 (blue) of the double Mackey-Glass systems when two corresponding parameters r are substituted by a Gaussian noise with noise strength $p_1 = 0.625$.	39
Figure 4.6	The error states and the time histories of x_1, x_2 (red) and y_1, y_2 (blue) of the double Mackey-Glass systems when two corresponding parameters r are substituted by a Gaussian noise with noise strength $p_1 = 0.05$.	39
Figure 4.7	Two corresponding parameters b are substituted by a Rayleigh noise with different noise strengths.	40
Figure 4.8	The error states and the phase portraits of the double Mackey-Glass systems when two corresponding parameters b are substituted by a Rayleigh noise with noise strength $p_2 = 0.5$.	40
Figure 4.9	The error states and the phase portraits of the double Mackey-Glass systems when two corresponding parameters b are substituted by a Rayleigh noise with noise strength $p_2 = 9.25$.	41
Figure 4.10	The error states and the phase portraits of the double Mackey-Glass systems which two corresponding parameters r are substituted by a Rayleigh noise with noise strength $p_2 = 0.16$.	41
Figure 4.11	The error states and the time histories of x_1, x_2 (red) and y_1, y_2 (blue) of the double Mackey-Glass systems when two corresponding parameters r are substituted by a Rayleigh noise with noise strength $p_2 = 0.08$.	42
Figure 4.12	Two corresponding parameters b are substituted by a Rician noise with different noise strengths.	42
Figure 4.13	The error states and the phase portraits of the double Mackey-Glass systems when two corresponding parameters b	43

	are substituted by a Rician noise with noise strength $p_3 = 5$.	
Figure 4.14	The error states and the phase portraits of the double Mackey-Glass systems when two corresponding parameters r are substituted by a Rician noise with noise strength $p_3 = 0.07$.	43
Figure 4.15	Two corresponding parameters b are substituted by a Rician noise with different noise strengths.	44
Figure 4.16	The error states and the phase portraits of the double Mackey-Glass systems when two corresponding parameters b are substituted by a uniform noise with noise strength $p_4 = 10.25$.	44
Figure 4.17	The error states and the phase portraits of the double Mackey-Glass systems when two corresponding parameters r are substituted by a uniform noise with noise strength $p_4 = 0.27$.	45
Figure 5.1	Two corresponding parameters b are substituted by a Rayleigh noise with different noise strengths.	50
Figure 5.2	The error states and the time histories of x_1, x_2 (red) and y_1, y_2 (blue) of the double Mackey-Glass systems when two corresponding parameters b are substituted by a Rayleigh noise with noise strength $p = 11$.	50
Figure 5.3	The error states and the time histories of x_1, x_2 (red) and y_1, y_2 (blue) of the double Mackey-Glass systems when two corresponding parameters b are substituted by a Rayleigh noise with noise strength $p = 8.5$.	51
Figure 5.4	The error states and the time histories of x_1, x_2 (red) and y_1, y_2 (blue) of the double Mackey-Glass systems when two corresponding parameters r are substituted by a Rayleigh noise with noise strength $p = 0.15$.	51
Figure 5.5	Chaos control by parameter excited method. The time histories of x_1, x_2 (red) and y_1, y_2 (blue) of the double Mackey-Glass system when parameter r is substituted by a uniform noise with noise strength $p = 0.165$.	52
Figure 5.6	The error states and the time histories of x_1, x_2 (red) and y_1, y_2 (blue) of the double Mackey-Glass systems when two corresponding parameters r_1 and k are substituted by a Rayleigh noise with noise strength $p = 0.03$.	52
Figure 5.7	The error states and the time histories of x_1, x_2 (red) and y_1, y_2 (blue) of the double Mackey-Glass systems when two corresponding parameters r_1 and k are substituted by a Rayleigh noise with noise strength $p = 0.12$.	53

Figure 5.8	Temporary lag synchronization. The error states and the time histories of x_1, x_2 (red) and y_1, y_2 (blue) of the double Mackey-Glass systems when the two corresponding parameters r_1 and k are substituted by a Rayleigh noise with noise strength $p = 0.103$.	53
Figure 5.9	Partial lag synchronization. The error states and the time histories of x_1 (red) and y_1 (blue) of the double Mackey-Glass systems when the two corresponding parameters r_1 and k are substituted by a Rayleigh noise with noise strength $p = 0.005$.	54
Figure 5.10	Partial chaos control by parameter excited method. The error states and the time histories of x_1 (red) and y_1 (blue) of the double Mackey-Glass systems when the two corresponding parameters r_1 and k are substituted by a Rayleigh noise with noise strength $p = 1$.	54
Figure 5.11	The error states and the time histories of x_1, x_2 (red) and y_1, y_2 (blue) when the two corresponding parameters b are substituted by a Rayleigh noise with noise strength $p = 8.5$ in presence of a small disturbance.	55
Figure 5.12	The error states and the time histories of x_1, x_2 (red) and y_1, y_2 (blue) when the two corresponding parameters b are substituted by a Rayleigh noise with noise strength $p = 5.25$ in presence of a small disturbance.	55
Figure 5.13	The error states and the time histories of x_1, x_2 (red) and y_1, y_2 (blue) when the two corresponding parameters r are substituted by a Rayleigh noise with noise strength $p = 0.03$ in presence of a small disturbance.	56
Figure 5.14	The error states and the time histories of x_1, x_2 (red) and y_1, y_2 (blue) when the two corresponding parameters r_1 and k are substituted by a Rayleigh noise with noise strength $p = 0.03$ in presence of a small disturbance.	56