

誌謝

在這兩年的碩士研究生涯中，有太多人令我心存感激。首先，要特別感謝我的論文指導教授劉柏村博士與聖約翰科技大學副校長林嘉淦博士，感謝老師的指導、教誨和鼓勵，不僅僅是在學術研究上的指導，對於人生規劃及待人處事的態度上，亦讓我獲益良多，使我能順利的完成碩士學位。另外，還要感謝中山物研所教授張鼎張博士，在學術研究上給我正確詳盡的指導，在此致上內心最誠摯的敬意和謝意。諸位口試委員的指導和建議，也在此謹申謝意。

此外，要感謝蔡志宗學長與王建文學長悉心的教導使我得以一窺超臨界流體領域的深奧，在實驗、量測分析以及論文寫作給予我莫大的協助與建議，使我在這些年中獲益匪淺，順利獲得知識與學位。另外亦得特別感謝李逸哲學長、蔡維志學長、李昇翰學長與林俊文學長的大力協助，因為有你們的陪伴、幫忙及搞笑讓兩年的研究生活變得絢麗多彩。還有要感謝王敏全學長、吳興華學長、鄒一德學長、陳弘根學長、黃千睿學長、曾子怡學姐、卓立華學姐、黃震鑠學長、陳世青學長、葉炳宏學長、曹書瑋學長、馮立偉學長、王俊文學長，感謝學長們平日對我的照顧以及研究上的建議。也要感謝實驗室一起工作的同學—李啟銘、李崇維、葉唐豪、陳又菁、蕭秀娟、鍾宛芳、聶建名、李亞諭、蕭任偉、林立夫、林原園、謝彥廷、葉睿龍、奚鵬博、翁麗雯...等，以及學弟—周誼明、高逸侑、郭豫杰、鄭逸立、竹立煒、林威廷、陳巍方、王超駿、張繼聖、蔡尚祐、陳思維...等，感謝你們陪伴我共同走過這一段甘甜的子，讓我無論是在實驗中或是讀書時永遠充滿歡樂。同時，衷心感謝國家奈米元件實驗室(NDL)和交大半導體中心提供良好的研究設備與充足的資源。

最後，我願將這份榮耀呈獻給我深愛的父母親—楊錫煌先生、張淑姿女士。感謝父母親多年來辛苦的教導與栽培，一直在背後默默地支持與關懷我，陪我度過了許多風雨與榮耀的時光，讓我能無後顧之憂，全力衝刺學業，終於不負所望完成學業，在此獻上我內心最深的謝意。此外，特別要感謝陪伴我多年的女友—林秀珊，在背後的默默支持更是我前進的動力，一直以來因為你的支持及協助，使我能順利的從大學畢業到現在碩士論文的完成，在此由衷的對你說聲謝謝。

楊柏宇 2007年6月

Contents

Chinese Abstract	-----	i
English Abstract	-----	ii
Chinese Acknowledgment	-----	iii
Contents	-----	iv
Table Captions	-----	vi
Figure Captions	-----	vii
Chapter 1 Introduction		
1.1 Supercritical Fluid Technology	-----	1
1.2 General Background	-----	2
1.2.1 Metal Oxide dielectric films	-----	2
1.2.2 Amorphous silicon thin film transistor	-----	2
1.2.3 Nanocrystal nonvolatile memories	-----	3
1.3 Motivation	-----	4
Chapter 2 Application of Supercritical Fluid Technology on Metal-Oxide Dielectric Thin Film		
2.1 Fabrication of Metal-Insulator-Silicon (MIS) and Experiment Process	---	6
2.2 Analysis of Material and Discussion	-----	7
2.2.1 Fourier Trans-form Infrared Spectroscopy (FTIR) Analysis	-----	7
2.2.2 Thermal Desorption System – Atmospheric Pressure Ionization Mass Spectrometer (TDS-APIMS) Analysis	-----	8
2.2.3 X-ray Photoelectron Spectroscopy (XPS) Analysis	-----	8
2.2.4 Auger Electron Spectroscopy (AES) Analysis	-----	10
2.2.5 Transmission Electron Microscopy (TEM) Analysis	-----	11
2.3 Analysis of Electrical Characteristics and Discussion	-----	12
2.3.1 The current density-electric field (J - E) characteristics	-----	12

2.3.2 Conduction Mechanism	-----	12
2.3.3 The capacitance-voltage (<i>C-V</i>) characteristics	-----	17
2.3.4 Breakdown voltage measurement and gate bias stress	-----	19
2.4 Summary	-----	20
Chapter 3	Application of Supercritical Fluid Technology on Amorphous Silicon Thin Film Transistors (a-Si:H TFTs)	
3.1 Fabrication of SiN _x Film and Experiment Process	-----	22
3.1.1 Fourier Trans-form Infrared Spectroscopy (FTIR) Analysis	-----	23
3.1.2 The current density-electric field (<i>J-E</i>) characteristics	-----	23
3.1.3 Breakdown voltage measurement	-----	23
3.1.4 The capacitance-voltage (<i>C-V</i>) characteristics	-----	23
3.2 Fabrication of a-Si:H TFTs and Experiment Process	-----	25
3.3 Analysis of Electric Characteristics and Discussion	-----	26
3.4 Summary	-----	29
Chapter 4	Application of Supercritical Fluid Technology on Nanocrystal Non-volatile Memories	
4.1 Fabrication of Non-volatile Memories and Experiment Process	-----	30
4.2 Analysis of Characteristics and Discussion	-----	31
4.2.1 Transmission Electron Microscopy (TEM) Analysis	-----	31
4.2.2 The current density-electric field (<i>J-E</i>) characteristics	-----	31
4.2.3 The capacitance-voltage hysteresis and retention characteristics	---	32
4.3 Summary	-----	33
Chapter 5	Conclusion	----- 34
References	-----	67
Vita	-----	71

Table Captions

Chapter 1

Table 1-1 Critical temperature and pressure for some common fluids.

Table 1-2 Comparison of physical properties of CO₂.

Chapter 2

Table 2-1 Summary of binding energies for ultra thin HfO₂ films.

Table 2-2 Summary of binding energies for ultra thin HfO₂ films O 1s after various post-treatments, including Baking-only, H₂O vapor and 3000psi-SCCO₂ treatment.

Table 2-3 The extracted parameters from C-V curves of HfO₂ films after different treatment, measuring at 1M Hz with gate bias swing from negative voltage to positive voltage (forward). The V_{fb} means the flat-band voltage, and defined as $C/C_{\max} = 80\%$. The change of flat-band voltage of different- treated HfO₂ films under forward swing is label as ΔV .

Chapter 4

Table 4-1 Summary of electrical Characteristics for Non-volatile Memories after various post-treatments, including Baking-only and 3000psi-SCCO₂ treatment.

Figure Captions

Chapter 1

Fig. 1-1 Phase diagram for CO₂.

Fig. 1-2 Density-pressure-temperature surface for pure CO₂.

Chapter 2

Fig. 2-1 The supercritical fluid system.

Fig. 2-2 The experiment processes of thin HfO₂ film with various treatments.

Fig. 2-3 The FTIR spectra of HfO₂ films (a) after various post-treatments, including Baking-only, H₂O vapor and 3000psi-SCCO₂ treatment, (b) after SCCO₂ treatment under different pressure.

Fig. 2-4 The transporting mechanism for SCCO₂ fluids taking H₂O molecule into HfO₂ film.

Fig. 2-5 The thermal desorption spectroscopy (TDS) measurement, (a) m/e (mass-to-charge ratio) = 32 peak that is attributed to O₂, (b) m/e = 18 peak that is attributed to H₂O.

Fig. 2-6 The X-ray photoemission spectra of HfO₂ films Hf 4f after various post-treatments, including (a) Baking-only, (b) H₂O vapor and (c) 3000psi-SCCO₂ treatment.

Fig. 2-7 The X-ray photoemission spectra of HfO₂ films O 1s after various post-treatments, including (a) Baking-only, (b) H₂O vapor and (c) 3000psi-SCCO₂ treatment.

Fig. 2-8 Auger electron spectroscopy: (a) 3000psi-SCCO₂ treatment (b) H₂O vapor treatment and (c) Baking-only treatment.

- Fig. 2-9 The TEM images show the MIS (Al/HfO₂/Si-Substrate) structure after various post-treatments: (a) 3000psi-SCCO₂ treatment (b) H₂O vapor treatment and (c) Baking-only treatment.
- Fig. 2-10 Conduction mechanism for Al/HfO₂/Si MIS structure.
- Fig. 2-11 The leakage current densities of HfO₂ films after different treatments. (The negative bias is applied on gate electrode)
- Fig. 2-12 (a) Curve of $\ln(J/E)$ versus reciprocal of electric field ($1/E$) for the baking-only treated HfO₂ film, and a schematic energy band diagram accounting for trap-assisted tunneling shown in the inset. (b) Leakage current density versus the square root of electric field ($E^{1/2}$) plot for the 3000 psi-SCCO₂ treated HfO₂ film. The inset shows the energy band diagram of Schottky-type conduction mechanism.
- Fig. 2-13 (a) The leakage current densities of HfO₂ films after SCCO₂ treatments under different pressures (The negative bias is applied on gate electrode). (b) The plot of $\ln(J/E)$ versus $E^{1/2}$, which is according to Poole-Frenkel emission, and inset is the energy band diagram of Poole-Frenkel emission.
- Fig. 2-14 The leakage current densities of HfO₂ films after SCCO₂ treatments under different pressures (The positive bias is applied on gate electrode). Inset plots the energy band diagram of leakage current.
- Fig. 2-15 The capacitance-voltage characteristics of HfO₂ films after different treatment, measuring at 1M Hz with gate bias swing from negative voltage to positive voltage (forward) and from positive voltage to negative voltage (reverse).
- Fig. 2-16 The mechanism of extracting of fixed charge with SCCO₂ fluids.
- Fig. 2-17 The equivalent capacitance models of MOS structure (a) without C_{it} , (b) with C_{it} .

Fig. 2-18 The capacitance-voltage characteristics of HfO₂ films after different treatment, measuring at 1M Hz and 100k Hz with forward gate bias swing.

Fig. 2-19 The breakdown characteristic curves of HfO₂ films after various treatments (a) at positive and (b) at negative gate bias region, individually.

Fig. 2-20 The variation of leakage current of different-treated HfO₂ films as a function of stress time at a high electric field = 5 MV/cm.

Chapter 3

Fig. 3-1 The experiment processes of thin SiN_x film with various treatments.

Fig. 3-2 The FTIR spectra of SiN_x films after various post-treatments, including Baking-only, H₂O vapor and 3000psi-SCCO₂ treatment.

Fig. 3-3 The leakage current densities of SiN_x films after different treatments.

Fig. 3-4 The breakdown characteristic curves of SiN_x films after various treatments.

Fig. 3-5 The capacitance-voltage characteristics of SiN_x films after different treatment, measuring at 1M Hz with gate bias swing from negative voltage to positive voltage (forward) and from positive voltage to negative voltage (reverse).

Fig. 3-6 The structure of a-Si:H TFTs.

Fig. 3-7 The experiment processes of a-Si:H TFTs with various treatments.

Fig. 3-8 The transfer characteristics of identical a-Si:H TFTs before and after the SCCO₂ treatment. The gate bias region (1), (2), (3), (4) express sequentially above- threshold, forward sub-threshold, reverse sub-threshold and Pool-Frenkel emission region [42].

Fig. 3-9 The output characteristics of a-Si:H TFTs before and after SCCO₂ treatment.

Fig. 3-10 The transfer characteristics of SCCO₂-treated TFT at different temperature, in linear operation region with $V_{DS} = 0.1$ V. Inset is the plot of $\ln(I_{DS})$ versus reciprocal of temperature ($1/T$).

Fig. 3-11 The plot of activation energy versus gate bias, before and after SCCO₂ treatment. The inset shows the definition of activation energy ($E_{act.}$).

Fig. 3-12 The density of states in mobility gap of a-Si:H film. (a) a-Si:H TFT with no SCCO₂ treatment before and after the hot baking on a hot plate at 150 °C for 120 min, which taken as the control sample. (b) a-Si:H TFT device before and after SCCO₂ treatment.

Chapter 4



Fig. 4-1 The experiment processes of Memories with various treatments.

Fig. 4-2 The TEM images show the Non-volatile Memories structure after various post-treatments: (a) Baking-only treatment (b) 3000psi-SCCO₂ treatment.

Fig. 4-3 The leakage current densities of Non-volatile Memories after different treatments.

Fig. 4-4 The capacitance-voltage hysteresis characteristics of Non-volatile Memories after different treatment: (a) Baking-only treatment (b) 3000psi-SCCO₂ treatment.

Fig. 4-5 The retention characteristics of Non-volatile Memories after different treatment: (a) Baking-only treatment (b) 3000psi-SCCO₂ treatment.