

References

Chapter 1

- [1] T. Sakata, Y. Miyahara, “Detection of DNA recognition events using multi-well field effect devices.”, Biosensors and Bioelectronics, 21, 827–832 (2005).
- [2] J. J. Xu, W. Zhao, X. L. Luo and H. Y. Chen, “A sensitive biosensor for lactate based on layer-by-layer assembling MnO₂ nanoparticles and lactate oxidase on ion-sensitive field-effect Transistors.”, Chem. Commun., 6, 792–794 (2005).
- [3] A. L. Simonian, J. K. Grimsley, A. W. Flounders, J. S. Schoenige, T. C. Cheng, J. J. DeFrank and J. R. Wild, “Enzyme-based biosensor for the direct detection of fluorine-containing organophosphates”, Analytica chimica Acta, 442, 15-23 (2001).
- [4] M. Basu, S. Seggerson, J. Henshaw, J. Jiang, R. Cordona, C. Lefave, P. J. Boyle, A. Miller, M. Pugia and S. Basu, “Nano-biosensor development for bacterial detection during human kidney infection: Use of glycoconjugate-specific antibody-bound gold NanoWire arrays (GNWA).”, Glycoconjugate Journal, 21, 487-496 (2004).
- [5] R. R. LaPierre, M. C. Plante, J.A. Garrett, H. A. Budz, ”Nanowire fabrication and biosensor applications.”, Proc. of SPIE, 5969, 59690G-1 (2005)
- [6] L. A. Bauer, N. S. Birenbaum and G. J. Meyer, “Biological applications of high aspect ratio nanoparticles”, J. Mater. Chem, 14, 517-526 (2004).
- [7] Z. Li, Y. Chen, X. Li, T. I. Kamins, K. Nauka and R. S. Williams, “Sequence-specific label-free DNA sensors based on silicon nanowires”, Nano Lett, 4, 245-247 (2004).
- [8] G. P. Anderson, K. D. King, K. L. Gaffney, L. H. Johnson, “Multi-analyte

- interrogation using the fiber optic biosensor.”, Biosens Bioelectron, 14, 771-777 (2000).
- [9] J. P. Golden, E. W. Saaski, G. P. Anderson, and F. S. Ligle, “Portable multichannel fiber optic biosensor for field detection.” Opt. Eng., 36, 1008–1013 (1997).
- [10] K. D. King, G. P. Anderson, K. E. Bullock, M. J. Regina, E. W. Saaski, and F. S. Ligler, “Detecting staphylococcal enterotoxin B using an automated fiber optic biosensor”, Biosensors and Bioelectronics, 14, 163–170 (1999)
- [11] C. M. Niemeyer. “Nanoparticles, proteins, and nucleic acids: biotechnology meets materials science.” Angew. Chem. Int. Ed., 40, 4128-4158 (2001).
- [12] C. H. Chang, S. J. Su, Y. K. Chi, G. C. Chi, J. Y. Chang, C. A. Sheu, J. K. Chen, J. F. “GaN metal-semiconductor-metal ultraviolet photodetectors with transparent indium-tin-oxide Schottky contacts” Photonics Technology Letters, IEEE, 13, 848-850 (2001).
- [13] G. Parish, S. Keller, P. Kozodoy, J. A. Ibbetson, H. Marchand, P. T. Fini, S. B. Fleischer, S. P. DenBaars, and U. K. Mishra, “High-performance (Al,Ga)N-based solar-blind ultraviolet p-i-n detectors on laterally epitaxially overgrown GaN” Appl. Phys. Lett., 75, 247-249 (1999).
- [14] I. Ferguson, C. A. Tran, R. F. Karlicek, Z. C. Feng, R. Stall, S. Liang, Y. Lu, and C. Joseph, “GaN and AlGaN metal–semiconductor–metal photodetectors” Mater. Sci. Eng. B, 50, 311-314 (1997).
- [15] P. Bhattacharya, “Semiconductor Optoelectronic Devices” , Prentic Hall, Chapter 8 (1994).

- [16] J. I. Pankove, “Optical Processes in Semiconductor”, Dover Publications, Chapter 14 (1975).
- [17] D. Long, Chapter 4, “Optical and Infrared Detectors” , R. J. Keyes, Springer-Verlag (1980).
- [18] Y. Cui, Q. Wei, H. Park, C. M. Lieber, “Nanowire Nanosensors for Highly Sensitive and Selective Detection of Biological and Chemical Species.”, Science, 293, 1289 – 1292 (2001).
- [19] J. T. Nevill, D. Di Carlo, P. Liu, K. H. Jeong, and L. P. Lee, “Detection Of Protein Conformation Changes With A Nano Gap Biosensor.”, Solid-State Sensors, Actuators and Microsystems, 2, 1668-1671 (2005).
- [20] J. T. Nevill, K. H. Jeong, and L. P. Lee, “Ultrasensitive biosensor to detect changes in structure of water and ice.”, Solid-State Sensors, Actuators and Microsystems, 2, 1577-1580 (2005).
- [21] R. J. Chen, H. C. Choi, S. Bangsaruntip, E. Yenilmez, X. Tang, Q. Wang, Y. L.Chang, and H. Dai, “An Investigation of the Mechanisms of Electronic Sensing of Protein Adsorption on Carbon Nanotube Devices.”, J. AM. CHEM. Soc. 126, 1563-1568 (2004).
- [22] R. Budakian and S. J. Puttermann, “Force detection using a fiber-optic cantilever” Appl. Phys. Lett., 81, 2100-2102 (2002).
- [23] J. Mertens, M. Álvarez, and J. Tamayo, “Real-time profile of microcantilevers for sensing applications” Appl. Phys. Lett., 87, 234102-234105 (2005).
- [24] J. Li, Y. B. Wang, J. D. Qiu, D. C. Sun and X. H. Xia, “Biocomposites of covalently linked glucose oxidase on carbon nanotubes for glucose biosensor”, Analytical and Bioanalytical Chemistry, 383, 918-922 (2005).

- [25] W. C. Poh, K. P. Loh, W. D. Zhang, S. Triparthy, J. S. Ye, F. S. Sheu , “Biosensing Properties of Diamond and Carbon Nanotubes” *Langmuir*, 20, 5484-5492 (2004).
- [26] R. Lucklum and P. Haauptmann, “The quartz crystal microbalance: mass sensitivity, viscoelasticity and acoustic amplification.” *Sensor Actuat. B*, 70, 30 (2000).
- [27] J. Rickert, A. Brecht and W. Gopel, “Quartz crystal microbalance for quantitative biosensing characterizing protein multilayers.” *Biosens. Bioelectron.*, 12, 567 (1997).
- [28] Y. Y. Wong, S. P. Ng, M. H. Ng, S. H. Si, S. Z. Yao and Y. S. Fung, “Immunosensor for the differentiation and detection of salmonella species based on a quartz crystal microbalance.” *Biosens. Bioelectron.*, 17, 676 (2002).
- [29] W. U. Wang , C. Chen , K. H. Lin , Y. Fang , C. M. Lieber, “Label-free detection of small-molecule–protein interactions by using nanowire nanosensors.”, *PNAS*, 102, 3208-3212 (2005).
- [30] F. E. Mallard, G. Marchand, F. E. Ginot, R. Campagnolo, “Opto-electronic DNA chip: high performance chip reading with an all-electric interface.” *Biosensors and Bioelectronics*, 20, 1813–1820 (2005).
- [31] R. Martins, P. Baptista, L. Raniero, “Amorphous/nanocrystalline silicon biosensor for the specific identification of unamplified nucleic acid sequences using gold nanoparticle probes.”, *APPLIED PHYSICS LETTERS*, 90 , 023903 (2007).

Chapter 2

- [1] W. Schottky, “Halbleitertheorie der sperrsicht.” *Naturwissenschaften*, 26,

843 (1938).

[2] S. M. Sze, Physics of Semiconductor Devices, John Wiley & Sons, Inc., Chap 10 (1985).

[3] S. Y. Wang, D. M. Bloom, and D. M. Collins, “Ultrahigh speed photodetectors,” SPIE, 439, 178 (1993).

[4] R. March, H. Tretow, and W. Ludwig, “Physical properties of Au-ZnSe metal-semiconductor contacts.” Phys. Status Solidi, 25, 567-573 (1974).

[5] S. M. Sze, Physics of Semiconductor Devices, 2nd Ed., John Wiley & Sons, New York (1981).

[6] E. H. Rhoderick, “Metal-semiconductor contacts” IEE Proc., 129, 1 (1982).

[7] E. H. Rhoderick and R. H. Williams, Metal-Semiconductor Contacts, 2nd Ed., Clarendon Press, Oxford (1988).

[8] W. Schottky and E. Spenke, “Quantitative treatment of the space charge and boundary-layer theory of the crystal rectifier.”, Wiss. Veroff. Siemens-Werken., 18, 225 (1939).

[9] E. Spenke, Electronic Semiconductors, McGraw-Hill, New York, (1958).

[10] H. M. Gupta and G. F. Leal Ferreira, “Theory of photoinjection and conductivity in insulators”, Phys. Rev. B, 24, 2205 - 2210 (1981).

[11] C. R. Crowell and S. M. Sze, “Current transport in metal-semiconductor barriers”, Solid State Electron., 9, 1035 (1966).

[12] A. M. Cowley and S. M. Sze, “Surface states and barrier height of metalsemiconductor systems”, J. Appl. Phys., 36, 3212 (1965).

Chapter 3.

[1] R. A. Laudise, “The growth of single crystals”, J. Electrochem. Soc., 118,

154C (1971).

[2] J. S. Chang, "Selective Reactive Ion Etching of SiO₂" Solid State Technol., 11, 214 (1984).

[3] Z. Abraham, "Proximity correction method for E-beam lithography" United states patent #US005241185A (1993).

[4] T. Utsumi, "Low-Energy E-Beam Proximity Lithography (LEEPL): Is the Simplest the Best?" Jpn. J. Appl. Phys., 38, 7046-7051 (1999).

[5] M. Gesley, "Mask Patterning Challenges Beyond 150 nm" Jpn. J. Appl. Phys., 37, 6675-6680 (1998).

[6] K. M. Harafuji, A. Nomura, N. Kawamoto, M. Yamashita, "A novel hierarchical approach for proximity effect correction in electron beam lithography", IEEE Transactions on, 12, 1508-1514 (1993).

[7] V. Bouchiat, D. Esteve, "Lift-off lithography using an atomic force microscope", Appl. Phys. Lett., 20, 3098-3100 (1996).

[8] W. Chen and H. Ahmed, "Fabrication of sub-10 nm structures by lift-off and by etching after electron-beam exposure of poly(methylmethacrylate) resist on solid substrates" Journal of Vacuum Science & Technology B, 11, 2519-2523 (1993).

[9] E. Yablonovitch, T. Gmitter, J. P. Harbison, and R. Bhat, "Extreme selectivity in the lift-off of epitaxial GaAs films", Applied Physics Letters, 51, 2222-2224 (1987).

[10] Y. J. Chen, J. H. Hsu and H. N. Lin, "Fabrication of metal nanowires by atomic force microscopy nanoscratching and lift-off process", Nanotechnology, 16, 1112–1115 (2005).

[11] S. Bhattacharya, A. Datta, J. M. Berg, and S. Gangopadhyay, "Studies on Surface Wettability of Poly(Dimethyl) Siloxane (PDMS) and Glass Under

Oxygen-Plasma Treatment and Correlation With Bond Strength" JOURNAL OF MICROELECTROMECHANICAL SYSTEMS, 14, 590-597 (2005).

[12] N. Sundararajan, M. S. Pio, L.P. Lee, and A. A. Berlin, Member IEEE, "Three-Dimensional Hydrodynamic Focusing in Polydimethylsiloxane (PDMS) Microchannels", JOURNAL OF MICROELECTROMECHANICAL SYSTEMS, 13, 559-567 (2004).

[13] S. Chen and K. Kimura, "Synthesis and Characterization of Carboxylate-Modified Gold Nanoparticle Powders Dispersible in Water", Langmuir, 15, 1075 -1082 (1999).

[14] S. J. Park, S. Kim, S. Lee, "Synthesis and Magnetic structure of uniform Iron nanorods and nanoshperes", Journal of the American Chemical Society, 122, 8581-8582 (2000).



Chapter 4

[1] J. C. Carrano, T. Li, P. A. Grudowski, C. J. Eiting, R. D. Dupuis, and J. C. Campbell Appl. Phys. Lett., 83, 6148 (1998).

[2] R. J. Stirn, Y. C. M. Yeh, "A 15% efficient antireflection-coated metal-oxide-semiconductor solar cell", 27, 95-98 (1975).

[3] E. A. Martin, K. Vaccaro, J. P. Lorenzo, "Backside illuminated MSM device method", united state patent # 5494833 (1996).

[4] E. B. Grann, M. G. Moharam, D. A. Pommet, "Optimal design for antireflective tapered two-dimensional subwavelength grating structures." J. Opt Soc Am (A), 12, 333-339 (1995).

[5] H. L. Chen, Wonder Fan, C. C. Cheng, C. H. Lin, and K. T. Huang, "Fabrication of Texturing Antireflection Structures in Solar Cells by Using the

Defocusing Exposure in Optical Lithography”, J. Electrochem. Soc., 153, G802-G806 (2006).

[6] H. Sai, H. Fujii, K. Arafune, Y. Ohshita, and M. Yamaguchi, “Antireflective subwavelength structures on crystalline Si fabricated using directly formed anodic porous alumina masks”, APPLIED PHYSICS LETTERS, 88, 201116 (2006).

[7] C. Rossel, G. I. Meijer, D. Bremaud, D. Widmer, “ Electrical current distribution across a metal-insulator-metal structure during bistable switching”, Journal of Applied Physics, 90, 2892-2898 (2001).

[8] L. H. Laih, T. C. Chang, Y. A. Chen, W.C. Tsay, J. W. Hong, “A U-grooved metal-semiconductor-metal photodetector (UMSM-PD) with an i-a-Si:H overlayer on a [100] P-type Si wafer”, Photonics Technology Letters, IEEE, 10, 579-581 (1998).

[9] J. I. Chyi, T. S. Wei, J. W. Hong, W. Lin, Y. K. Tu, “Low dark current and high linearity InGaAs MSM photodetectors” Electronics Letters, 30, 355-356 (1994).

[10] J. Ohsawa , T. Kozawa , O. Fujishima , H. Itoh, “Narrow-band 400 nm MSM photodetectors using a thin InGaN layer on a GaN/sapphire structure“ Physica status solidi (c), 3, 2278-2282 (2006).

[11] S. J. Xu, W. Liu and M. F. Li, “Effect of temperature on longitudinal optical phonon-assisted exciton luminescence in heteroepitaxial GaN layer.” APPLIED PHYSICS LETTERS, 77, 3376 (2002).

[12] 贺艳峰, 张家明, 郭小英, 朱广华, 陆祖宏, “化学发光法检测肿瘤标志物”, 化学通报第68 卷 (2005).

[13] Y. Iwasaki , T. Horiuchi, M. Morita, O. Niwa, “Time differential surface

plasmon resonance measurements applied for electrochemical analysis”,
Electroanalysis, 9, 1239-1241 (2005).

[14] A. J. Haes, S. Zou, G. C. Schatz, and R. P. Van Duyne, “Nanoscale Optical Biosensor: Short Range Distance Dependence of the Localized Surface Plasmon Resonance of Noble Metal Nanoparticles”, J. Phys. Chem. B, 108, 6961-6968 (2004).

