

Table of Contents

| | |
|---|------------|
| Table of contents | |
| Abstract (Chinese) | i |
| Abstract (English) | iii |
| Acknowledge | v |
| List of Publications | vi |
| Contents | ix |
| Figure Captions | xi |
| | |
| Chapter 1 Introduction | 1 |
| Chapter 2 Basic theory | 8 |
| 2-1 Type-II superconductors | 8 |
| 2-2 Basic vortex physics | 12 |
| 2-3 Simulation and results | 14 |
| Chapter 3 Fabrication process and measurement techniques | 19 |
| 3.1 Sample preparation | 19 |
| 3-1-1 E-beam lithography | 21 |
| 3-1-2 Etching | 25 |
| 3-1-3 Film growth and characterization | 27 |
| 3-2 Measurements | 29 |
| 3-2-1 Transport measurements | 29 |
| 3-2-2 Magnetic and atomic force microscopy | 31 |
| Chapter 4 Results and discussion | 32 |
| 4-1 Basic periodic pinning | 32 |
| 4-1-1 Results of square array of pinning sites | 32 |

| | |
|---|-----------|
| 4-1-2 Periodic Pinning basics | 37 |
| 4-1-3 Pinning mechanism | 42 |
| 4-2 Influence of lattice geometry | 48 |
| 4-3 asymmetric pinning | 51 |
| 4-3-1 asymmetric pinning properties for regular arrays | 51 |
| 4-3-2 asymmetric pinning properties for spacing-graded arrays | 55 |
| 4-2 Ratchet effect | 65 |
| Chapter 5 Conclusions | 83 |
| References | 85 |



List of Figures

| | | |
|------|---|----|
| 2-1 | Schematic magnetic field verse temperature phase diagram | 9 |
| 2-2 | Numerical simulation of vortex positions at various matching fields for a square pinning array | 17 |
| 2-3 | Numerical simulation of vortex positions at various matching fields for a triangular pinning array | 18 |
| 3-1 | Schematic of the electron-beam lithography and lift-off process..... | 20 |
| 3-2 | Schematic diagram of the EB control system | 21 |
| 3-3 | SEM..... | 22 |
| 3-4 | Bonding pads were defined by photo lithography and Au was thermally evaporated onto a SiN-coated silicon substrate. We used these patterned structures as starting electrodes in the present method..... | 23 |
| 3-5 | Scanning electron micrograph of a SiN-coated silicon substrate with holes. The holes are 200 nm in diameter and positioned on a square lattice with a lattice constant equal 500nm. The scale is given at the bottom of the picture..... | 26 |
| 3-6 | Dc sputtering system..... | 28 |
| 3-7 | Cross section of the niobium film..... | 28 |
| 3-8 | SQUID system..... | 30 |
| 3-9 | AFM..... | 31 |
| 4-1 | Field dependence of the resistance and critical current for a Nb film with a square array of defects at T=8.75 K..... | 35 |
| 4-2 | I - V characteristics for a triangle lattice at T=8.73 K under various magnetic fields applied perpendicular to the film plane. The arrows represent the crossover currents between integer and half-integer matching fields. | 36 |
| 4-3 | Magnetoresistance for different injected current in a Nb film with a square array of defects at T=8.75 K. | 36 |
| 4-4 | Magnetic force micrograph of a square lattice of submicron magnetic dot (a) before magnetization, and after magnetization along axis of the dots. | 40 |
| 4-5 | Critical current density in function of magnetic field at T/Tc=0.985 for a superconducting film covering the triangular magnetic dot array in the single-domain and in the multi-domain state. | 40 |
| 4-6 | Critical current density in function of magnetic field showed the asymmetric properties for different magnetism. | 46 |
| 4-7 | Three configurations of the magnetic dot arrays used in our simulation: (a) FM, (b) AFM, and (c) AFM2×2. The black open and gray filled circles are the up- and down-magnetized dots. The dotted lines indicate the unit cells for each configuration. | 47 |
| 4-8 | SEM micrographes for a Nb film with different geometries of defect array. | 48 |
| 4-9 | Critical current as a function of the magnetic field for a Nb film with different geometries of defect array. | 49 |
| 4-10 | Critical current as a function of the magnetic field for a Nb film with a triangular array of defects. | 53 |

| | | |
|------|---|----|
| 4-11 | The vortices distribution ~filled circles! and pinning sites (open circles) for (a) the incommensurate row and (b) the interstitial flowing channel.... | 53 |
| 4-12 | The trajectories of vortices for $n = 2$ for case A (a) and case B (b) for driving force just above the critical depinning force. The open circles represent the pinning sites. | 54 |
| 4-13 | SEM micrograph. Sample A is triangular array of pinning sites and the sample B is graded ones. | 56 |
| 4-14 | SEM micrograph shows the top view of the small gradient sample..... | 57 |
| 4-15 | SEM micrograph shows the top view of the large gradient sample..... | 58 |
| 4-16 | dc voltage vs dc applied current for a Nb film with graded pinning site's density at first matching field. | 60 |
| 4-17 | (a) MR curves for injected positive/negative current at $T = 8.20$ K. The inset (b) and (c) show sharp and shallow dips around the first matching field. | 61 |
| 4-18 | Magnetoresistance curves MR of a niobium film with spacing-graded array of holes in two opposite direction of dc current (negative current filled square, positive current open circle). (a) $T = 7.90$ K, (b) $T = 7.86$ K..... | 64 |
| 4-19 | Dc voltage drop V_{dc} as a function of ac current I_{ac} for different applied magnetic fields. | 74 |
| 4-20 | Dc voltage drop as a function of ac current for different temperature..... | 74 |
| 4-21 | The $V_{dc}(I_{ac})$ for different applied magnetic field at $T = 8.20$ K..... | 75 |
| 4-22 | The comparison between the maximum rectified value (V_{max}) and Magnetoresistance as a function of applied magnetic field..... | 77 |
| 4-23 | Magnetoresistance as a function of applied magnetic field..... | 77 |
| 4-24 | Dc voltage drop V_{dc} as a function of ac current I_{ac} for different magnetic field. Panels (a)-(b): $H < H_1$. Panel (c): $H = H_1$. Panel (d)-(f): $H > H_1$. H_1 is the first matching field and is equal to 150 Oe..... | 81 |
| 4-25 | (a) The dependence of the maximum/minimum rectification dc voltage (V_{max}) in the $V_{dc}(I_{ac})$ curves of the peak/dip for different applied magnetic field. (b) the position of peak (open symbols) and dip (filled symbols) as a function of applied magnetic field..... | 82 |