

# Contents

<b>Acknowledgements</b> .....	I
<b>Chinese Abstract</b> .....	II
<b>English Abstract</b> .....	III
<b>Contents</b> .....	IV
<b>List of Figures</b> .....	VII
<b>List of Tables</b> .....	XI
<b>List of Acronyms</b> .....	XII

## Chapter 1

### Introduction

1.1 Review of Wavelength Tunable Laser using FPLD.....	1
1.2 Review of Fiber Bragg Grating Sensor Network.....	2
1.2.1 Multiplexing techniques.....	3
1.2.1 Fiber laser scheme.....	4
1.3 Organization of the Dissertation.....	6
References.....	7

## Chapter 2

### Wavelength Tunable Laser using FPLD

2.1 Linear-Cavity Fiber Laser Scheme.....	12
2.1.1 Experimental Setup.....	12
2.1.2 Results and Discussion.....	13
2.2 Fiber Ring Laser Scheme.....	15
2.2.1 Experimental Setup.....	15
2.2.2 Results and Discussion.....	16

2.3 External-Injection Scheme.....	18
2.3.1 Experimental Setup.....	18
2.3.2 Results and Discussion.....	20
References.....	22

## **Chapter 3**

### **Fiber-laser-based Sensor Network with Self-Healing Function**

3.1 Self-Healing Ring Architecture.....	36
3.1.1 Architecture Description.....	36
3.1.2 Experimental Results and Discussion.....	38
3.2 Hybrid Star-Ring Architecture.....	41
3.2.1 Architecture Description.....	42
3.2.2 Experimental Results and Discussion.....	43
3.3 Star-Bus-Ring Architecture.....	46
3.3.1 Architecture Description.....	47
3.3.2 Experimental Results and Discussion.....	48
References.....	50

## **Chapter 4**

### **Large-Scale Sensor Network using Fiber laser Scheme**

4.1 Intensity and Wavelength Division Multiplexing Sensor System.....	66
4.1.1 Principles.....	67
4.1.2 Experimental Results and Discussion.....	67
4.2 Linear-Cavity Fiber Raman Laser .....	70
4.2.1 Experimental Setup.....	71
4.2.2 Experimental Results and Discussion.....	72
4.3 Fiber Ring Laser with EDWA and SOA.....	74
4.3.1 Experimental Setup.....	75
4.3.2 Experimental Results and Discussion.....	76

References.....77

**Chapter 5**

**Conclusions**

5.1 Summary for the Dissertation.....89

    5.1.1 Wavelength Tunable Laser using FPLD..... 89

    5.1.2 Fiber-laser-based Sensor Network with Self-Healing Function.....90

    5.1.3 Large-Scale Sensor Network using Fiber laser Scheme..... 92

5.2 Suggestions for Future Work.....93



## List of Figures

**Fig. 2.1** Experimental setup of the wavelength-tunable mode-locked linear-cavity fiber laser.

**Fig. 2.2** Output spectrum of the gain-switched FPLD.

**Fig. 2.3** Output spectra and pulse waveforms of the fiber laser when the central wavelength of the tunable bandpass filter is at different FPLD lasing modes. (a) Output spectra. (b) Pulse waveforms.

**Fig. 2.4** The SMSR and pulsewidth as a function of wavelengths.

**Fig. 2.5** Experimental setup of the wavelength-tunable mode-locked fiber ring laser.

**Fig. 2.6** Schematic diagram of the EDWA.

**Fig. 2.7** Fiber laser (a) without VODL and (b) with VODL.

**Fig. 2.8** Output spectrum of gain-switched FPLD.

**Fig. 2.9** (a) Output spectra and (b) pulse waveforms of the fiber ring laser when the central wavelength of the tunable filter coincides with one of the wavelength of the FPLD lasing modes.

**Fig. 2.10** The SMSR and pulsewidth as a function of wavelengths.

**Fig. 2.11** Schematic diagram of the proposed system for the generation of wavelength-tunable optical pulses.

**Fig. 2.12** Output spectra of the backward ASE and the ASE through the tunable filter.

**Fig. 2.13** Output spectra obtain at different points in Fig.1, (a) at point “A”, (b) at point “B”, (c) at point “C”.

**Fig. 2.14** Output spectrum of the system when the FPLD is without ASE injection.

**Fig. 2.15** (a) Output spectra and (b) pulse waveforms of the system when the central wavelength of the tunable filter is tuned to one of the wavelength of the FPLD lasing modes.

**Fig. 2.16** The SMSR and pulsewidth as a function of wavelengths.

**Fig. 3.1** Schematic diagram of the proposed self-healing sensor network based on a linear-cavity fiber laser scheme.

**Fig. 3.2** Schematic situation (indicated by the dashed line) when Sensing Region 2 is selected by using a TDM signal.

**Fig. 3.3** Schematic situation when a breakpoint occurs and the fiber link fails in Sensing Region N-1.

**Fig. 3.4** Experimental setup for the proposed FBG sensor network. We examine three sub-networks in the self-healing ring architecture. Each sub-network includes ten sensing FBGs  $f_i$  ( $i=1, 2, \dots, 10$ ).

**Fig. 3.5** Output spectra of the linear-cavity fiber laser at different lasing wavelengths.

**Fig. 3.6** When the link fails in Region 2, the FBGs  $f_m$  ( $m=6, 7, 8, 9, 10$ ) loses their sensing information whenever Sensing Region 2 is selected by using a TDM signal.

**Fig. 3.7** State (b) of the 1x2 switch can be modified to reconfigure the fiber link for FBGs  $f_m$  ( $m=6, 7, 8, 9, 10$ ) that lost the sensing information. The self-healing ring architecture can regenerate the sensing signals from FBGs  $f_m$  ( $m=6, 7, 8, 9, 10$ ).

**Fig. 3.8** Schematic diagram of a hybrid star-ring architecture for FBG sensor system.

**Fig. 3.9** Schematic diagram of a remove node.

**Fig. 3.10** Schematic diagram (indicated by the dashed line) when the optical switches states are normally set.

**Fig. 3.11** Schematic diagram when three breakpoints occur.

- (a) When the SW in the Bar state.
- (b) When the SW in the cross state.

**Fig. 3.12** Experimental setup for the proposed FBG sensor network. We examine the case of two breakpoints occur.

**Fig. 3.13** When the link fails, the FBGs  $S_m$  ( $m=4, 5, 8, 9, 10$ ) loses their sensing information.

**Fig. 3.14** The OS can be modified to reconfigure the fiber link for FBGs  $S_m$  ( $m=4, 5, 8, 9, 10$ ) that lost the sensing information.

**Fig. 3.15** Schematic diagram of star-bus-ring architecture for FBG sensors.

**Fig. 3.16** Schematic diagram of remote node.

**Fig. 3.17** Schematic situation (indicated by dashed line)

- (a) when Sensing Region 1 is selected using TDM signal.
- (b) when Sensing Region 2 is selected using TDM signal.

**Fig. 3.18** Schematic diagram when breakpoints occur in bus subnet.

**Fig. 3.19** Schematic diagram when breakpoints occur in star subnet.

**Fig. 3.20** Experimental setup for proposed FBG sensor network.

**Fig. 3.21** Schematic diagram when Sensing Region 7 is selected.

**Fig. 3.22** Output spectra of linear-cavity fiber laser at different lasing wavelengths.

**Fig. 3.23** Schematic diagram when Sensing Region 8 is selected.

**Fig. 3.24** When link fails, sensing information FBG  $m$  ( $m=6, 7, 8, 9,$  and  $10$ ) is lost.

**Fig. 3.25** The RN7 is modified to reconfigure the fiber link for FBG  $m$  ( $m=6, 7, 8, 9,$  and  $10$ ) that lost sensing information.

**Fig. 4.1** Schematic diagram of the tunable multiport fiber laser for IWDM sensor systems.

**Fig. 4.2** Output spectra at 30% lasing port within the working range from 1528nm to 1572nm.

**Fig. 4.3** Laser stability regarding output power variation and wavelength drift at 1533.19 nm.

**Fig. 4.4** Output powers of the 30%, 20% and 10% lasing ports at different lasing wavelengths.

**Fig. 4.5** Output spectra of the 30%, 20% and 10% lasing ports at different lasing wavelengths.

**Fig. 4.6** Output signals from the PD under the scanning Fabry-Perot filter operation.

**Fig. 4.7** Schematic diagram of the long-distance FBG sensor system.

**Fig. 4.8** (a) Schematic diagram of the Raman gain measurement. (b) Raman gain at different signal wavelength.

**Fig. 4.9** Output spectra of the linear-cavity fiber laser with 330-mW pump power (a) when no strain was applied (b) when strain was applied to FBG2.

**Fig. 4.10** The strain measurement of the FBG2.

**Fig. 4.11** Variation of peak power as a function time for each lasing line.

**Fig. 4.12** The relationship between the peak power and the Raman pump

power.

**Fig. 4.13** Schematic diagram of the long-distance FBG sensor system.

**Fig. 4.14** Optical gain spectra of the EDWA, SOA, and hybrid amplifier when the input power is set at -25 dBm.

**Fig. 4.15** ASE spectra of the EDWA and hybrid amplifier.

**Fig. 4.16** Output spectra of the fiber ring laser with (a) hybrid amplifier and (b) SOA.

**Fig. 4.17** Wavelength shifts of FBG3 when different strains were imposed on it.

**Fig. 4.18** Variation of peak power as a function time for each lasing wavelength.



**Table 3.1** Brief comparisons of the proposed sensor networks.



## List of Acronyms

<b>ASE</b>	Amplified spontaneous emission
<b>C</b>	Coupler
<b>CO</b>	Center office
<b>EDFA</b>	Erbium doped fiber amplifier
<b>EDWA</b>	Erbium doped waveguide amplifier
<b>FBG</b>	Fiber Bragg grating
<b>FPLD</b>	Fabry-Perot laser diode
<b>MVS</b>	Minimum variance shift
<b>NZDSF</b>	Non-zero dispersion shifted fiber
<b>IWDM</b>	Intensity and wavelength division multiplexing
<b>OCDMA</b>	Optical code-division multiple access
<b>OS</b>	1x2 optical switch
<b>OSA</b>	Optical spectrum analyzer
<b>OTDM</b>	Optical time division multiplexed
<b>PC</b>	Polarization controller
<b>PBC</b>	Polarization beam combiner
<b>SNR</b>	Signal-to-noise ratio
<b>SMF</b>	Single mode fiber
<b>SOA</b>	Semiconductor optical amplifier
<b>SW</b>	2x2 optical switch
<b>TF</b>	Tunable filter
<b>WDM</b>	Wavelength division multiplexed
<b>VODL</b>	Variable optical delay line