

Table of Contents

| | |
|---------------------------------|-------------|
| Abstract (Chinese) | i |
| Abstract (English) | iii |
| Acknowledgement | v |
| Table of Contents | vi |
| Figure Captions | x |
| List of Tables | xiii |
| Preface | xiv |

| | | |
|------------------|--|----------|
| Chapter 1 | Introduction | 1 |
| 1.1 | Planar-integrated free space optics (Planar optics)..... | 1 |
| 1.2 | Flat panel display (FPD)..... | 1 |
| 1.3 | Motivation and objectives of this thesis..... | 2 |
| 1.4 | Organization of this thesis..... | 4 |
| 1.5 | References..... | 5 |
| Chapter 2 | Planar Optics | 6 |
| 2.1 | Theories of typical planar optics..... | 7 |
| 2.1.1 | Compensation of aberration..... | 7 |
| 2.1.2 | Efficiency of quantized diffractive optics..... | 10 |
| 2.2 | Modeling..... | 13 |
| 2.2.1 | Refractive optical element (ROE)..... | 13 |
| 2.2.2 | Modeling of Diffractive optical element (DOE)..... | 14 |
| 2.2.3 | Design of Diffractive optical element (DOE)..... | 17 |
| 2.3 | Fabrication techniques..... | 19 |
| 2.3.1 | Micro-electro-mechanical-systems (MEMS)..... | 20 |

| | | |
|------------------|--|-----------|
| 2.3.2 | Diamond machining..... | 22 |
| 2.3.3 | Imprint..... | 22 |
| 2.4 | Out-coupling efficiency..... | 23 |
| 2.4.1 | Causes of insufficient out-coupling efficiency..... | 24 |
| 2.4.2 | Method of improving reflectivity: Composite metal coating... | 25 |
| 2.5 | Summary..... | 29 |
| 2.6 | References..... | 29 |
| Chapter 3 | Planar Zoom Module..... | 31 |
| 3.1 | Model of Planar Zoom Module (PZM)..... | 31 |
| 3.2 | Theory of Beam Expander..... | 33 |
| 3.3 | Analysis of Beam Expander..... | 37 |
| 3.3.1 | Discussion on aberrations..... | 37 |
| 3.3.2 | Simulation results..... | 37 |
| 3.4 | Fabrication Considerations..... | 38 |
| 3.4.1 | Dimensions of elements..... | 38 |
| 3.4.2 | Sorts of beam expander..... | 40 |
| 3.5 | Summary..... | 42 |
| 3.6 | Reference..... | 43 |
| Chapter 4 | Multi-Zoned Light-Enhancing Layer | 44 |
| 4.1 | Design of MZ-LEL..... | 45 |
| 4.2 | Modeling..... | 46 |
| 4.2.1 | Fresnel's equation considered..... | 46 |
| 4.2.2 | Preliminary verification using a single-pixel OLED..... | 47 |
| 4.2.3 | Examination of earlier research..... | 48 |
| 4.3 | Arrayed LEL with multi-zoned shape for OLED panel..... | 50 |

| | | |
|------------------|---|-----------|
| 4.3.1 | Model of light source..... | 50 |
| 4.3.2 | Experiment and analysis..... | 51 |
| 4.4 | Discussions..... | 53 |
| 4.5 | Summary..... | 55 |
| 4.6 | Reference..... | 56 |
| Chapter 5 | Seam Effect of Wire-Grid Polarizer..... | 57 |
| 5.1 | Investigation of seam effect by using RCWA..... | 58 |
| 5.1.1 | Review of literature..... | 58 |
| 5.1.2 | Energy conservation..... | 59 |
| 5.1.3 | Numerical Accuracy..... | 61 |
| 5.2 | Analyses of WGP patches..... | 64 |
| 5.2.1 | Wide-seam WGP..... | 64 |
| 5.2.2 | Narrow-seam WGP..... | 65 |
| 5.2.3 | Discussion..... | 67 |
| 5.3 | Summary..... | 69 |
| 5.4 | Reference..... | 69 |
| Chapter 6 | Conclusions and Future Works..... | 71 |
| 6.1 | Conclusions..... | 71 |
| 6.1.1 | Composite metal coating to enhance reflectivity..... | 71 |
| 6.1.2 | Planar zoom module for beam scaling..... | 72 |
| 6.1.3 | Multi-zoned light-enhancing layer for OLED display..... | 73 |
| 6.1.4 | RCWA of seam effect on wire-grid polarizer..... | 74 |
| 6.2 | Future works..... | 76 |
| 6.2.1 | Planar beam expander for fluorescence correlation spectroscopy..... | 76 |
| 6.2.2 | Light-enhancing layer integrated passivation..... | 78 |

| | | |
|-----------------|---|-----------|
| 6.2.3 | Planar inspection system with protein grating bio-chip..... | 81 |
| 6.3 | Reference..... | 84 |
| Appendix | Acronyms | 86 |



Figure Captions

| | | |
|-----------|--|----|
| Fig. 1-1 | Optical components in LCDs..... | 2 |
| Fig. 1-2 | Material and component cost of LCDs..... | 3 |
| Fig. 1-3 | Optical components in FPDs that correspond to planar optics..... | 3 |
| Fig. 2-1 | Concepts of planar optics: (a) typical and (b) extended forms..... | 6 |
| Fig. 2-2 | Illustration of imaging function in a typical planar optical lens..... | 8 |
| Fig. 2-3 | Phase distribution of the quantized 1-D diffractive grating..... | 12 |
| Fig. 2-4 | Unfolded planar optics with (a) original, (b) half unfolded, and (c) fully unfolded optical paths..... | 14 |
| Fig. 2-5 | Illustration of Kirthhoff approximation..... | 15 |
| Fig. 2-6 | Light propagation in a typical planar optical system: (a) perspective and (b) side views..... | 16 |
| Fig. 2-7 | Illustration of a quantized DOE lens..... | 18 |
| Fig. 2-8 | Phase difference between the 0th and the lth sub-levels in a DOE lens..... | 19 |
| Fig. 2-9 | Fabrication techniques of planar optics..... | 20 |
| Fig. 2-10 | Flowchart of the fabrication of ALEL..... | 21 |
| Fig. 2-11 | Types of imprint: (a) hot embossing, (b) UV imprinting and (c) micro-contact printing..... | 23 |
| Fig. 2-12 | Ag-Al compound reflector: (a) side and (b) top views..... | 26 |
| Fig. 2-13 | Fabrication procedures..... | 27 |
| Fig. 2-14 | Fabricated Ag-Al compound reflector with the measurement location marks..... | 28 |
| Fig. 3-1 | Side view of a planar zoom lens system..... | 32 |

| | | |
|----------|--|----|
| Fig. 3-2 | Perspective view of a planar zoom lens system: (a) the 1st and (b) the 2nd configurations..... | 33 |
| Fig. 3-3 | Two-mirror structure of a beam expander..... | 33 |
| Fig. 3-4 | Side view of a multi-magnification beam expander..... | 35 |
| Fig. 3-5 | Side view of varying the magnification between (a) the 1st and (b) the 2nd configurations..... | 36 |
| Fig. 3-6 | Ray tracing results of the (a) 1st and (b) 2nd configurations..... | 38 |
| Fig. 3-7 | Dimensions of the element for the 1st configuration..... | 39 |
| Fig. 3-8 | Transformation from a continuous-surface device to a hybrid device.. | 42 |
| Fig. 4-1 | Design of MZ-LEL: (a) profile of MZ-LEL, (b) illustration of the transmission cone of the mesa zone and (c) superimposition of the MZ-LEL on an OLED pixel..... | 46 |
| Fig. 4-2 | Photo of the MZ-LEL..... | 48 |
| Fig. 4-3 | Some simulations of an OLED with an LEL based on an earlier study. The simulation was performed by ray tracing and taking the Fresnel's equation into account..... | 49 |
| Fig. 4-4 | Optical model of OLED panel..... | 51 |
| Fig. 4-5 | Side-view of ALEL..... | 51 |
| Fig. 4-6 | Photo of an OLED panel with and without ALEL..... | 52 |
| Fig. 4-7 | Effect of the refractive index of glue..... | 53 |
| Fig. 5-1 | Side view of wire-grid polarizer..... | 59 |
| Fig. 5-2 | Illustration of WGP patches..... | 61 |
| Fig. 5-3 | Relationship between diffraction efficiency and number of calculated diffraction orders (r) for different numbers of gratings per patch ($g=1, 2, 5$)..... | 63 |
| Fig. 5-4 | Illustration of seam and grating regions..... | 64 |

| | | |
|----------|---|----|
| Fig. 5-5 | Relationship between extinction ratio W_s/P_p for a wide-seam WGP (seam width $\gg \lambda$) and a nano-seam WGP (seam width = 100 nm)..... | 66 |
| Fig. 5-6 | Relationship between the 1 st order diffraction angle and P_p/λ | 68 |
| Fig. 6-1 | System setup for sampling-volume-controlled fluorescence correlation spectroscopy (SVC-FCS)..... | 77 |
| Fig. 6-2 | Illustration of new planar beam expander..... | 77 |
| Fig. 6-3 | Fabrication of a bottom-emission OLED with an LIS: (a) pattern a transparent plate with the profile of LEL to form an LIS and (b) use the LIS as a substrate to fabricate a bottom-emission OLED..... | 79 |
| Fig. 6-4 | Fabrication procedures of a top-emission OLED with an LIS: (a) pattern the passivation as an LIS by molding techniques, (b) fabricate a top-emission OLED until the passivation process, (c) cover the LIS on the OLED, and (d) enclose the whole device..... | 80 |
| Fig. 6-5 | Illustration of OLED with 5 x 5 pixels and the LIS..... | 80 |
| Fig. 6-6 | Inspection system with a protein grating bio-chip..... | 81 |
| Fig. 6-7 | Reflective planar inspection system with protein grating bio-chip..... | 82 |
| Fig. 6-8 | Transmissive planar inspection system with protein grating bio-chip... | 83 |

List of Tables

| | | |
|-----------|---|----|
| Table 2.1 | Performance parameters of metal films on fused silica for $\lambda = 850$ nm..... | 26 |
| Table 4.1 | Comparison of different structures with and without the Fresnel's equation..... | 50 |
| Table 5.1 | Comparison of RCWA and FDTD for ideal WGP..... | 67 |

